


Salad & Sandwich Prep Table - Mega Top Refrigerator With Drawers



Features

- CFC free refrigerant and foam insulation.
- Equipped with an electronic thermostat and digital LED temperature display for precise control and convenient reading.
- Features a self-closing swing door for added convenience.
- The magnetic gasket can be replaced without the need for any tools.
- External construction comprises stainless steel framework.
- Internally constructed with 304 stainless steel.
- Incorporates auto defrosting and auto evaporation mechanisms to prevent condensation.
- The coated copper tube, boasting a sturdy 0.7mm thickness, ensures durability.
- Crafted from a single bent tube, minimizing the risk of leaks with only two welding joints.
- The condenser is efficiently positioned inside the condensation pan to facilitate the evaporation of excess water.
- Dispose of daily waste effortlessly with the stainless steel baseplate that lifts easily.
- Adjustable and heavy-duty epoxy-coated wire shelves for flexible storage options.
- Includes 1/6 size polycarbonate GN pans and a plastic cutting board.
- Comes with easy-to-mount 4" casters (front casters equipped with brakes), standard with all units.
- Electrical specifications: 115/60/1 with a NEMA 5-15P plug and a 10ft cord.



Temperature

- Interior temperature range: 1°C to 4°C (33°F to 40°F)

Warranty

- 3 years parts and labour
- 5 years compressor warranty



CSSU-36M-2D
CSSU-48M-2D
CSSU-60M-2D



CSSU-36M-4D
CSSU-48M-4D
CSSU-60M-4D



CSSU-29M-2D



CSSU-72M-2D



CSSU-72M-4D



CSSU-72M-6D

Specifications

Model	Doors & Drawers	1/6 Size Pans	Ext. Dimensions W x D x H (in)	V/Hz/Ph	AMPS	Power	Storage Capacity(cu-ft)	NEMA PLUG	Ship Weight(lbs)	Ship Data W x D x H (in)
CSSU-29M-2D	0&2	12	29 x 36 1/2 x 35 5/8 (42 1/2)	115/60/1	3	250W/0.34HP	8.5	5-15	278	32 1/8 x 37 1/5 x 47 5/8
CSSU-36M-2D	2&2	15	36 1/4 x 36 1/2 x 35 5/8 (42 1/2)	115/60/1	3	300W/0.40HP	11.5	5-15	322	39 2/5 x 37 1/5 x 47 5/8
CSSU-36M-4D	0&4	15	36 1/4 x 36 1/2 x 35 5/8 (42 1/2)	115/60/1	3	300W/0.40HP	11.5	5-15	355	39 2/5 x 37 1/5 x 47 5/8
CSSU-48M-2D	1&2	18	48 1/4 x 36 1/2 x 35 5/8 (42 1/2)	115/60/1	4	380W/0.51HP	15	5-15	352	51 2/5 x 37 1/5 x 47 5/8
CSSU-48M-4D	0&4	18	48 1/4 x 36 1/2 x 35 5/8 (42 1/2)	115/60/1	4	380W/0.51HP	15	5-15	385	51 2/5 x 37 1/5 x 47 5/8
CSSU-60M-2D	2&2	24	61 1/8 x 36 1/2 x 35 5/8 (42 1/2)	115/60/1	4.5	400W/0.54HP	20	5-15	424	64 2/5 x 37 1/5 x 47 5/8
CSSU-60M-4D	0&4	24	61 1/8 x 36 1/2 x 35 5/8 (42 1/2)	115/60/1	4.5	400W/0.54HP	20	5-15	455	64 2/5 x 37 1/5 x 47 5/8
CSSU-72M-2D	2&2	30	71 3/4 x 36 1/2 x 35 5/8 (42 1/2)	115/60/1	4.5	400W/0.54HP	23	5-15	485	75 x 37 1/5 x 47 5/8
CSSU-72M-4D	1 & 4	30	71 3/4 x 36 1/2 x 35 5/8 (42 1/2)	115/60/1	4.5	400W/0.54HP	23	5-15	518	75 x 37 1/5 x 47 5/8
CSSU-72M-6D	0&6	30	71 3/4 x 36 1/2 x 35 5/8 (42 1/2)	115/60/1	4.5	400W/0.54HP	23	5-15	551	75 x 37 1/5 x 47 5/8



If the data and structure update, without notice, subject to material object.