

Walk-In Coolers & Freezers

With Top Mounted Compressor



Features

- Constructed with modular 3 or 4 inch thick panels with EPA-compliant polyurethane insulation
- Walls are constructed from 26 gauge corrosion-resistant steel
- Floors are constructed with 26 gauge corrosion-resistant steel and anti-slip aluminium covering
- Temperature: 0 degrees Celcius (coolers), -20 degrees Celcius (freezers)
- Ceiling mounted Kideblock refrigeration system included (ETL listed)
- Easy installation, constructed for indoor use
- Air-cooled condensing unit
- Electronic control provided for automatic defrost
- 36" W x 84" H self-closing door with heavy-duty hinges
- Door(s) are constructed with perimeter door heater wire and magnetic gasket
- LED lights
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- Hardwire connection required
- Warranty: 1 year warranty on parts and labour, 1 additional year provided for parts



Cooler and freezer units can be combined
 Custom sizes available for order

SPECIFICATIONS

MODEL	EXT. DIMENSIONS W x D x H (FT)	SYSTEM	TEMP (C)	V/Ph/HZ	HP	AMPS	KW
Coolers (floorless) and 3" Thick Panels							
WT-663R	6 x 6 x 8.5	EMR1009M2Z	0	230/1/60	0.75	6.9	0.5
WT-683R	6 x 8 x 8.5	EMR1009M2Z	0	230/1/60	0.75	6.9	0.5
WT-883R	8 x 8 x 8.5	EMR1009M2Z	0	230/1/60	0.75	6.9	0.5
WT-8103R	8 x 10 x 8.5	EMR2016M2Z	0	230/1/60	1.5	10.4	1.1
WT-10103R	10 x 10 x 8.5	EMR2016M2Z	0	230/1/60	1.5	10.4	1.1
Freezers (with floor) and 4" Thick Panels							
WT-664F	6 x 6 x 8.5	EMR1016L2Z	-20	230/1/60	1.5	7.2	1.1
WT-684F	6 x 8 x 8.5	EMR1016L2Z	-20	230/1/60	1.5	7.2	1.1
WT-884F	8 x 8 x 8.5	EMR2018L2Z	-20	230/1/60	2	15.7	1.5
WT-10104F	10 x 10 x 8.5	EMR3018L2Z	-20	230/1/60	2.5	17	1.9



Certified To ANSI/NSF 7 Standards
 If the data and structure update, without notice, subject to material object



Hardwired
 This product must be hardwired by a professional; it does not plug into a standard wall outlet.