Under Counter Refrigerator

Features

- -CFC free refrigerant and foam insulation.
- -Equipped with an electronic thermostat and digital LED temperature display for precise control and convenient reading.
- -Features a self-closing swing door for added convenience.
- -The magnetic gasket can be replaced without the need for any tools.
- -External construction comprises stainless steel framework.
- -Internally constructed with 304 stainless steel.
- -Incorporates auto defrosting and auto evaporation mechanisms to prevent condensation.
- -The coated copper tube, boasting a sturdy 0.7mm thickness, ensures durability.
- -Crafted from a single bent tube, minimizing the risk of leaks with only two welding joints.
- -The condenser is efficiently positioned inside the condensation pan to facilitate the evaporation of excess water.
- -Adjustable and heavy-duty epoxy-coated wire shelves for flexible storage options.
- -Comes with easy-to-mount 4" casters (front casters equipped with brakes), standard with all units.
- -Electrical specifications: 115/60/1 with a NEMA 5-15P plug and a 10ft cord.

Temperature

- -Interior temperature range: 1°C to 4°C (33°F to 40°F)
- -Ambient temperature upto 45°C (113°F)

Warranty

-3 years parts and labour

5 years compressor warranty







welding joint

nterface



Specifications

Model	Door	Ext. Dimensions s W x D x H (in)	Int Dimensions W x D x H (in)	Shelves	V/Hz/Ph	AMPS	S Power	Storage Capacity(cu./ft)	NEMA PLUG	Ship Weight(I	Ship Data bs) W x D x H (in)
CUC27	1	27 3/4 x 29 7/8 x 35 5/8	24 x 24 x 24 3/8	2	115/60/1	3	250W/0.34H	HP 6.5	5-15P	210	32 1/8 x 33 3/8 x 39
CUC36	2	36 1/4 x 29 7/8 x 35 5/8	32 1/2 x 24 x 24 3/8	2	115/60/1	3	300W/0.41H	IP 9	5-15P	225	39 1/2 x 33 3/8 x 39
CUC48	2	48 1/4 x 29 7/8 x 35 5/8	42 7/8 x 24 x 24 3/8	2	115/60/1	4	380W/0.51H	IP 12	5-15P	284	51 1/2 x 33 3/8 x 39
CUC60	2	61 1/8 x 29 7/8 x 35 5/8	55 7/8 x 24 x 24 3/8	2	115/60/1	4	380W/0.51H	IP 15	5-15P	335	64 1/2 x 33 3/8 x39
CUC72	3	71 3/4 x 29 7/8 x 35 5/8	66 3/8 x 24 x 24 3/8	2	115/60/1	4.5	400W/0.54	HP 18	5-15P	397	75 x 33 3/8 x 39

















Under Counter Refrigerator

















29 7/8" (760 mm)

