EXPLORER Mobile Gateway

Beyond Line-Of-Sight Push-To-Talk and Data Communication

June 2020 Product Sheet



Beyond Line-Of-Sight Communication

EXPLORER Mobile Gateway is an IP-based radio and data communications device that supports satellite/3G/LTE/LAN backhaul and Land Mobile Radio (LMR) integration to provide seamless switching between available networks in any situation. It is a cost-effective system designed to expand and augment traditional LMR systems widely used in the Public Safety, Utility, Mining, and Oil & Gas sectors.


The network agnostic multi-bearer solution extends legacy Push-To-Talk capabilities to hybrid data networks such as terrestrial cellular networks (where available), supplemented by satellite where no terrestrial network coverage is present. With no user intervention required, the system automatically routes voice and data traffic via the most reliable network available.

Enhanced Capabilities

EXPLORER Mobile Gateway solves many challenges faced by traditional LMR system operators:

- Coverage area can be extended by using satellite and existing cellular-based networks
- Lowers expensive terrestrial infrastructure costs
- High availability to support critical communications
- Scalable from two to thousands of units
- Seamless switching between available satellite, cellular, and LAN connectivity ensures constant communications
- Compatibility with many different brands of land mobile radios.
- SIP integration to any existing infrastructure
- Voice compression technologies are used to allow for the most efficient use of bandwidth across multiple transport mediums.
- 256-bit AES-CTR encryption





PRISM PTT⁺ integrates the EXPLORER Mobile Gateway into a fully Cobham-managed flat-rate solution, including access to the PRISM Portal and 24/7 support.

The look and feel of the included Control Speaker Microphone is exactly like a simple legacy Push-To-Talk handset. The vehicle installation of the system requires an on-the-move satellite terminal and the EXPLORER Mobile Gateway. Up to two cellular modems can be connected to the EXPLORER Mobile Gateway, allowing for independent network connections. The all-important automatic routing functionality enables seamless switching between the available networks.

Cobham PRISM PTT+ Service

The EXPLORER Mobile Gateway is managed and configured in the Cobham-managed PRISM Portal. The web-based portal ensures a simple and easy configuration of any EXPLORER Mobile Gateway, no matter its location and with over-the-air updates to vehicles. Access to the PRISM Portal is bought separately (item no. 650000-001).

The portal offers a long list of functionalities, e.g.:


- Quick configuration of talk groups
- Preconfigured E&M radio interfaces for most existing LMR/DMR radios
- Easy duplication of configuration across EXPLORER Mobile Gateways
- User-friendly configuration of tracking and AGC settings
- Recording of all voice in one or more talk groups
- Advanced routing configuration for critical applications

EXPLORER Mobile Gateway



Beyond Line-Of-Sight Push-To-Talk and Data Communication

- A ruggedized and easy to use digital Push-To-Talk communication solution.
- Designed to cost effectively expand and augment Land Mobile Radio systems.
- Built-in support for LMR devices to ensure over-the-horizon radio communication.
- Voice-over-IP technologies optimized for use under difficult satellite or terrestrial link conditions.
- Automatic voice and data routing between cellular (2G/3G/LTE) and satellite networks.
- Beyond Line-Of-Sight communication global coverage.



15 PIN D-SUB Input/Output				
1	Line In +	600 Ohm input		
2	Line Out +	600 Ohm output		
3	+12 VDC output	Fused, max. 100 mA		
4	Input 1	PTT, active low		
5	Input 2	General purpose digital input		
6	Audio+	Amplified audio output 4-16 Ohm (1 W)		
7	Output 1	PTT, push/pull 12 V		
8	Output 2	Open drain		
9	Service port (out)	UART, RS-232 levels		
10	Service port (in)	UART, RS-232 levels		
11	GND	Ground		
12	Audio-	Amplified audio output		
13	GND	Ground		
14	Line Out -	Ground		
15	Line In -	Ground		

On/off

Volume

		A1	DC
		A2	DC
		1	Igr
		2	Со
ut		3	Ge
		4	Со
		5	Со
-			
	Specifica		
		Dimen:	

	`			
A1	DC+			
A2	DC-			
1	Ignition			
2	Common. Connected to pin 4 or pin 5.			
3	General purpose open drain output. Max. 300			
4	Connected to pin 2 when the PTT unit is on.			
5	Connected to pin 2 when the PTT unit is off.			
Specifications				
Dimensions (H / W / D):				
EXPLORER Mobile Gateway: 41 / 223 / 175 mm				

Difficusions (II / W / D).					
EXPLORER Mobile Gateway:	41 / 223 / 175 mm				
(Terminal)	1.6 / 8.8 / 6.9 inches				
EXPLORER 6205 CSM:	148 / 67 / 40 mm				

5.8 / 2.6 / 1.6 inches

Weight:

EXPLORER Mobile Gateway: 1 kg / 2.3 lbs EXPLORER 6205 CSM: 375 g / 0.8 lbs

Services:

Push-To-Talk Voice: Group call, Dispatch call IP Service: Seamless switching of IP Data

-15° to +55°

-40° to +80°

Approvals: CE, GMPCS, FCC

GROUP 3 PTT button **Environmental conditions**

4 Control buttons

Jogwheel selector

- Menu Home
- Menu Shift

LCD Display

- Network status

- Current Group

- Connection status

- Replay

Distress button on the rear

Ingress Protection:

Temperature:

Operational:

EXPLORER Mobile Gateway: IP31 EXPLORER 6205 CSM:

Power

Power supply:

EXPLORER Mobile: Gateway Nominal 12-24 VDC Operating 10.5-32 VDC EXPLORER 6205 CSM: Powered by the gateway

Power consumption:

Max wattage: 38W Typical use:

Interfaces

1 x LAN interface:

Connector type: RJ-45 Data rate: 10/100 Mbps API integration: Supported

1 x I/O interface:

15 pin D-SUB connector containing: Connector type:

Loudspeaker output, Audio in, Audio out, PTT in, PTT out, serial port, 4-wire E&M interface

2 x USB:

300 mA

Connector type: USB host for Cellular Modems

1 x Microphone:

Connector type:

12 pin LTW connector for the EXPLORER 6205 Control Speaker Microphone

User interface:

Handset (CSM):

Power On/Off, PTT button, 4 control buttons, 40x30mm Display, Jogwheel selector, Dimmer (display backlight),

Distress button

Product number

403648A-00500 **EXPLORER Mobile Gateway**

Related Products

650000-001 Cobham PRISM Managed Service 403723A-00500 **EXPLORER 323 Terminal** 403706A-050 **EXPLORER Connection Box**

For further information please contact:

Cobham SATCOM Land Lundtoftegaardsvej 93 D DK-2800 Kgs. Lyngby, Denmark

Tel: +45 3955 8800

Subject to change without notice