

Chassis Set-Up Sheet

	SWAY BA	R DIA.	LOAD	ON BAR			DATE:	
						DE	PLACE:	
LF CASTER		TOW	OUT	CASTER .		RF_	TIRE SIZES TIRE STAGGER	
CAMBER				CAMBER			TIKE SIZES TIKE STAGGEN	
CAIVIBER				CAIVIBER				
SHOCK BRAND:				SHOCK BE	RANE):		
VALVING:				VALVING:				
SPRING RATE	MEASURE			SPRING R	ATE	MEASURE		
		FRO						-
			#				THIRD LINK	
L			%	(<u></u>	/ 8 \	
#	LF		 F	RF			• • •	
					-			
LEFT SIDE		40 MARKS					TRAILING ARM POSITIONS	
	LR		F	RR			L	
#1		1					R	
" %							1-6-	
WEDGE			#				1	
			%					
LR		REAR RR				R	PANHARD ROD FRONT REAR	٦
			Ī	SHOCK BR			FRONT REAR	
SHOCK BRAND: VALVING:			8	VALVING:	AND	•		
	AE A CUIDE		-		TE T	MEASURE	&	
SPRING RATE N	MEASURE			SPRING RA	IE	MEASURE	╎╿┟┷┧	4
			1		-			لـ
			ŀ		\dashv		RIDE HEIGHT	
		NOT	- L		60,4 90,0		0\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
		NOTI	<u> </u>				L R&L B	
							R \	
								_
							TIRES	
							GOODYEAR McCREARY	
						HOOSIER OTHER	_	
							COMPOUND	_
							GEAR SET	

LAPS

PRACTICE: _____

MAIN EVENT: __ TOTAL ON ENGINE: __