

# INSTALLATION INSTRUCTIONS

Doc#M530-09-K3



## MWL-530-09/530-09B



### FITMENT:

Fits Dyna Models 06-UP & Street Bob Models 09-2017

**MAX CAPACITY:** 10 lbs

**MATERIAL:** 3/8" Solid steel & 1/2" tubing outside

### TECHNICAL SPECS:

May require a fender/seat

**WELCOME:** These instructions describe the procedure for properly installing the Motherwell Products Solo Luggage Rack.

### ATTENTION INSTALLER (if other than owner):

Please forward this instruction sheet to the purchaser of this product as it contains valuable information necessary to the end user.

**CAUTION:** Start screw carefully to avoid cross threading.

### USE AND CARE:

Wash your accessories with the same care you use when washing your motorcycle. Use mild soap and water. DO NOT use abrasive chemicals, cleaners.

### WARNING:

Never carry more than 10 lbs. on rack, and always secure cargo properly. Failure to do so can affect handling. Make sure neither cargo straps are loose and come in contact with moving parts, i.e., wheels, brakes, etc...

### TOOLS REQUIRED:

#2 Phillips Screw Driver  
Kit #3

### PARTS INCLUDED:

Luggage Rack  
2 Phillips 3/4" Pan Head Screw  
2 1/4 Bond Seal S/S  
1 Foam Tab

### MWL Part #:

FAS-009, FAS-057, FOAM-AFT, FOAM-FWD

### MOUNTING PROCEDURE:

- 1) Remove Pillion seat.
- 2) Install foam tabs on back and front of the rack.
- 3) Place rack on fender mounting points. (The forward mount sits on top of the driver's seat)
- 4) Install the stock screw into rear pick up point on the rack. (DO NOT TIGHTEN)
- 5) For the front mount, place the nylon washer on the rack with the stainless steel washer on top.
- 6) From there insert the supplied Phillips screw loosely.
- 7) Proceed to tighten both screws down.

Great Rides Start With Motherwell

Motherwell Products USA, Inc  
7074 Portal Way #140  
Ferndale, WA 98248  
Toll Free (877) 703-7118  
[www.motherwellproducts.com](http://www.motherwellproducts.com)