

PRODUCT SPECIFICATION REPORT

No. 1 prevents asphalt from sticking to surfaces. No. 1 can be use with polymer modified SMA designs, crumb rubber designs, warm mix designs, most PG mix designs and conventional designs.

NO. 1 ASPHALT RELEASE AGENT

Asphalt Release Agent

PROD. #4336



F	F/	ΔΤ	U	R	FS	/R	FN	JF	FI	TS:	,
	L	N I.	υ		LJ	שו				1	•

Excellent Release Properties	Can be used with virtually all mix-designs.
Concentrated	For best results, use with a 15:1 dilution ratio for conventional mixes and as a straight ready-to-use for sticky mixes.
Safe	Water-based inert chemistry will not harm asphalt, trucks or equipment. It will not strip hot asphalt or affect the paved mat.
DOT Approved	Please check local State DOT guidelines & approval list.

APPLICATIONS:

Can be used on transportation vehicles such as dump trucks, dump trailers, flow-boys, live bottom trailers, & hopper trailers. Can be used on paving equipment such as asphalt pavers, rubber-tired rollers, material transfer vehicles (MTVs), & windrow elevators.

COMPANION PRODUCTS:

Zep 45 DualForce Penetrant & Lubricant, Zep 45 Sidewinder Super Penetrant, Shell Shock Walnut Hand Cleaner, MVP Waterless Hand Cleaner, Cherry Bomb Industrial Hand Wipes, Soy Response Soy-Based Solvent Degreaser (Liquid & Aerosol), Big Orange Citrus Degreaser (Liquid & Aerosol).

SPECIFICATIONS:

Physical Form	Liquid				
Color	Amber				
Odor	Mild				
рН	7-9				
Flammability	Non-flammable				
D.O.T. Shipping Label	Not Regulated				

PACKAGING: Bulk Delivery

Zep Sales & Service www.zep.com 1-877 I BUY ZEP