



PRODUCT SPECIFICATION REPORT

BMF provides a protective barrier between asphalt and a surface, thus preventing asphalt from sticking to surfaces. BMF is designed for use on polymer modified SMA designs, crumb rubber designs, warm mix designs, most PG mix designs and conventional designs. BMF is used to coat transportation vehicles such as dump trucks, dump trailers, live bottom trailers & hopper trailers.

BMF ASPHALT RELEASE AGENT PROD. #4369

Asphalt Release Agent



FEATURES/BENEFITS:

Excellent Release Properties	For best results, dilute 5:1 for sticky mixes and 15:1 for conventional mixes
Water Based Inert Chemistry	Will not harm asphalt, trucks or equipment. It will not strip hot asphalt or affect the paved mat
DOT Approved	Meets the Department of Transportation requirements for all 50 states*

APPLICATIONS:

Used as a release agent to prevent asphalt from sticking to the bed of the truck, tools, and other equipment. For asphalt manufacturers, road paving crews, trucking companies.

COMPANION HARDWARE:

- ARA0001 Asphalt Release Arch Complete System
- ARA0002 Asphalt Release Dual Arch Complete System
- ARA0008 Asphalt Release Mounted System Push Button
- ARA0009 Asphalt Release Manual Sprayer

COMPANION PRODUCTS:

- Asphalt Remover – Big Orange, Lemon Clear, Soy Response
- Hand Cleaner – MVP, Cherry Bomb

SPECIFICATIONS:

Physical Form	Liquid
Odor	Sweet
Color	Amber
pH	8.5 - 10
Flammability	Non-Flammable
D.O.T. Shipping Label	Not Regulated

PACKAGING:

- 5 Gallon Pail
- 55 Gallon Drum
- 275 Gallon Totes

Zep Sales & Service
www.zep.com
1-877 | BUY ZEP

* Pending approval for Minnesota