

Section 1 - Identification

Product Name: Stick It Nail Glue

Product Sku: NG01

Company: **Kiara Sky Professional Nails Inc.**
8700 Swigert Ct. Ste. 109-209
Bakersfield, CA 93311

Company Number: (661)393-4800

Emergency Contact: CHEMTEL **Contract:** MIS2294037

Emergency Phone: (800)255-3924 **Outside of U.S.:** (813)248-0585

Section 2 - Hazards Identification

GHS classifications

Health: Eye Irritation, Category 2A
Skin irritation, Category 2
Target Organ Toxicity (Single exposure),
Category 3 Skin Sensitization, Category 1

Physical: Flammable Liquids, Category 4

GHS label elements

Note: If this product is a consumer product it is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.

Hazard pictograms:



Signal Word: WARNING

Hazard statements: H227: Combustible liquid.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.

Precautionary statements

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash skin and hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P313: Get medical advice/attention.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P337+P313: If eye irritation persists: Get medical advice/attention.
P362: Take off contaminated clothing.
P370: In case of fire: Use dry chemical, foam or carbon dioxide to extinguish.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.
P403+P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

Section 3 - Composition/Information on Ingredients

Ingredient name:	CAS number:	Wt. %
Ethyl Cyanoacrylate	7085-85-0	80 - 100
Polymethyl methacrylate	9011-14-7	10 - 20
Hydroquinone	123-31-9	< 0.1

Section 4 - First Aid Measures

Description of necessary first aid measures

Eye contact:

Immediately flush eyes with large quantities of water for several minutes, while holding eyelids apart. Remove contact lenses if easy to do so. Continue rinsing. Get medical attention if irritation or bonding occurs.

Skin contact:

Wash with soap and water. Peel or roll skin apart.

Ingestion:

Peel or roll skin apart. Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Avoid swallowing solid adhesive after detachment. Not a toxic product.

Inhalation:

Remove to fresh air. Prolonged or repeated elevated exposure may cause allergic reactions with asthma-like symptoms in sensitive individuals.

Over-exposure signs/symptoms

Eye contact:

Immediately flush eyes with large quantities of water for several minutes, while holding eyelids apart. Remove contact lenses if easy to do so. Continue rinsing. Get medical attention if irritation or bonding occurs.

Skin contact:

Bonds skin in seconds. May cause skin irritation. May cause sensitization by skin contact. Cyanoacrylates generate heat on polymerization, so very large amounts will burn the skin.

Ingestion:

Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Not a toxic product.

Inhalation:

Prolonged or excessive inhalation may cause respiratory tract irritation.

Acute Effects:

Avoid exposure to vapor concentration in confined areas.

Chronic Effects:

Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

Section 5 - Fire-fighting measures

General hazard:	Combustible liquid and vapor. Product polymerized to solid by water.
Extinguishing media:	Use dry chemical extinguisher or flush with large amounts of water.
Hazardous composition products:	Can burn in fire, releasing irritating vapors.
Explosion hazard:	None known.
Fire fighting procedures:	Evacuate area and fight fire from a safe distance.
Fire fighting equipment:	As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.
Fire explosion:	None known.
Sensitive to static discharge:	None known.
Sensitivity to impact	None known.
Hazardous decomposition products:	Combustible by-products of carbon monoxide/dioxide.

Section 6 - Accidental release measures

Methods and materials for containment and cleaning up

Small spill :

Polymerize with water. Solid material may be scraped from surface.

Large spill:

Polymerize with water. Increase ventilation to area. Solid material may be scraped from surface.

Section 7 - Handling and storage

Precautions for safe handling

General procedures:

Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

Handling:

Avoid breathing (dust, vapor, mist, gas). Avoid contact with skin, eyes and clothing. Keep container closed when not in use.

Storage:

Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition.

Storage temperature:

Ideal storage: 41-50F (5-10C)

Shelf life:

One year from the date of shipment from Kiara Sky Professional Nails, unless otherwise noted.

Section 8 - Exposure controls/personal protection

Exposure guidelines

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)

EXPOSURE LIMITS

Chemical Name	ETHYL-2-CYANO ACRYLATE	ppm	mg/m3
Ethyl Cyanoacrylate	OSHA PEL	TWA	[1]
	ACGIH TLV	TWA	0.2
	Supplier OEL	TWA	0.2 ppm
Hydroquinone	ACGIH TLV	TLV (DSEN)	1
	OSHA PEL	TWA	2

OSHA TABLE COMMENTS:

1. NL = Not Listed

Engineering controls:

Use only in a well ventilated area. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

Personal protective equipment

Eyes and face: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin: Use Nitrile gloves and aprons to prevent contact. Do not use PVC, Nylon or Cotton materials.

Respiratory: Use only in a well-ventilated area. In case of insufficient ventilation, wear suitable respiratory equipment. Recommended: Full-face NIOSH-approved respirator with organic vapor cartridge.

Work hygienic practices: Avoid direct contact and breathing vapor. Use with adequate ventilation. Wash hands with soap and water after use.

Other use precautions: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Section 9 - Physical and chemical properties

Appearance

Physical state:	Liquid.
Odor:	Characteristic odor, intensely irritating.
Odor threshold:	Odor Threshold = 1 ppm
Appearance:	Transparent, colorless liquid.
pH:	No data available.
Percent volatile:	No data available.
Flash point and method:	80°C (176°F) to 93.4°C (200°F) TAG CC
Flammable limits:	No data available.
Autoignition temperature:	485°C (905°F)
Vapor pressure:	< 0.2 mm Hg
Vapor density:	No data available.
Boiling point:	> 149°C (300°F)
Freezing point:	No data available.
Melting point:	No data available.

Thermal decomposition:	No data available.
Solubility in water:	Insoluble
Partition coefficient: N-Octanol/water:	No data available.
Evaporation rate:	No data available.
Density:	No data available.
Specific gravity:	1.06 g/mL at 25°C
Viscosity #1:	25 to 50 Centipoise at 22°C (72°F)
Molecular weight (VOC):	No data available. < 20.00 g/L Per SCAQMD Method 316B.

Section 10 - Stability and reactivity

Hazardous polymerization:	No
Conditions to avoid:	Avoid temperatures above 176°F (80°C), moisture and alkalines.
Possibility of hazardous reactions:	Possible polymerization reaction in the presence of water, amines, alkalis and alcohols.
Hazardous decomposition products:	Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition. Oxides of nitrogen and probably hydrogen cyanide are also possible.
Incompatible materials:	Strong oxidizers, peroxides, strong acids, alkalis. Amines, strong oxidizing agents, strong bases, oxygen scavengers.
Comments:	REACTIVITY: Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

Section 11 - Toxicological information

Information on toxicological effects

Acute toxicity

Respiratory or skin sensitisation: Possible skin sensitizer.

Carcinogenicity:

IARC: None known.

NTP: None known

OSHA: None known

This product has not been tested on animals to obtain toxicology data. Products components' toxicology data were found in scientific literatures. This data may or may not be present in this document.

Section 12 - Ecological information

Environmental data:

This material should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

Section 13 - Disposal considerations

Disposal methods: Dispose of in a manner consistent with federal, state, and local regulations.

Section 14 - Transport information

DOT (Department of Transportation)

Proper shipping name: NOT REGULATED

AIR (ICAO/IATA)

Proper shipping name: ID8000, CONSUMER COMMO DITY, 9 (PKG LESS THAN OR EQUAL TO 30 kg G); or UN3334, AVIATION REGULATED LIQUID, N.O.S (ETHYL CYANOACRYLATE), 9, III (LTD QTY, IP VO L LESS THAN OR EQUAL TO 5.0 L, OP WGT LESS THAN OR EQUAL TO 30 kg G) *

VESSEL (IMO /MDG)

Shipping name: NOT REGULATED

Comments: * This product may be shipped as EXCEPTED QUANTITIES OF CLASS 9, UN3334 (IP VOL LESS THAN OR EQUAL TO 0.03 L, OP VOL LESS THAN O R EQUAL TO 1.0 L)

The transport information provided in this section only applies to the material formulation/itself, and is not specific to any package/configuration. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organizations to follow all applicable laws, regulations, and rules relating to the transportation of the material.

Section 15 - Regulatory information

United States

SARA TITLE III (Superfund Amendments and Reauthorization Act)

311/312 HAZARD CATEGORIES: Immediate Health, Delayed Health, Fire, Reactive.

313 REPORTABLE INGREDIENTS: None above reporting de minimus.

302/304 EMERGENCY PLANNING :

Emergency Plan: None above reporting de minimus.

TSCA (Toxic Substance Control Act)

Chemical Name	CAS
Ethyl Cyanoacrylate	7085-85-0
Polymethyl methacrylate	9011-14-7
Hydroquinone	123-31-9

TSCA status: All components are listed on or are exempt from listing on the Toxic Substances Control Act.

CLEAN AIR ACT

40 CFR PART 68---Risk Management for Chemical Accident Release Prevention: Not applicable.

Section 16 - Other information

Title: Regulatory Department


Hazardous Material Information System (U.S.A.)

Health	2
Flammability	2
Physical hazards	1
Personal protection	

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Kiara Sky Professional Nails Inc., does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.