

## Section 1 - Identification

**Product Name:** Superior Bond Acrylic Primer  
**Product Sku:** APRIME  
**Product Type:** Liquid.  
**Company:** **Kiara Sky Professional Nails Inc.**  
8700 Swigert Ct. Ste. 109-209  
Bakersfield, CA 93311

## Section 2 - Hazards Identification

**OSHA/HCS status:** This material is considered hazardous by the OSHA Hazard Communication Standard. (29 CFR 1910.1200).

**Classification of the substance or mixture:** FLAMMABLE LIQUIDS - Category 2  
SKIN IRRITATION - Category 2  
EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)  
(Narcotic effects) -Category 3  
Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 37%  
Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 99.8%  
Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 99.8%

### GHS label elements

**Hazard pictograms:**



**Signal Word:** Danger

**Hazard statements:** Highly flammable liquid and vapor.  
Causes serious eye irritation.  
Causes skin irritation.  
May cause an allergic skin reaction.  
May cause drowsiness and dizziness.

### Precautionary statements

#### **Prevention:**

Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

#### **Response:**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**Storage:** Store locked up. Store in a well-ventilated place. Keep cool.

**Disposal:** Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazards not otherwise classified:** None known.

### ***Section 3 - Composition/Information on Ingredients***

**Substance/mixture:** Mixture

**Other means of identification:** Not available.

#### **CAS number/other identifiers**

**CAS number:** Not applicable.

| <b>Ingredient name:</b>     | <b>CAS number:</b> | <b>EC number:</b> | <b>INCI Name:</b> | <b>%</b>  |
|-----------------------------|--------------------|-------------------|-------------------|-----------|
| 2-hydroxyethyl methacrylate | 868-77-9           | 212-782-2         | HEMA              | ≥25 - ≤50 |
| ethyl acetate               | 141-78-6           | 205-500-4         | ETHYL ACETATE     | ≥25 - ≤50 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

### ***Section 4 - First Aid Measures***

#### **Description of necessary first aid measures**

##### **Eye contact:**

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

##### **Inhalation:**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

##### **Skin contact:**

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

##### **Ingestion:**

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

## **Most important symptoms/effects, acute and delayed**

### **Potential acute health effects**

|                      |  |
|----------------------|--|
| <b>Eye contact:</b>  | Causes serious eye irritation.   |
| <b>Inhalation:</b>   | Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. |
| <b>Skin contact:</b> | May cause an allergic skin reaction.   |
| <b>Ingestion:</b>    | Can cause central nervous system (CNS) depression.                                     |

### **Over-exposure signs/symptoms**

|                      |  |
|----------------------|--|
| <b>Eye contact:</b>  | Adverse symptoms may include the following: pain or irritation, watering, redness  |
| <b>Inhalation:</b>   | Adverse symptoms may include the following: nausea or vomiting, headache, dizziness/vertigo, drowsiness/fatigue, unconsciousness |
| <b>Skin contact:</b> | Adverse symptoms may include the following: redness, irritation  |
| <b>Ingestion:</b>    | No specific data.  |

## **Indication of immediate medical attention and special treatment needed, if necessary**

|                                    |   |
|------------------------------------|---|
| <b>Notes to physician:</b>         | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.   |
| <b>Specific treatments:</b>        | No specific treatment.  |
| <b>Protection of first-aiders:</b> | No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

## ***Section 5 - Fire-fighting measures***

### **Extinguishing media**

|  |  |
|--|--|
| <b>Suitable extinguishing media:</b>                   | Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.   |
| <b>Unsuitable extinguishing media:</b>                 | Do not use water jet.  |
| <b>Specific hazards arising from the chemical:</b>     | Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.   |
| <b>Hazardous thermal decomposition products:</b>       | Decomposition products may include the following materials:<br>carbon dioxide, carbon monoxide   |
| <b>Special protective actions for fire-fighters:</b>   | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. |
| <b>Special protective equipment for fire-fighters:</b> | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.  |

## ***Section 6 - Accidental release measures***

### **Personal precautions, protective equipment and emergency procedures**

#### **For non-emergency personnel:**

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

#### **For emergency responders:**

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **Environmental precautions:**

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### **Methods and materials for containment and cleaning up**

#### **Small spill :**

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### **Large spill:**

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## ***Section 7 - Handling and storage***

### **Precautions for safe handling**

#### **Protective measures:**

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### **Advice on general occupational hygiene:**

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### **Conditions for safe storage, including any incompatibilities:**

Shield UV light sources. Store between the following temperatures: 13 to 27°C (55.4 to 80.6°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8 - Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name             | Exposure limits  |
|-----------------------------|--|
| 2-hydroxyethyl methacrylate | None.  |
| Ethyl acetate               | <b>ACGIH TLV (United States, 3/2017).</b><br>TWA: 400 ppm 8 hours.<br>TWA: 1440 mg/m <sup>3</sup> 8 hours.<br><b>OSHA PEL 1989 (United States, 3/1989).</b><br>TWA: 400 ppm 8 hours.<br>TWA: 1400 mg/m <sup>3</sup> 8 hours.<br><b>NIOSH REL (United States, 10/2016).</b><br>TWA: 400 ppm 10 hours.<br>TWA: 1400 mg/m <sup>3</sup> 10 hours.<br><b>OSHA PEL (United States, 6/2016).</b><br>TWA: 400 ppm 8 hours.<br>TWA: 1400 mg/m <sup>3</sup> 8 hours. |

#### Appropriate engineering controls:

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Environmental exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

##### Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

##### Eye/face protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

##### Skin protection

###### Hand protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

###### Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection:**

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection:**

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## ***Section 9 - Physical and chemical properties***

**Appearance**

|   |  |
|---|--|
| Physical state:                               | Liquid.                                      |
| Color:  | Colorless.                                   |
| Odor:   | Ester.                                       |
| pH:   | Not available.                               |
| Melting point:                                | Not available.                               |
| Boiling point:                                | 77.1°C (170.8°F)                             |
| Flash point:                                  | Closed cup: -3.3°C (26.1°F) [Tagliabue.]     |
| Lower and upper explosive (flammable) limits: | Lower: 0.04%                                 |
| Vapor pressure:                               | Not available.                               |
| Vapor density:                                | 1 [Air = 1]                                  |
| Relative density:                             | 0.94   |
| Solubility:                                   | Not available.                               |
| Solubility in water:                          | Not available.                               |
| Partition coefficient: n-octanol/water        | Not available.                               |
| Auto-ignition temperature:                    | 750 to 900°C (1382 to 1652°F)                |
| Viscosity:                                    | Dynamic (room temperature): 15 mPa·s (15 cP) |
| Flow time (ISO 2431):                         | Not available.                               |

## ***Section 10 - Stability and reactivity***

|  |   |
|--|---|
| <b>Reactivity:</b>                         | No specific test data related to reactivity available for this product or its ingredients.  |
| <b>Chemical stability:</b>                 | The product is stable.  |
| <b>Possibility of hazardous reactions:</b> | Hazardous reactions or instability may occur under certain conditions of storage or use.  |
| <b>Conditions to avoid:</b>                | Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. |
| <b>Incompatible materials:</b>             | Reactive or incompatible with the following materials:<br>oxidizing materials   |
| <b>Hazardous decomposition products:</b>   | Under normal conditions of storage and use, hazardous decomposition products should not be produced.  |

## **Section 11 - Toxicological information**

### **Specific target organ toxicity (single exposure)**

| <b>Name</b>   | <b>Category</b> | <b>Route of exposure</b> | <b>Target organs</b> |
|---------------|-----------------|--------------------------|----------------------|
| Ethyl acetate | Category 3      | Not applicable.          | Narcotic effects     |

**Information on the likely routes of exposure:** Not available.

### **Potential acute health effects**

**Eye contact:** Causes serious eye irritation.

**Inhalation:** Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.

**Skin contact:** Causes skin irritation. May cause an allergic skin reaction.

**Ingestion:** Can cause central nervous system (CNS) depression.

### **Symptoms related to the physical, chemical and toxicological characteristics**

**Eye contact:** Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation:** Adverse symptoms may include the following:  
nausea or vomiting  
headache  
dizziness/vertigo  
drowsiness/fatigue  
unconsciousness

**Skin contact:** Adverse symptoms may include the following:  
redness  
irritation

**Ingestion:** No specific data.

### **Delayed and immediate effects and also chronic effects from short and long term exposure**

#### **Short term exposure**

**Potential immediate effects:** Not available.

**Potential delayed effects:** Not available.

#### **Long term exposure**

**Potential immediate effects:** Not available.

**Potential delayed effects:** Not available.

### **Potential chronic health effects**

Not available.

**General:** Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity:** No known significant effects or critical hazards.

**Mutagenicity:** No known significant effects or critical hazards.

**Teratogenicity:** No known significant effects or critical hazards.

**Developmental effects:** No known significant effects or critical hazards.

**Fertility effects:** No known significant effects or critical hazards.

### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Not available.

## ***Section 12 - Ecological information***

### **Persistence and degradability**

Not available.

### **Bioaccumulative potential**

| Product/ingredient name     | LogP <sub>ow</sub> | BCF | Potential |
|-----------------------------|--------------------|-----|-----------|
| Ethyl acetate               | 0.68               | 30  | low       |
| 2-hydroxyethyl methacrylate | 0.42               | -   | low       |

### **Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>) :** Not available.

**Other adverse effects:** No known significant effects or critical hazards.

## ***Section 13 - Disposal considerations***

### **Disposal methods:**







The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### **United States - RCRA Toxic hazardous waste "U" List**

| Ingredient                                     | CAS #    | Status | Reference number |
|--|----------|--------|------------------|
| Ethyl acetate (I); Acetic acid ethyl ester (I) | 141-78-6 | Listed | U112             |



## Section 14 - Transport information

|                            | DOT Classification   | TDG Classification   | Mexico Classification  | ADR/RID   | IMDG   | IATA   |
|----------------------------|--|--|--|---|--|--|
| UN number                  | UN1993   | UN1993   | UN1993   | UN1993  | UN1993   | UN1993   |
| UN proper shipping name    | FLAMMA-BLE LIQUID, N.O.S.(ethyl acetate)   | FLAMMA-BLE LIQUID, N.O.S.(ethyl acetate)   | FLAMMA-BLE LIQUID, N.O.S.(ethyl acetate)   | FLAMMA-BLE LIQUID, N.O.S.(ethyl acetate)  | FLAMMA-BLE LIQUID, N.O.S.(ethyl acetate)   | FLAMMA-BLE LIQUID, N.O.S.(ethyl acetate)   |
| Transport hazard class(es) | 3<br> | 3<br> | 3<br> | 3<br> | 3<br> | 3<br> |
| Packing group              | II   | II   | II   | II  | II   | II   |
| Environmental hazards      | No.  | No.  | No.  | No.   | No.  | No.  |

### Additional information

|  |  |
|--|--|
| <b>DOT Classification:</b>   | <b>Reportable quantity</b> 16774 lbs / 7615.4 kg [2140.2 gal / 8101.5 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements. |
| <b>TDG Classification:</b>   | Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).  |
| <b>ADR/RID:</b>  | <b>Special provisions</b> 640 (C)<br><b>Tunnel code</b> (D/E)  |
| <b>IMDG:</b>   | <b>Emergency schedules</b> 307   |
| <b>IATA:</b>   | <b>Special provisions</b> A3   |
| <b>Special precautions for user:</b>   | <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.                    |
| <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:</b> | Not available.   |

## Section 15 - Regulatory information

**U.S. Federal regulations:** TSCA 8(a) CDR Exempt/Partial exemption: Not determined

**Clean Air Act Section 112:** Not listed

### (b) Hazardous Air Pollutants (HAPs)

**Clean Air Act Section 602 Class I Substances** Not listed

**Clean Air Act Section 602 Class II Substances** Not listed

**DEA List I Chemicals (Precursor Chemicals)** Not listed

**DEA List II Chemicals (Essential Chemicals)** Not listed

## **SARA 302/304**

### **Composition/information on ingredients**

No products were found.

**SARA 304 RQ:** Not applicable.

## **SARA 311/312**

**Classification:** FLAMMABLE LIQUIDS - Category 2  
SKIN IRRITATION - Category 2  
EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects)  
-Category 3

### **Composition/information on ingredients**

| Name                        | %         | Classification  |
|-----------------------------|-----------|---|
| 2-hydroxyethyl methacrylate | ≥25 - ≤50 | SKIN IRRITATION - Category 2<br>EYE IRRITATION - Category 2A<br>SKIN SENSITIZATION - Category 1   |
| Ethyl acetate               | ≥25 - ≤50 | FLAMMABLE LIQUIDS - Category 2<br>EYE IRRITATION - Category 2A<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)<br>(Narcotic effects) - Category 3 |

## **State regulations**

**Massachusetts:** The following components are listed: ETHYL ACETATE; ACETIC ACID, ETHYL ESTER  
**New York:** The following components are listed: Ethyl acetate  
**New Jersey:** The following components are listed: ETHYL ACETATE; ACETIC ACID, ETHYL ESTER  
**Pennsylvania:** The following components are listed: ACETIC ACID ETHYL ESTER

### **California Prop. 65**

This product does not require a Safe Harbor warning under California Prop. 65.

## **International regulations**

### **Chemical Weapons Convention List Schedule I, II & III Chemicals :**

Not listed

### **International lists:**

**Australia inventory (AICS):** All components are listed or exempted.  
**China inventory (IECSC):** All components are listed or exempted.  
**Japan inventory:** All components are listed or exempted.  
**Korea inventory:** All components are listed or exempted.  
**Malaysia Inventory (EHS Register):** Not determined.  
**New Zealand Inventory of Chemicals (NZIoC):** All components are listed or exempted.  
**Philippines inventory (PICCS):** All components are listed or exempted.  
**Taiwan inventory (CSNN):** All components are listed or exempted.  
**Thailand:** Not determined.  
**Turkey:** Not determined.  
**United States:** All components are listed or exempted.  
**Viet Nam:** Not determined.

## Section 16 - Other information


### Hazardous Material Information System (U.S.A.)

|                     |   |   |
|---------------------|---|---|
| Health              | / | 2 |
| Flammability        |   | 3 |
| Physical hazards    |   | 1 |
| Personal protection |   |   |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

### National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### History

Date of printing: 3/31/2021

Date of issue/Date of revision: 3/31/2021

Date of previous issue: 12/24/2019

Version: 2

### Key to abbreviations:

ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
UN = United Nations

**References:** Not available.

✔ Indicates information that has changed from previously issued version.

### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, Kiara Sky Professional Nails, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Information contained within this SDS is only to be distributed as required by law.