

SAFETY DATA SHEET



Date Prepared: 06/22/2016

Product SKU: KSDSP01

Date-Revised: 12/20/2019

Revision No: 4

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: Kiara Sky Dip Essential Seal Protect

MANUFACTURER

Kiara Sky Professional Nails Inc.
8700 Swigert Ct. Ste. 109-209
Bakersfield, CA 93311

Emergency Contact: CHEMTEL
Emergency Phone: (800)255-3924
Outside of U.S.: (813)248-0585
Company Number: (661)393-4800

Contract: MIS2294037

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Target Organ Toxicity (Single exposure), Category 3
Serious Eye Damage/Eye Irritation, Category 2A
Acute Toxicity (Oral), Category 4

Physical:

Flammable Liquids, Category 2

GHS LABEL ELEMENTS



Exclamation
mark



Flame

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H225: Highly flammable liquid and vapor.
H302: Harmful if swallowed.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENT(S)

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground and bond container and receiving equipment.
P242: Use non-sparking tools.
P243: Take action to prevent static discharges.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P264: Wash skin and hands thoroughly after handling.

SAFETY DATA SHEET



Date Prepared: 06/22/2016

Product SKU: KSDSP01

Date-Revised: 12/20/2019

Revision No: 4

P270: Do not eat, drink, or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P330: Rinse mouth.

P337+P313: If eye irritation persists: Get medical advice/attention.

P370+P378: In case of fire: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment for extinction.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Ethyl Acetate	85 - 100	141-78-6
Methyl propyl ketone	< 1	107-87-9
Methyl-Isobutyl Ketone	< 1	108-10-1
N,N-DIMETHYL-P-TOLUIDINE	< 1	99-97-8

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: If swallowed, seek medical advice immediately and show this container or label.

INHALATION: Remove to fresh air. Get medical attention if breathing is difficult.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE EFFECTS: Vapors may be irritating to eyes, throat and mucous membranes; ingestion may cause headache, drowsiness and possible unconsciousness.

5. FIRE FIGHTING MEASURES

GENERAL HAZARD: Highly flammable. Irritant.

EXTINGUISHING MEDIA: Use dry chemical, foam or carbon dioxide.

EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back.

SAFETY DATA SHEET



Date Prepared: 06/22/2016

Product SKU: KSDSP01

Date-Revised: 12/20/2019

Revision No: 4

FIRE FIGHTING PROCEDURES: Avoid using large quantities of water.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide or carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

LARGE SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on adsorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: This product is readily biodegradable. Do not release into surface waters.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid breathing of vapors. Use only in well ventilated areas. When handling, do not eat, drink or smoke.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
Chemical Name		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
		ppm	mg/m ³	ppm	mg/m ³
Ethyl Acetate	TWA	400	1400	400	1440
Methyl-Isobutyl Ketone	TWA	100	410	20	-
	STEL	-	-	75	-
N,N-DIMETHYL-P-TOLUIDINE	TWA	0.50 ppm	No data available	No data available	No data available
	STEL	No data available	No data available	No data available	No data available

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Avoid contact with eyes.

SKIN: Wear suitable gloves.

RESPIRATORY: Use only in a well-ventilated area. In case of insufficient ventilation, wear suitable respiratory equipment. Recommended: Full-face NIOSH-approved respirator with organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Strong fruity odor.

ODOR THRESHOLD: No data available

SAFETY DATA SHEET



Date Prepared: 06/22/2016

Product SKU: KSDSP01

Date-Revised: 12/20/2019

Revision No: 4

APPEARANCE: Clear, Colorless liquid
COLOR: Clear to pale yellow
pH: No data available
PERCENT VOLATILE: No data available
FLASHPOINT AND METHOD: 1.11°C (30°F) TCC
FLAMMABLE LIMITS: 2 to 11.4
AUTOIGNITION TEMPERATURE: 427°C (800.6°F)
VAPOR PRESSURE: 73 mmHg at 20°C (68°F)
VAPOR DENSITY: No data available
BOILING POINT: 77°C (170°F) to 78°C (172°F)
FREEZING POINT: No data available
MELTING POINT: Not Established
THERMAL DECOMPOSITION: No data available
SOLUBILITY IN WATER: Slightly soluble.
EVAPORATION RATE: 4.5 (n-Butyl Acetate=1)
SPECIFIC GRAVITY: 0.9 (water=1)
VISCOSITY #1: < 5 Centipoise
(VOC): 9 g/L

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: No
CONDITIONS TO AVOID: Heat, sparks and flame.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, dioxide.
INCOMPATIBLE MATERIALS: Strong oxidizing agents, acids and bases.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

SERIOUS EYE DAMAGE/IRRITATION: None known.
SKIN CORROSION/IRRITATION: None known.
CHRONIC: Repeated exposure may cause skin dryness or cracking.
SUBCHRONIC: No data available on this product.
IRRITATION: May cause eye irritation, skin irritation and irritation of respiratory tract.
STOT-SINGLE EXPOSURE: Inhalation- vapor: May cause drowsiness or dizziness.
STOT-REPEATED EXPOSURE: None known.
GENETIC EFFECTS: None known.

SAFETY DATA SHEET



Date Prepared: 06/22/2016

Product SKU: KSDSP01

Date-Revised: 12/20/2019

Revision No: 4

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: This product is readily biodegradable. Do not release into surface waters.

AQUATIC TOXICITY (ACUTE)

96-HOUR LC₅₀: > 220 mg/L48-HOUR EC₅₀: > 500 mg/L96-HOUR EC₅₀: > 360 mg/L

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with local, State, and Federal regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: UN1173, ETHYL ACETATE, 3, II

AIR (ICAO/IATA)

SHIPPING NAME: ID800, SONSUMER COMMODITY, 9; or UN1173, ETHYL ACETATE, 3, II

VESSEL (IMO/IMDG)

SHIPPING NAME: UN1173, ETHYL ACETATE, 3, II

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Ethyl Acetate	85 - 100	5,000 lbs.
Methyl-Isobutyl Ketone	< 1	5,000

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Ethyl Acetate	141-78-6
Methyl propyl ketone	107-87-9
Methyl-Isobutyl Ketone	108-10-1

TSCA STATUS: All ingredients in this mixture are in compliance with TSCA.

CALIFORNIA PROPOSITION 65: **WARNING:** This product can expose you to chemicals including Methyl-Isobutyl Ketone (MIBK) and N,N-Dimethyl P-Toluidine, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SAFETY DATA SHEET



Date Prepared: 06/22/2016

Product SKU: KSDSP01

Date-Revised: 12/20/2019

Revision No: 4

Chemical Name	Wt.%	Listed
Methyl-Isobutyl Ketone	<1	<ul style="list-style-type: none"> • Cancer • Developmental Toxicity
N,N-DIMETHYL-P-TOLUIDINE	< 1	<ul style="list-style-type: none"> • Cancer

GENERAL COMMENTS: Massachusetts Right to Know Components: Ethyl acetate (CAS 141078-6), **Pennsylvania Right to Know Components:** Ethyl acetate (CAS 141078-6), **New Jersey Right to Know Components:** Ethyl acetate (CAS 141078-6)

16. OTHER INFORMATION

APPROVED BY: Regulatory Department

PREPARED BY: Product Safety


Date-Revised: 12/20/2019

REVISION SUMMARY: This MSDS replaces the 06/15/2019 MSDS.

HMIS RATING

HEALTH	<input type="checkbox"/>	1
FLAMMABILITY		3
PHYSICAL HAZARD		0
PERSONAL PROTECTION	<input type="checkbox"/>	

NFPA CODES



MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Kiara Sky Professional Nails Inc. does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.