



EXHAUST / INTAKE GUARD







	Α	В	С	D	F	Weight	
Model Number	in	in	in	in	in	Lbs	Blower
	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)	
EG125	2.8	6.45	2.57	4.92	5.8	0.53	P15/S14
	(71)	(164)	(65)	(125)	(147)	(0.24)	
EG125CIP	2.8	6.45	2.57	4.92	5.8	0.53	P15/S14 XP
	(71)	(164)	(65)	(125)	(147)	(0.24)	
EG160	2.56	10.6	5.62	6.3	8	0.88	P20/S16/J20
	(65)	(270)	(143)	(160)	(202)	(0.4)	
EG160CIP	2.56	10.6	5.62	6.3	8	0.88	P20/S16/J20 XP
	(65)	(270)	(143)	(160)	(202)	(0.4)	
EG200	2	11.8	5.75	7.87	9.1	1.01	P25/S18/J25
	(50)	(300)	(146)	(200)	(230)	(0.46)	
EG200CIP	2	11.8	5.75	7.87	9.1	1.01	P25/S18/J25 XP
	(50)	(300)	(146)	(200)	(230)	(0.46)	
EG250	3.2	13.2	6.7	9.84	11.5	2.16	P30/J30
	(82)	(336)	(172)	(250)	(292)	(0.98)	
EG250CIP	3.2	13.2	6.7	9.84	11.5	2.16	P30/J30 XP
	(82)	(336)	(172)	(250)	(292)	(0.98)	
EG315	2	16.2	8.4	12.4	14.7	2.64	P35
	(50)	(411)	(214)	(315)	(373)	(1.2)	
EG315CIP	2	16.2	8.4	12.4	14.7	2.64	P35 XP
	(50)	(411)	(214)	(315)	(373)	(1.2)	

 $\label{eq:continuous} \mbox{CIP} = \mbox{``Carbon Impregnated Polypropylene''}. \mbox{ Material suited for explosion resistant blower systems.} \\ \mbox{$\mathsf{XP} = $\mathsf{Explosion Resistant}$}$

FEATURES:

Polypropylene exhaust/intake guard/bird screen. Designed to prevent entry of external elements into moving components inside the housing. Can be mounted on the outlet or inlet. A smooth angle allows to reduce air resistance when mounted on the blower outlet.

- Recommended up to 140°F.
- Available in spark resistant (CIP/ATEX) version.
- UV treated.
- Corrosion resistant.
- Square mesh 0.4"x0.4" (10x10mm) opening.
- Color: Grey (standard) or Black (CIP/XP)

Project Name	
Date	
Engineer / Sales Rep	
Client	
Contractor	

Property rights to all drawings, details, representations, ideas, data, notes and specifications either copies or originals thereof that may be incorporated into the design and/or project are the property solely of Plastec Ventilation, Inc. Permission for any copies of said copyrighted materials, drawings, details, representations, ideas, data, notes and specifications either originals or copies thereof to be made, coped or altered by any person, business, or corporation may only be authorized with the expressed written permission of Plastec Ventilation, Inc. By the use of this data, the user acknowledges that he/she has read and understand all of the notes included herein.