


FLEXIBLE PVC REDUCER/COUPLING





Model Number	Α	В	С	Weight	Blower
	in	in	in	Lbs	compatibility
156-33	3.4	3.4	4.25	0.83	S10
156-43	4.4	3.4	4	1	S10/S12
156-44	4.5	4.5	4.25	1.25	S12
156-54	5.5	4.4	4	1.25	P15/S14/S12
156-63	6.4	3.4	6	2.1	P20/S16/S10/J20
156-64	6.4	4.4	5.63	2.25	P20/S16/S12/J20
156-65	6.4	5.5	4.75	1.5	P15/S14/P20/S16/J20
156-66	6.4	6.4	6	2.5	P20/S16/J20
156-84	8.55	4.4	6	3.33	P25/S18/S12/J25
156-86	8.55	6.4	5.88	3	P25/S18/P20/S16/J20/J25
156-88	8.55	8.55	5.75	7	P25/S18/J25
156-106	10.6	6.4	6.63	5	P30/P20/S16/J30/J20
156-108	10.6	8.55	6.38	5	P30/P25/S18/J30/J20
156-1010	10.6	10.6	5.88	11	P30/J30
156-126	12.6	6.4	6.25	9	P35/P20/S16/J20
156-128	12.6	8.55	6.5	4	P35/P25/S18/J25
156-1210	12.6	10.6	6.25	5	P35/P30/J30
156-1212	12.6	12.6	6.38	7	P35
ISLDC20	20	20	9	12	P50
156-LDC2320	20	23	9.5	16	P50

FEATURES

Manufactured from flexible PVC materials that comply with the applicable requirements of ASTM C 1173 Standard Specification for Flexible Transition Couplings. Can be used to form a leak proof joint between section plain end pipe or fittings of the same or different materials such as iron, clay, ductile iron, concrete, and plastic.

- Manufactured out of elastomeric Polyvinyl Chloride. .
- 300 premium grade stainless steel hose clamps.
- Deflection sealing resistance up to 4.3 psi.
- Shear testing up to 50lbs per inch of nominal diameter.
- Shore "A" durometer hardness testing up to 50-75.

Project Name	
Date	
Engineer / Sales Rep	
Client	
Contractor	

Property rights to all drawings, details, representations, ideas, data, notes and specifications either copies or originals thereof that may be incorporated into the design and/or project are the property solely of Plastec Ventilation, Inc. Permission for any copies of said copyrighted materials, drawings, details, representations, ideas, data, notes and specifications either originals or copies thereof to be made, coped or altered by any person, business, or corporation may only be authorized with the expressed written permission of Plastec Ventilation, Inc. By the use of this data, the user acknowledges that he/she has read and understand all of the notes included herein.