



FEATURES:

- Precision Motor Control. **PMC** matches the motor speed to the pressure and tip size selected.
- No pulsation at any pressure with any size tip.
- No Rust Fluid manifold. Only High grade Stainless Steel and Aircraft grade aluminum is used.
- No cylinder to wear out.
- Long Life fluid manifold.
- Built for professional use.
- All metal construction.
- More powerful PMDC motor results in the lowest amperage use in its class.
- High efficiency motor/controller results in 10% more output then competitive models.

T9 AIRLESS SPRAYER

| Specifications | |
|----------------|-------------------|
| Max Pressure | 3300psi (226 bar) |
| Max Tip | 0.031 |
| Max GPM | 1.05 (4lpm) |
| Motor HP | 2.1 HP |
| Hi-Cart | 97 lbs. (44 kg) |
| Lo-Cart | 97 lbs (44kg) |

| Description | Part # |
|--------------------------|---------|
| T9 Hi Cart Complete 110V | 602-804 |
| T9 Lo Cart Complete 110V | 602-806 |
| T9 Hi Cart Complete 220V | 602-814 |
| T9 Lo Cart Complete 220V | 602-816 |





FEATURES:

- Precision Motor Control. **PMC** matches the motor speed to the pressure and tip size selected.
- No pulsation at any pressure with any size tip.
- No Rust Fluid manifold. Only High grade Stainless Steel and Aircraft grade aluminum is used.
- No cylinder to wear out.
- Long Life fluid manifold.
- Built for professional use.
- All metal construction.
- More powerful PMDC motor results in the lowest amperage use in its class.
- High efficiency motor/controller results in 10% more output then competitive models.

T11 AIRLESS SPRAYER

| Specifications | |
|----------------|-------------------|
| Max Pressure | 3300psi (226 bar) |
| Max Tip | 0.033 |
| Max GPM | 1.17 (4.45 lpm) |
| Motor HP | 2.5 HP |
| Hi-Cart | 105 lbs. (48 kg) |
| Lo-Cart | 105 lbs (48kg) |

| Description | Part # |
|---------------------------|---------|
| T11 Hi Cart Complete 110V | 602-834 |
| T11 Lo Cart Complete 110V | 602-836 |
| T11 Hi Cart Complete 220V | 602-844 |
| T11 Lo Cart Complete 220V | 602-846 |

