

W-400 Classic Plus Series MANUAL SPRAY GUN



- Universal spray gun for industrial coating
- VOC-compliant professional spray gun, significantly more than 65% transfer efficiency
- Large and uniformly shaped wet core, even with high viscosity materials
- Clearly noticeable reduction in banding
- 280 NI / min air consumption; also suitable for small compressors capacity
- For ANEST IWATA-typical: quiet and pleasant background noise
- With 380g one of the lightest guns on the market
- Conical seal nozzle, minimum wear parts
- Quality surface for an easy cleaning
- Clearer design, easy maintenance



MODEL	ø mm	bar	NI/min	m ³ /min	mm	No.	g
W400-082G	0.8	2.0	280	60	80	LV2	380
W400-102G	1.0			95	150		
W400-122G	1.2			140	175		
W400-132G	1.3			160	225		
W400-142G	1.4			210	255		
W400-162G	1.6			240	270		
W400-182G	1.8			290	320		
W400-202G	2.0	3.0	360	460	320	R2	
W400-251G	2.5			580	340	W1	



Max. Working Pressure: 6.8 bar (98 PSI)

Noise Level (LAeqT) 79.7 dB (A)

Temperature range: 5~40° C

Air nipple: G 1/4" M

Fluid nipple: M 16 x 1.5 mm



declaration of ATEX conformity for use in zone 1 and in zone 2