Sheaves

Schaefer Blocks rely on a variety of sheave designs, materials and scorings. We do not recommend the replacement of Schaefer sheaves in the field. We suggest the return of Schaefer Blocks to our factory for inspection and/or replacement of worn or UV affected sheaves. Schaefer sheaves are designed to be compatible with Schaefer products, and are not intended for use in other manufacturers blocks. There is a risk of incompatibility or failure when using Schaefer sheaves in blocks manufactured by anyone other then Schaefer Marine.

Delrin™ Ball Bearing

Delrin™ Sheaves with Delrin™ Ball Bearing are used in line applications to reduce friction. To provide the maximum load bearing capability, we designed our Delrin™ ball bearing sheaves and inner races with curved surfaces to match the ball races. The resulting sheave has a much higher save working load than other manufacturers'.

DelrinTM

Delrin™ Sheaves are injected molded with UV inhibitors and monitored molding cycles lending to a strong, UV resistant product. These sheaves offer durable, lasting service for all line application.

Aluminum Universal Circuit Sheaves (UC)

These extremely low friction ball bearing sheaves accomodate both line and wire. High strength self-contained DelrinTM bearing package, and NomexTM/TeflonTM self-lubricating bushing is used in all "UC" sheaves. The combined benefits of the design mean easier turning under the heaviest loads.

Aluminum

This configuration accommodates both line and wire, providing a chafe-free surface for line while giving full support to wire to prevent flattening. Hardcoat Anodized 6061-T6 Aluminum offers superior strength and corrosion resistance.

tem	Material	Max Line	Max Wire	Outside Dia.	Inside Dia.	Width
62-020-01	Delrin™	1/4" (6mm)		3/4" (19mm)	1/4" (6mm)	11/32" (9mm)
62-020-02	Delrin™	5/16" (8mm)		1-1/16" (27mm)	5/16" (8mm)	7/16" (11mm)
62-214	Delrin™ (BB)	5/16" (8mm)		1-1/16" (27mm)	3/16" (5mm)	1/2" (13mm)
62-220	Delrin™	1/2" (13mm)		1-1/16" (27mm)	3/8" (10mm)	5/8" (16mm)
62-030-02	Delrin™	1/2" (13mm)		1-7/16" (37mm)	3/8" (10mm)	5/8" (16mm)
62-030-04	Delrin™ Black	1/2" (13mm)		1-7/16" (37mm)	3/8" (10mm)	5/8" (16mm)
62-031	Delrin™	3/8" (10mm)		1-7/16" (37mm)	5/16" (8mm)	17/32" (13mm)
62-095-BW	Alum.		5/32" (4mm)	1-7/16" (37mm)	5/16" (8mm)	9/32" (7mm)
62-150-02A	Delrin™ (BB)	1/2" (13mm)		1-7/16" (37mm)	3/16" (5mm)	5/8" (16mm)
62-218-BW	Alum.	1/2" (13mm)	3/16" (5mm)	1-7/16" (37mm)	3/8" (10mm)	19/32" (15mm)
62-219	Delrin™	1/2" (13mm)		1-3/4" (44mm)	3/8" (10mm)	5/8" (16mm)
62-043-01	Delrin™	5/8" (16mm)		1-7/8" (48mm)	7/16" (11mm)	13/16" (21mm)
62-043-01B	Delrin™	5/8" (16mm)		1-7/8" (48mm)	7/16" (11mm)	13/16" (21mm)
62-043-02	Delrin™ Black	5/8" (16mm)		1-7/8" (48mm)	7/16" (11mm)	13/16" (21mm)
62-043-02B	Delrin™ Black	5/8" (16mm)		1-7/8" (48mm)	7/16" (11mm)	13/16" (21mm)
62-243	Alum. (U.C.)	5/8" (16mm)	1/8" (3mm)	1-7/8" (48mm)	1/4" (6mm)	13/16" (21mm)
62-018	Delrin™	1/2" (13mm)		2" (51mm)	3/8" (10mm)	5/8" (16mm)
62-018-01	Delrin™ Black	1/2" (13mm)		2" (51mm)	3/8" (10mm)	5/8" (16mm)
62-023-15BW	Alum.	1/2" (13mm)	3/16" (5mm)	2" (51mm)	3/8" (10mm)	5/8" (16mm)
62-023-15CW	Alum.	1/2" (13mm)	3/16" (5mm)	2" (51mm)	1/2" (13mm)	5/8" (16mm)
62-051	Delrin™	1/2" (13mm)		2" (51mm)	1/2" (13mm)	5/8" (16mm)
62-051-01	Delrin™ Black	1/2" (13mm)		2" (51mm)	1/2" (13mm)	5/8" (16mm)
62-152-02A	Delrin™ (BB)	1/2" (13mm)		2" (51mm)	3/16" (5mm)	5/8" (16mm)
62-030-01	Delrin™	1/2" (13mm)		2-1/4" (57mm)	3/8" (10mm)	5/8" (16mm)
62-030-03	Delrin™ Black	1/2" (13mm)	222	2-1/4" (37mm)	3/8" (10mm)	5/8" (16mm)
62-019	Delrin™	5/8" (16mm)		2-3/8" (60mm)	7/16" (11mm)	13/16" (21mm
62-019-02	Delrin™ Black	5/8" (16mm)		2-3/8" (60mm)	7/16" (11mm)	13/16" (21mm
62-019-02B	Delrin™ Black	5/8" (16mm)		2-3/8" (60mm)	7/16" (11mm)	13/16" (21mm
62-019-03B	Delrin™ Black	5/8" (16mm)		2-3/8" (60mm)	1/2" (13mm)	13/16" (21mm
62-053-B	Delrin™	5/8" (16mm)		2-3/8" (60mm)	7/16" (11mm)	13/16" (21mm
62-054-BW	Alum.	5/8" (16mm)	3/16" (5mm)	2-3/8" (60mm)	7/16" (11mm)	3/4" (19mm)
62-065B	Delrin™	5/8" (16mm)		2-3/8" (60mm)	1/2" (13mm)	13/16" (21mm
62-070-BW	Alum.	5/8" (16mm)	3/16" (5mm)	2-3/8" (60mm)	1/2" (13mm)	3/4" (19mm)
62-081-BW	Alum.	3/8" (10mm)	3/16" (5mm)	2-3/8" (60mm)	5/8" (16mm)	9/16" (14mm)
62-153-02A	Delrin™ (BB)	5/8" (16mm)		2-3/8" (60mm)	1/4" (6mm)	13/16" (21mm
62-228-BW	Alum.		1/8" (3mm)	2-3/8" (60mm)	7/16" (11mm)	13/32" (10mm
62-242	Alum. (U.C.)	5/8" (16mm)		2-3/8" (60mm)	1/4" (6mm)	13/16" (21mm
62-244	Alum. (U.C.)	3/4" (19mm)	1/4" (3mm)	2-1/2 (64mm)	1/2" (13mm)	1-1/32" (26mr
62-039-02BW	Plastic	3/4" (19mm)		3-1/4" (83mm)	5/8" (16mm)	3/4" (19mm)
62-229-BW	Alum.		3/16" (5mm)	3-1/4" (83mm)	5/8" (16mm)	17/32" (14mn
62-241	Alum. (U.C.)	5/8" (16mm)	3/16" (5mm)	3-1/4" (83mm)	3/8" (10mm)	13/16" (21mm
62-230-BW	Alum.		1/4" (6mm)	4" (102mm)	3/4" (19mm)	11/16" (18mm
62-240	Alum. (U.C.)	3/4" (19mm)	1/4" (6mm)	4" (102mm)	1/2" (13mm)	1-1/32" (26mm
62-247	Alum. (U.C.)	7/8" (22mm)	3/8" (10mm)	5-1/2" (140mm)	3/4" (19mm)	1-3/16" (30mn