



PRODUCT TECHNICAL DATASHEET















Dimensions





BAMBINO BM30

Electromechanical HIGH SPEED BRUSHLESS motor, low voltage, super intensive use, onboard encoder, ideal for sliding gates up to 400kg with built in digital controller and magnetic limit switch.





Brushless

s Intensive Use

High Speed

Digital Encoder

Max Gate Weight	400 kg
Maximum Gate Length	12m
Power Line Supply	230V AC - 50Hz
Motor Power Supply	24V
Power Rating	125W
Duty Cycle	100% Intensive Use
Thrust	50 - 350N
Operating Temperature	-20+55°C
Protection Level	IP43
Reductor Type	Irreversible
Manoeuvre Speed	26 m/min (0.44 m/s)
Limit Switch	Magnetic
Onboard Control Unit	B70/IDC
Encoder	Digital encoder + magnetic digital SENSORED, 4096 PPR
Batteries Recovery	Optional 2 external battery 12V 7AH
Type Exit Gear	Z15/mod 4
Maximum Power Absorbtion	320W
Maximum Start Up Force	350N
Maximum Fricion At Start	40N















Brushless Digital Motor

Features a compact design with neodymium iron-baron magnets, available in 24V & 36V AC versions, operating at ambient temperature with low consumption.

Speed & Acceleration With Maximum Safety

Controls motor torque precisely for smooth acceleration and deceleration, ensuring safety.

Super Intensive Use

Operates at low voltage with a 100% duty cycle, maintaining low energy consumption.

• External Transformer For Heavy Gates

Low voltage options reduce installation costs where high voltage is unavailable.

Extremely Low Energy Consumption

Consumes about 1/3 the power of other brands for the same gate weight and speed.

Amazingly Quiet

Precision gearing and smooth torque control result in very quiet operation, ideal for residential applications.

Powerful Digital Encoder

SENSORED technology provides 4096 pulses per revolution for precise control and safety in obstacle detection.

Limit Switch

Available with magnetic limit switches.

Standby Batteries

Emergency battery backup system available, with optional 'fail open' setting during power outages.

Multifunctional Digital Display

4-quadrant display with 6 function keys for parameter adjustment, error checking, and self-learning.

High Precision Engineering

Features premium materials and double shielded ball bearings for precise alignment and durability.

Reinforced Aluminum Body

Aluminum housing reinforced with titanium and epoxy-painted for weather protection.

Sustainablity

Roger Technology is a green customer-centric company dedicated to creating sustainable products through environmentally responsible production processes, innovative technologies, and a culture that prioritizes the health, safety, and development of its workers and customers.