THE MERCURY BALUSTRADE





Design Details

Residential Balustrade

Visually appealing and designed to withstand the elements, this panel is perfect for residential retaining walls, decks and balconies, and conforms to residential balustrade requirements.

Commercial Balustrade

With its super rigid top rail, this panel is the ideal solution for commercial applications, apartment buildings, parks or schools and conforms to commercial balustrade requirements.

Raking Aluminium Balustrade & Fence Panel

Mercury Balustrade Panels are the most rigid, full-width aluminium raking panels on the market. The patented mechanism not only allows it to rake up to 30°, it also adds to the rigidity, putting it up there with custom made steel panels but without the drawbacks or price tag!

Two variants - both balustrade compliant at full 2.4m centres and rakeable to 30°.

- Mercury Commercial: 40x50mm top rail, 40x40mm bottom rail and 25x25mm pickets
- Mercury Residential: 40x40mm top and bottom rails and 25x25mm pickets

Producer Statement (PS1) available on www.fencelab.co.nz .



Residential Balustrade Specifications

Rails: Alu 40x40mm top and bottom custom extrusion

Pickets: Alu 25 x 25mm SHS

Recommended Posts: Alu or Steel 65 x65 x 2.5mm SHS

Commercial Balustrade Specifications


Rails: Alu 50x40mm top and 40x40mm bottom custom extrustions


Pickets: Alu 25 x 25mm SHS

Recommended Posts: Steel 65 x 65 x 2.5mm SHS

1.0/1.2 Flat Top 2 Rail

Height	А	В		
1.0m	1000mm	120mm		
1.2m	1200mm	120mm		





Compliancy Table

Panel	Application	Bldg Code Ref	Width	Load	Posts	Relevant Mounting
The Mercury Standard - 40 x 40 Rails, 1.0mh, 1.2mh	Residential Retaining Walls - Single Dwelling	A	2.4m	0.35 KN/M	65 X 2.5mm (6063-T5 Grade Aluminium) Or Steel	Concrete-In
						Timber Retaining Wall Coach Screw
						Timber Retaining Wall Bolt
	Residential Deck And Balcony Balustrade	C3	1.2m	0.75 KN/M	65 X 2.5mm (6063-T5 Grade Aluminium) Or Steel	Deck Joist Flange Mount
						Deck Joist Side Mount
The Mercury Commercial - 50 x 40 Top Rail, 40 x 40 Bottom Rail 1.0mh, 1.2mh	Multi Dwelling Residential, Commercial, Parks And Schools	C3, B, E	2.4m	0.75 KN/M	65 X 2.5 Steel	Concrete Side Mount
						Concrete Flange Mount
						Block Wall Side Mount
						Block Wall Flange Mount
						Timber Retaining Wall Coach Screw
						Timber Retaining Wall Bolt
						Concrete-In

See The Mercury Balustrade Producer Statement (PS1) at FenceLab.co.nz

Panels are supplied with 14 gauge tek screws. Upgrade to Pentaforce security screws for fencing in public places:



- 5 Sided Pentagon recess to stop all standard driver tool shapes, only the registered Pentaforce driver tools can be used for installation and removal.
- Two types: Self drilling 1 5mm
 - Self drilling 5 10mm