

Description:	Colourtrend Ceramic Matt is a premium quality, low odour emulsion for interior walls and ceilings. It is an acrylic matt coating enhanced with ceramic technology, providing superior stain resistance and durability in a smooth matt finish. This ceramic matt finish gives minimal light reflection which helps to hide imperfections and gives colour richness and depth. Ceramic technology gives exceptional stain resistance to most household stains. The combination of tightly packed ceramic microspheres combined with tough acrylic resin allows most stains to be washed away with just soap and water giving you a vastly superior paint. This product is classed as a breathable coating.		
Special Features:	<input type="checkbox"/> Acrylic resin <input type="checkbox"/> EN13300 certified <input type="checkbox"/> Low VOC <input type="checkbox"/> Easy clean up with soapy water	<input type="checkbox"/> Excellent coverage <input type="checkbox"/> Excellent sheen retention <input type="checkbox"/> Very low odour <input type="checkbox"/> Excellent stain resistance	<input type="checkbox"/> Superior washability <input type="checkbox"/> Excellent flow & levelling properties <input type="checkbox"/> Available in all Colourtrend Colours <input type="checkbox"/> Non-hazardous under EU legislation
Classification	Colourtrend Ceramic Matt is classified as Class 1 Section 5.4 (wet scrub resistance) and Class 1 Section 5.5 (opacity) under EN13 300 / BS 13 300. Independent certification is available on request.		
Colour Range:	Entire Colourtrend range, RAL & BS 4800. Some pale colours are restricted to larger size cans.		
Recommended Uses:	Suitable for use on domestic and light industrial walls and ceilings. Chemical resistance: NOT SUITABLE. Heat resistance: NOT SUITABLE – not suitable for use on radiators. NOTE: Stir thoroughly before use.		
Solids:	54 \square 2% by weight 37 \square 2% by volume		
Specific Gravity:	1.36 \square 0.02 g/cm ³		
Theoretical Coverage:	Up to 12m ² /litre when applied under normal conditions on a non-porous surface.		
VOC:	European limit for this product (Cat A/a): 30g/L (2010). This contains max 30g/L.		
Thinning:	Sealing new or bare surface (eg . plaster) Prime 4 PSU is recommended, alternatively first coat Colourtrend Ceramic matt can be thinned down with max 10% water Up to 15 % water may be used for spray application.		
Drying Conditions:	At ambient temperature (20-23 ° C) : Touch dry: 2-4 hours depending on film thickness and drying conditions. Re-coat after 4-6 hours. Full paint properties do not develop for a minimum of 7 to 10 days after application (depending on drying conditions). The paint should not be washed before this time has elapsed. NOTE: Do NOT apply if surfaces are in poor drying conditions. Do NOT apply in temperatures below 10°C or above 25 °C. Cool conditions and high humidity will lengthen drying times. Air ventilation will help improve drying conditions.		
Finish:	Matt Finish		

Storage:	Store in dry, cool conditions and protect from frost.
Application Method:	Brush, roller or spray.
Spray Suggestion:	Spray Application: Airless or air assisted airless, pressure pot.
Clean Up:	Clean equipment with water immediately after use. Replace lid on can and stir thoroughly before re-use.
Surface Preparation:	<p>Surface to be painted should be clean, dry and free from all forms of contamination. Remove all loose and flaking paint. Previously painted walls should be thoroughly washed down with Sugar Soap, rinsed with clean water and allowed to dry. Seal powdery surfaces with Colourtrend PRIME 4 PSU. Where necessary, rub down and then wipe down with a damp, lint free cloth, to avoid dust. Avoid the inhalation of dust. The appropriate mask should be worn if dry sanding.</p> <p>Any surface defects should be filled with the appropriate filler; we would recommend ALLPRO or Toupref. Colourtrend Ceramic Matt is suitable for application over most conventional fillers. Colourtrend Ceramic Matt is suitable for use over surfaces previously painted with alkyd/oil paints. The surface should receive a fine sanding with a fine grade of sandpaper, wiped down with a damp, lint free cloth and then allowed to dry prior to painting. Acrylics have superior adhesion to previously painted surfaces.</p>
Cleaning Recommendations for Painted Surfaces:	<p>Wash stain as soon as possible with a clean lint free cloth and clean soapy water. Rinse and allow to dry. Do not apply too much pressure as over enthusiastic scrubbing may damage the paint finish. Oil based stains may not be completely removed, marks from permanent markers will not be removed.</p> <p>Full paint properties do not develop for a minimum of 7 to 10 days after application (depending on drying conditions). The paint should not be washed before this time has elapsed.</p>
Safety, Health and Environmental Information	<p>Not classified as hazardous for health.</p> <p>Handle with care.</p> <p>Avoid prolonged contact with skin and breathing of spray mist.</p> <p>A Material Health & Safety Data Sheet is available on request.</p>

IMPORTANT NOTE:

The information contained in this Data Sheet is not intended to be conclusive, and any person using this product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from General Paints as to the suitability of this product for the intended purpose, does so at his or her own risk. Whilst we attempt to ensure that all advice we give about this product (whether in the sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of this product. Therefore, unless we specifically agree in writing to do so, we do not accept liability whatsoever, or howsoever arising, for the performance of this product or from any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is likely to change from time to time in the light of experience and our policy of on-going product updates.

HEALTH & SAFETY INFORMATION: This product should not be used without reference to the relevant Health and Safety Data Sheet, which General Paints Ltd. has provided for its customers. If for any reason a copy of this Data Sheet is not available the user should contact General Paints Ltd. to obtain a copy before using this product.

Description:	Colourtrend Interior Matt is a top quality emulsion, which gives excellent coverage and application. It is suitable for all interior wall and ceiling surfaces. This pure acrylic emulsion has superior wet and dry hiding characteristics, is alkali resistant, is washable and is resistant to yellowing. This product is classed as a breathable coating		
Special Features:	<input type="checkbox"/> Acrylic resin	<input type="checkbox"/> Excellent coverage	<input type="checkbox"/> Washable
	<input type="checkbox"/> EN13300 certified	<input type="checkbox"/> Excellent sheen retention	<input type="checkbox"/> Good flow & levelling properties
	<input type="checkbox"/> Low VOC	<input type="checkbox"/> Very low odour	<input type="checkbox"/> Available in all Colourtrend Colours
	<input type="checkbox"/> Easy clean up with soapy water	<input type="checkbox"/> Good stain resistance	<input type="checkbox"/> Non-hazardous under EU legislation
Classification	Colourtrend Interior Matt is classified as Class 1 Section 5.4 (wet scrub resistance) and Class 1 Section 5.5 (opacity) under EN13 300 / BS 13 300. Independent certification is available on request.		
Colour Range:	Entire Colourtrend range, RAL & BS 4800. Some pale colours are restricted to larger size cans.		
Recommended Uses:	Suitable for use on domestic and light industrial walls and ceilings. Chemical resistance: NOT SUITABLE. Heat resistance: NOT SUITABLE – not suitable for use on radiators. NOTE: Stir thoroughly before use.		
Solids:	52 \square 2% by weight 37 \square 2% by volume		
Specific Gravity:	1.4 \square 0.02 g/cm ³		
Theoretical Coverage:	Up to 12m ² /litre when applied under normal conditions on a non-porous surface.		
VOC:	European limit for this product (Cat A/a): 30g/L (2010). This contains max 30g/L.		
Thinning:	Sealing new or bare surface (eg . plaster) Prime 4 PSU is recommended, alternatively first coat Colourtrend Interior matt can be thinned down with max 10% water Up to 15 % water may be used for spray application.		
Drying Conditions:	At ambient temperature (20-23 ° C) : Touch dry: 2-4 hours depending on film thickness and drying conditions. Re-coat after 4-6 hours. Full paint properties do not develop for a minimum of 7 to 10 days after application (depending on drying conditions). The paint should not be washed before this time has elapsed. NOTE: Do NOT apply if surfaces are in poor drying conditions. Do NOT apply in temperatures below 10°C or above 25 °C. Cool conditions and high humidity will lengthen drying times. Air ventilation will help improve drying conditions.		
Finish:	Matt Finish		
Storage:	Store in dry, cool conditions and protect from frost.		
Application Method:	Brush, roller or spray.		

Spray Suggestion:	Spray Application: Airless or air assisted airless, pressure pot.
Clean Up:	Clean equipment with water immediately after use. Replace lid on can and stir thoroughly before re-use.
Surface Preparation:	<p>Surface to be painted should be clean, dry and free from all forms of contamination. Remove all loose and flaking paint. Previously painted walls should be thoroughly washed down with Sugar Soap, rinsed with clean water and allowed to dry. Seal powdery surfaces with Colourtrend PRIME 4 PSU. Where necessary, rub down and then wipe down with a damp, lint free cloth, to avoid dust. Avoid the inhalation of dust. The appropriate mask should be worn if dry sanding.</p> <p>Any surface defects should be filled with the appropriate filler; we would recommend ALLPRO or Toupret. Colourtrend Interior Matt is suitable for application over most conventional fillers. Colourtrend Interior Matt is suitable for use over surfaces previously painted with alkyd/oil paints. The surface should receive a fine sanding with a fine grade of sandpaper, wiped down with a damp, lint free cloth and then allowed to dry prior to painting. Acrylics have superior adhesion to previously painted surfaces.</p>
Cleaning Recommendations for Painted Surfaces:	<p>Wash stain as soon as possible with a clean lint free cloth and clean soapy water. Rinse and allow dry. Do not apply too much pressure as over enthusiastic scrubbing may damage the paint finish. Oil based stains may not be completely removed; marks from permanent markers will not be removed.</p> <p>Full paint properties do not develop for a minimum of 7 to 10 days after application (depending on drying conditions). The paint should not be washed before this time has elapsed.</p>
Safety, Health and Environmental Information	<p>Not classified as hazardous for health.</p> <p>Handle with care.</p> <p>Avoid prolonged contact with skin and breathing of spray mist.</p> <p>A Material Health & Safety Data Sheet is available on request.</p>

IMPORTANT NOTE:

The information contained in this Data Sheet is not intended to be conclusive, and any person using this product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from General Paints as to the suitability of this product for the intended purpose, does so at his or her own risk. Whilst we attempt to ensure that all advice we give about this product (whether in the sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of this product. Therefore, unless we specifically agree in writing to do so, we do not accept liability whatsoever, or howsoever arising, for the performance of this product or from any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is likely to change from time to time in the light of experience and our policy of on-going product updates.

HEALTH & SAFETY INFORMATION:

This product should not be used without reference to the relevant Health and Safety Data Sheet, which General Paints Ltd. has provided for its customers. If for any reason a copy of this Data Sheet is not available the user should contact General Paints Ltd. to obtain a copy before using this product.

Description:	Colourtrend Soft Sheen is a top quality emulsion, which gives excellent coverage and application. It is suitable for all interior wall and ceiling surfaces. This pure acrylic emulsion has superior wet and dry hiding characteristics, is alkali resistant, is washable and is resistant to yellowing. This product is classed as a breathable coating.		
Special Features:	<input type="checkbox"/> Acrylic resin	<input type="checkbox"/> Excellent coverage	<input type="checkbox"/> Washable
	<input type="checkbox"/> Non-hazardous under EU legislation	<input type="checkbox"/> Excellent sheen retention	<input type="checkbox"/> Excellent flow & levelling properties
	<input type="checkbox"/> Low VOC	<input type="checkbox"/> Very low odour	<input type="checkbox"/> Available in all Colourtrend Colours
	<input type="checkbox"/> Easy clean up with soapy water	<input type="checkbox"/> Good stain resistance	
Colour Range:	Entire Colourtrend range, RAL & BS 4800. Some pale colours are restricted to larger size cans.		
Recommended Uses:	Suitable for use on domestic walls and ceilings. Chemical resistance: NOT SUITABLE. Heat resistance: NOT SUITABLE – not suitable for use on radiators. NOTE: Stir thoroughly before use.		
Solids:	52 \pm 2% by weight 37 \pm 2% by volume		
Specific Gravity:	1.28 \pm 0.02 g/cm ³		
Theoretical Coverage:	Up to 12m ² /litre when applied under normal conditions on a non-porous surface.		
VOC:	European limit for this product (Cat A/a): 30g/L (2010). This contains max 30g/L.		
Thinning:	Sealing new or bare surface (eg . plaster) Prime 4 PSU is recommended. Colourtrend Soft Sheen can be thinned down with max 10% water. Up to 15 % water may be used for spray application.		
Drying Conditions:	At ambient temperature (20-23 ° C) : Touch dry: 2-4 hours depending on film thickness and drying conditions. Re-coat after 4-6 hours. Full paint properties do not develop for a minimum of 7 to 10 days after application (depending on drying conditions). The paint should not be washed before this time has elapsed. NOTE: Do NOT apply if surfaces are in poor drying conditions. Do NOT apply in temperatures below 10°C or above 25 °C. Cool conditions and high humidity will lengthen drying times. Air ventilation will help improve drying conditions.		
Finish:	Low sheen Finish (6-10%)		
Storage:	Store in dry, cool conditions and protect from frost.		
Application Method:	Brush, roller or spray.		
Spray Suggestion:	Spray Application: Airless or air assisted airless, pressure pot.		

Clean Up:	Clean equipment with water immediately after use. Replace lid on can and stir thoroughly before re-use.
Surface Preparation:	<p>Surface to be painted should be clean, dry and free from all forms of contamination. Remove all loose and flaking paint. Previously painted walls should be thoroughly washed down with Sugar Soap, rinsed with clean water and allowed to dry. Seal powdery surfaces with Colourtrend PRIME 4 PSU. Where necessary, rub down and then wipe down with a damp, lint free cloth, to avoid dust. Avoid the inhalation of dust. The appropriate mask should be worn if dry sanding.</p> <p>Any surface defects should be filled with the appropriate filler; we would recommend ALLPRO or Toupret. Colourtrend Soft Sheen is suitable for application over most conventional fillers. Colourtrend Soft Sheen is suitable for use over surfaces previously painted with alkyd/oil paints. The surface should receive a fine sanding with a fine grade of sandpaper, wiped down with a damp, lint free cloth and then allowed to dry prior to painting. Acrylics have superior adhesion to previously painted surfaces.</p>
Cleaning Recommendations for Painted Surfaces:	<p>Wash stain as soon as possible with a clean lint free cloth and clean soapy water. Rinse and allow to dry. Do not apply too much pressure as over enthusiastic scrubbing may damage the paint finish. Oil based stains may not be completely removed, marks from permanent markers will not be removed .</p> <p>Full paint properties do not develop for a minimum of 7 to 10 days after application (depending on drying conditions). The paint should not be washed before this time has elapsed.</p>
Safety, Health and Environmental Information	<p>Not classified as hazardous for health.</p> <p>Handle with care.</p> <p>Avoid prolonged contact with skin and breathing of spray mist.</p> <p>A Material Health & Safety Data Sheet is available on request.</p>

IMPORTANT NOTE:

The information contained in this Data Sheet is not intended to be conclusive, and any person using this product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from General Paints as to the suitability of this product for the intended purpose, does so at his or her own risk. Whilst we attempt to ensure that all advice we give about this product (whether in the sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of this product. Therefore, unless we specifically agree in writing to do so, we do not accept liability whatsoever, or howsoever arising, for the performance of this product or from any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is likely to change from time to time in the light of experience and our policy of on-going product updates.

HEALTH & SAFETY INFORMATION: This product should not be used without reference to the relevant Health and Safety Data Sheet, which General Paints Ltd. has provided for its customers. If for any reason a copy of this Data Sheet is not available the user should contact General Paints Ltd. to obtain a copy before using this product.

Description: Colourtrend Weather Exterior Masonry Paint Colourtrend Weather exterior masonry paint is a pure acrylic, premium quality paint specially formulated to meet the demands of Irish Weather, good and bad. Colourtrend Weather is mould and mildew resistant, has excellent spread and coverage, is easy to clean and resists dirt pick-up. This product is classed as a breathable coating.

Special Features:

<input type="checkbox"/> Acrylic resin	<input type="checkbox"/> Excellent coverage	<input type="checkbox"/> Washable
<input type="checkbox"/> Non-hazardous under	<input type="checkbox"/> Excellent sheen & colour retention	<input type="checkbox"/> Good flow & levelling properties
<input type="checkbox"/> EU legislation	<input type="checkbox"/> Very low odour	<input type="checkbox"/> Available in all Colourtrend Colours
<input type="checkbox"/> Low VOC Easy clean up water with soapy	<input type="checkbox"/> Excellent mould and mildew resistance.	<input type="checkbox"/> Non-hazardous under EU

Colour Range: Entire Colourtrend range, RAL & BS 4800. Some pale colours are restricted to larger size cans.

Recommended Uses: Suitable for use on domestic and industrial exterior masonry.
NOTE: Stir thoroughly before use.

Solids: 48±2% by weight
35±2% by volume

Specific Gravity: 1.28±0.02 g/cm³

Theoretical Coverage: 9-12m²/litre on smooth surfaces
3-5m²/litre on pebble dashing

VOC: European limit for this product (Cat A/c): 40g/L (2010). This contains max 30g/L.

Thinning: Sealing new or bare surface Prime 4 PSU is recommended, alternatively first coat Colourtrend Weather matt can be thinned down with max 10% water.
Up to 15 % water may be used for spray application.

Drying Conditions: At ambient temperature (20-23 ° C) :
Touch dry: 2-4 hours depending on film thickness and drying conditions.
Re-coat after 4-6 hours.
Full paint properties do not develop for a minimum of 7 to 10 days after application (depending on drying conditions).
NOTE: Do not apply if surfaces are wet or in poor drying conditions. Do not apply at temperatures below 10°C or relative humidity above 80%

Finish: Matt Finish

Storage: Store in dry, cool conditions and protect from frost.

Application Method: Brush, roller or spray.

Spray Suggestion: Spray Application: Airless or air assisted airless, pressure pot.

Clean Up:	Clean equipment with water immediately after use. Replace lid on can and stir thoroughly before re-use.
Surface Preparation:	<p>Surface to be painted should be clean, dry, sound and free from all forms of contamination.</p> <p>New plaster Allow fresh plaster to dry out fully. When dried it will be uniform colour. This may, depending on weather conditions, take up to one week after plastering.</p> <ul style="list-style-type: none"> • Older unpainted plaster may require pre-treatment with Colourtrend Weather Fungicidal Wash if fungal growths are present. Apply fungicidal wash as per instructions on container. • Repair any large cracks with elastomeric exterior caulk. Dab with a damp sponge to feather edges of filler. • Power-wash to remove loose material, growths and dirt. • Ensure that any and all loose or flaking paint is removed and any remaining coats are well adhered to the substrate before commencing to apply fresh paint. Chalky or flaky surfaces will require Colourtrend Weather Stabilising Primer as the first coat.
Safety, Health and Environmental Information	<p>Not classified as hazardous for health.</p> <p>Handle with care.</p> <p>Avoid prolonged contact with skin and breathing of spray mist.</p> <p>A Material Health & Safety Data Sheet is available on request.</p>

IMPORTANT NOTE:

The information contained in this Data Sheet is not intended to be conclusive, and any person using this product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from General Paints as to the suitability of this product for the intended purpose, does so at his or her own risk. Whilst we attempt to ensure that all advice we give about this product (whether in the sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of this product. Therefore, unless we specifically agree in writing to do so, we do not accept liability whatsoever, or howsoever arising, for the performance of this product or from any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is likely to change from time to time in the light of experience and our policy of on-going product updates.

HEALTH & SAFETY INFORMATION: This product should not be used without reference to the relevant Health and Safety Data Sheet, which General Paints Ltd. has provided for its customers. If for any reason a copy of this Data Sheet is not available the user should contact General Paints Ltd. to obtain a copy before using this product.

Description: The Colourtrend Waterbased Trim range is an ideal interior and exterior alternative to solvent based paints. It is manufactured using natural, renewable oils and is designed to provide all the benefits of traditional solvent coatings: it has excellent flow and levelling properties and gives a hardwearing, easy-clean finish but as it's waterbased, it's low odour, quick drying, easy to clean up and kinder to the environment too! This product is classed as a breathable coating. Colourtrend Waterbased Eggshell is a water-thinnable, low-yellowing alkyd paint, ideal for wood and metal surfaces where a low-sheen is desirable; yet is super hard-wearing. Its formulation has been specifically developed to replace harmful solvent based wood and trim paints.

Product Description:

Special Features:

<input type="checkbox"/> Alkyd resin	<input type="checkbox"/> Excellent colour retention	<input type="checkbox"/> Mould & mildew
<input type="checkbox"/> Fast drying	<input type="checkbox"/> Excellent sheen retention	<input type="checkbox"/> resistant Excellent flow properties
<input type="checkbox"/> Low VOC	<input type="checkbox"/> Very low odour	<input type="checkbox"/> Good levelling
<input type="checkbox"/> Easy clean up with soapy water	<input type="checkbox"/> Compatible with oil or waterbased undercoats	<input type="checkbox"/> Good block resistance
		<input type="checkbox"/> Non-hazardous under EU legislation

Recommended Uses:

<input type="checkbox"/> All wood types	<input type="checkbox"/> Pre-primed metal substrates
<input type="checkbox"/> Doors	<input type="checkbox"/> Window frames
<input type="checkbox"/> Trim	

☐ Can also be used as a finish coat on interior substrates such as: plastered walls, PVC or ceramic tiles when used with the appropriate product from the Colourtrend primer range.

Solids: 54 \pm 2% by weight

43 \pm 2% by volume

Specific Gravity: 1.26 \pm 0.2 g/cm³

Theoretical Coverage: 10m²/L

Recommended Film Thickness: Wet: 95 microns

Dry: 40 microns (thin coats are recommended to achieve desired finish)

VOC: EU limit value for this product (Cat A/ d): 150g/L (2007) / 130g/L (2010). This product contains max 50 g/L

Thinning: Up to 15 % water may be used for spray application.

Drying Conditions: At ambient temperature (20-23 ° C) :

Touch dry: 2-4 hours depending on film thickness and drying conditions.

Re-coat after 6-8 hours.

Full paint properties do not develop for a minimum of 7 to 10 days after application.

Do not apply below +5°C.

Finish: Eggshell Finish: 25% \pm 5% sheen . Film thickness 95 microns wet, dried at 23°C RH 50%. Colour, film thickness and drying conditions may affect final sheen.

Colour Range: Wide Variety of Colours including Colourtrend RAL & BS.

Viscosity: 110 \pm 10 KU

Storage: Store in dry, cool conditions and protect from frost.

Application Method: Brush, roller or spray.

Spray Suggestion: Spray Application: Airless or air assisted airless, pressure pot.

Clean Up: Clean equipment with water immediately after use. Replace lid on can and stir thoroughly before re-use.

Surface Preparation:	Ensure surface is clean dry and free from dirt and grease. Unpainted metal substrates must be primed with appropriate metal Primer. For unpainted hardwoods such as teak, mahogany or cedar, 2 coats of Colourtrend PRIME 1 or PRIME 3 are recommended to prevent the bleed of oils and tannins through the coating.
Safety, Health and Environmental Information	Not classified as hazardous for health. Handle with care. Avoid prolonged contact with skin and breathing of spray mist. A Material Health & Safety Data Sheet is available on request.

IMPORTANT NOTE:

The information contained in this Data Sheet is not intended to be conclusive, and any person using this product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from General Paints as to the suitability of this product for the intended purpose, does so at his or her own risk. Whilst we attempt to ensure that all advice we give about this product (whether in the sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of this product. Therefore, unless we specifically agree in writing to do so, we do not accept liability whatsoever, or howsoever arising, for the performance of this product or from any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is likely to change from time to time in the light of experience and our policy of on-going product updates.

HEALTH & SAFETY INFORMATION: This product should not be used without reference to the relevant Health and Safety Data Sheet, which General Paints Ltd. has provided for its customers. If for any reason a copy of this Data Sheet is not available the user should contact General Paints Ltd. to obtain a copy before using this product.

Description:	The Colourtrend Waterbased Trim range is an ideal interior and exterior alternative to solvent based paints. It is manufactured using natural, renewable oils and is designed to provide all the benefits of traditional solvent coatings: it has excellent flow and levelling properties and gives a hardwearing, easy-clean finish but as it's waterbased, it's low odour, quick drying, easy to clean up and kinder to the environment too. This product is classed as a breathable coating. Colourtrend Waterbased Gloss is a water-thinnable, low-yellowing alkyd paint, ideal for wood and metal surfaces where a high-sheen is desirable; yet is super hard-wearing. Its formulation has been specifically developed to replace harmful solvent based wood and trim paints.		
Product Description:			
Special Features:	<input type="checkbox"/> Alkyd resin <input type="checkbox"/> Fast drying <input type="checkbox"/> Low VOC <input type="checkbox"/> Easy clean up with soapy water	<input type="checkbox"/> Excellent colour retention <input type="checkbox"/> Excellent sheen retention <input type="checkbox"/> Very low odour <input type="checkbox"/> Compatible with oil or waterbased undercoats	<input type="checkbox"/> Mould & mildew <input type="checkbox"/> resistant Excellent flow properties <input type="checkbox"/> Good levelling <input type="checkbox"/> Good block resistance <input type="checkbox"/> Non-hazardous under EU legislation
Recommended Uses:	<input type="checkbox"/> All wood types <input type="checkbox"/> Doors <input type="checkbox"/> Trim <input type="checkbox"/> Pre-primed metal substrates <input type="checkbox"/> Window frames <input type="checkbox"/> Can also be used as a finish coat on interior substrates such as: plastered walls, PVC or ceramic tiles when used with the appropriate product from the Colourtrend primer range.		
Solids:	48 \pm 2% by weight 35 \pm 2% by volume		
Specific Gravity:	1.23 \pm 0.2 g/cm ³		
Theoretical Coverage:	10m ² /L		
Recommended Film Thickness:	Wet: 115 microns Dry: 40 microns (thin coats are recommended to achieve desired finish)		
VOC:	EU limit value for this product (Cat A/ d): 150g/L (2007) / 130g/L (2010). This product contains max 50 g/L		
Thinning:	Up to 15 % water may be used for spray application.		
Drying Conditions:	At ambient temperature (20-23 ° C) : Touch dry: 2-4 hours depending on film thickness and drying conditions. Re-coat after 6-8 hours. Full paint properties do not develop for a minimum of 7 to 10 days after application. Do not apply below +5°C.		
Finish:	Gloss Finish: 85% \pm 5% sheen . Film thickness 115 microns wet, dried at 23°C RH 50%. Colour, film thickness and drying conditions may affect final sheen.		
Colour Range:	Wide Variety of Colours including Colourtrend RAL & BS.		
Viscosity:	110 \pm 10 KU		
Storage:	Store in dry, cool conditions and protect from frost.		
Application Method:	Brush, roller or spray.		
Spray Suggestion:	Spray Application: Airless or air assisted airless, pressure pot.		
Clean Up:	Clean equipment with water immediately after use. Replace lid on can and stir thoroughly before re-use.		

**Surface
Preparation:**

Ensure surface is clean dry and free from dirt and grease. Unpainted metal substrates must be primed with appropriate metal Primer. For unpainted hardwoods such as teak, mahogany or cedar, 2 coats of Colourtrend PRIME 1 or PRIME 3 are recommended to prevent the bleed of oils and tannins through the coating.

**Safety, Health
and
Environmental
Information**

Not classified as hazardous for health.

Handle with care.

Avoid prolonged contact with skin and breathing of spray mist.

A Material Health & Safety Data Sheet is available on request.

IMPORTANT NOTE:

The information contained in this Data Sheet is not intended to be conclusive, and any person using this product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from General Paints as to the suitability of this product for the intended purpose, does so at his or her own risk. Whilst we attempt to ensure that all advice we give about this product (whether in the sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of this product. Therefore, unless we specifically agree in writing to do so, we do not accept liability whatsoever, or howsoever arising, for the performance of this product or from any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is likely to change from time to time in the light of experience and our policy of on-going product updates.

HEALTH & SAFETY INFORMATION: This product should not be used without reference to the relevant Health and Safety Data Sheet, which General Paints Ltd. has provided for its customers. If for any reason a copy of this Data Sheet is not available the user should contact General Paints Ltd. to obtain a copy before using this product.

Description:	The Colourtrend Waterbased Trim range is an ideal interior and exterior alternative to solvent based paints. It is manufactured using natural, renewable oils and is designed to provide all the benefits of traditional solvent coatings: it has excellent flow and levelling properties and gives a hardwearing, easy-clean finish but as it's waterbased, it's low odour, quick drying, easy to clean up and kinder to the environment too. This product is classed as a breathable coating.		
Product Description:	Colourtrend Waterbased Satin is a water-thinnable, low-yellowing alkyd paint, ideal for wood and metal surfaces where a mid-sheen is desirable; yet is super hard-wearing. Its formulation has been specifically developed to replace harmful solvent based wood and trim paints.		
Special Features:	<input type="checkbox"/> Alkyd resin <input type="checkbox"/> Fast drying <input type="checkbox"/> Low VOC <input type="checkbox"/> Easy clean up with soapy water	<input type="checkbox"/> Excellent colour retention <input type="checkbox"/> Excellent sheen retention <input type="checkbox"/> Very low odour <input type="checkbox"/> Compatible with oil or waterbased undercoats	<input type="checkbox"/> Mould & mildew resistant <input type="checkbox"/> Excellent flow properties & levelling <input type="checkbox"/> Good block resistance <input type="checkbox"/> Non-hazardous under EU legislation
Recommended Uses:	<input type="checkbox"/> All wood types <input type="checkbox"/> Doors <input type="checkbox"/> Trim <input type="checkbox"/> Pre-primed metal substrates <input type="checkbox"/> Window frames <input type="checkbox"/> Can also be used as a finish coat on interior substrates such as: plastered walls, PVC or ceramic tiles when used with the appropriate product from the Colourtrend primer range.		
Solids:	52 ± 2% by weight 42 ± 2% by volume		
Specific Gravity:	1.25 ± 0.2 g/cm ³		
Theoretical Coverage:	10m ² /L		
Recommended Film Thickness:	Wet: 95 microns Dry: 40 microns (multiple thin coats are recommended to achieve desired hardness)		
VOC:	EU limit value for this product (Cat A/ d): 150g/L (2007) / 130g/L (2010). This product contains max 50 g/L		
Thinning:	Up to 15 % water may be used for spray application.		
Drying Conditions:	At ambient temperature (20-23 ° C) : Touch dry: 2-4 hours depending on film thickness and drying conditions. Re-coat after 6-8 hours. Do not apply below +5°C.		
Finish:	Satin Finish: 45% ± 5% sheen . Film thickness 95 microns wet, dried at 23°C RH 50%. Colour, film thickness and drying conditions may affect final sheen.		
Colour Range:	Wide Variety of Colours including Colourtrend RAL & BS.		
Viscosity:	110 ± 10 KU		
Storage:	Store in dry, cool conditions and protect from frost.		
Application Method:	Brush, roller or spray.		
Spray Suggestion:	Spray Application: Airless or air assisted airless, pressure pot.		
Clean Up:	Clean equipment with water immediately after use. Replace lid on can and stir thoroughly before re-use.		

Surface Preparation:

Ensure surface is clean dry and free from dirt and grease. Unpainted metal substrates must be primed with appropriate metal Primer. For unpainted hardwoods such as teak, mahogany or cedar, 2 coats of Colourtrend PRIME 1 or PRIME 3 are recommended to prevent the bleed of oils and tannins through the coating.

Safety, Health and Environmental Information

Not classified as hazardous for health.

Handle with care.

Avoid prolonged contact with skin and breathing of spray mist.

A Material Health & Safety Data Sheet is available on request.

IMPORTANT NOTE:

The information contained in this Data Sheet is not intended to be conclusive, and any person using this product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from General Paints as to the suitability of this product for the intended purpose, does so at his or her own risk. Whilst we attempt to ensure that all advice we give about this product (whether in the sheet or otherwise) is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of this product. Therefore, unless we specifically agree in writing to do so, we do not accept liability whatsoever, or howsoever arising, for the performance of this product or from any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is likely to change from time to time in the light of experience and our policy of on-going product updates.

HEALTH & SAFETY INFORMATION: This product should not be used without reference to the relevant Health and Safety Data Sheet, which General Paints Ltd. has provided for its customers. If for any reason a copy of this Data Sheet is not available the user should contact General Paints Ltd. to obtain a copy before using this product.