Elite Cleaner TECHNICAL DATA SHEET





PRODUCT BENEFITS:

- Unrivaled "Dual Action" Cleaner and Stain Remover.
- Nano-sized particles for Deep, Below Surface Cleaning & Mild Surface Abrasion.
- Proprietary Surfactants "Lift" Contaminates and Stains for Easy, Efficient Cleaning.
- Thick, Creamy Consistency is Ideal for Vertical Projects.
- Non-Toxic. Non-Flammable. VOC Compliant. Biodegradable.
- Clean, Fresh, Long-Lasting Rosemary Scent.

USES:

- Tile, Stone, Concrete, Masonry and Grout Surfaces.
- Removes Algae, Coating Sealers, Efflorescence, Food & Beverage Stains, Grease, Ground-in Dirt & Soil, Grout Haze & Residue (Cement, Epoxy & Urethane), Marks from Rubber, Ink & Pencil, Mineral & Hard Water Deposits, Mold & Mildew, Mortar Haze & Residue, Rust Stains, Sealer Residue, Soap Scum, Waxes & Floor Finishes and more.
- Interior and Exterior applications.

DIRECTIONS:

Read entire label before using. Use only as directed.

APPLICATION STEPS:

- 1. Shake Well before each use.
- 2. Sweep or vacuum surface to be cleaned to remove any loose contaminants.
- 3. Apply **Elite Cleaner** liberally on surface to be cleaned directly from bottle or with a SpongaUSA™ sponge, or a brush or scrub machine.
- Allow Elite Cleaner to dwell on surface for up to 5 minutes.
- Agitate with a Primo Tools™ White Nylon Scrub Pad, or a brush or other comparable non-marring scrubbing tool until contaminate or stain is removed.
- 6. Thoroughly rinse surface with water. A wet/dry vacuum may also be used.
- Some surfaces may require additional applications. <u>Expert Tip</u>: High-pressure (1000–3000 psi) sprayers are highly effective at rinsing away contaminates and stains when used in conjunction with **Elite Cleaner**.
- 8. Wipe surface completely dry using a clean, dry, white cotton or micro-fiber towel.
- If surface is to be sealed, allow 24 hours drying time prior to applying a high quality OMNI sealer (see OMNI Product Recommendation Guide).

SIZES:

Quarts, Gallons (other sizes available by special order).

COVERAGE:

Approx. 200 to 2000 sq. ft. (18.6m² to 185.8m²) per gallon depending on the type of surface, porosity, texture, temperature and method of application.

TECHNICAL SUPPORT:

Call 949-709-5270, Monday thru Friday, 6:00am PT to 4:00pm PT or e-mail <u>TechSupport@OMNI-Sealers.com</u> 24/7.

COMPLIANCE AND HANDLING:

- Complies with all Federal, State and Local VOC regulatory requirements.
- Use and store between 40°F and 100°F (4°C and 38°C).
- Store in original container only and close after each use.
- Shelf-life expected to be at least 1 year.

LIMITATIONS:

 Prevent product from contacting surrounding surfaces such as carpet, glass, landscaping, metal, paint and wood.

WARNINGS:

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. If product gets in eyes, flush with water for at least 15 minutes. If product gets on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

KEEP OUT OF REACH OF CHILDREN

WARRANTY:

100% SATISFACTION GUARANTEED, when used as directed. Contact OMNI Sealers for exclusive remedy of either refund of purchase price or replacement of product. Proof of purchase within one year of purchase, required. Determining suitability of product for intended use shall be solely the responsibility of the user. There are no warranties, expressed or implied, including those of merchantability or fitness for a particular purpose which is beyond the product description. In no case shall OMNI be liable for incidental or consequential damages.