

Epoxy Grout Haze Remover

TECHNICAL DATA SHEET



PRODUCT BENEFITS:

- Effective, Water-based Formulation that Removes Epoxy Grout Haze and Residue.
- Also Removes Urethane Grout Haze and Residue.
- Fast Acting with Long Dwell Time for Difficult Projects.
- Non-Toxic. Non-Flammable. VOC Compliant. Biodegradable.

USES:

- Tile, Most Stones, Concrete and Masonry Surfaces.
- Interior and Exterior applications.

DIRECTIONS:

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of application and desired results.

APPLICATION STEPS:

1. Apply a small amount of water to surface to be cleaned.
2. Apply **Epoxy Grout Haze Remover** liberally using a SpongaUSA™ sponge, or a mop, paint-pad applicator, paint roller, brush or low pressure pump sprayer.
3. Allow **Epoxy Grout Haze Remover** to dwell on surface for up to 10 minutes.
4. Agitate with a Primo Tools™ White Nylon Scrub Pad or a brush or other comparable non-marring scrubbing tool until epoxy or urethane grout haze and/or residue is removed from surface.
5. Thoroughly rinse surface with water. A wet/dry vacuum may also be used.
6. Some surfaces may require additional applications. Expert Tip: High-pressure (1000 – 3000 psi) sprayers are highly effective at rinsing away epoxy and urethane haze and/or residue when used in conjunction with **Epoxy Grout Haze Remover**.
7. Wipe surface completely dry using a clean, dry, white cotton or micro-fiber towel.
8. If surface is to be sealed, allow 24 hours drying time prior to applying a high quality OMNI sealer (see OMNI Product Recommendation Guide).

SIZES:

Quarts (other sizes available by special order).

COVERAGE:

Approx. 15 to 65 sq. ft. (1.2m² to 5.9m²) per quart depending on the type of surface, porosity, texture, temperature and method of application

TECHNICAL SUPPORT:

Call 949-709-5270, Monday thru Friday, 6:00am PT to 4:00pm PT or e-mail TechSupport@OMNI-Sealers.com.

COMPLIANCE AND HANDLING:

- Complies with all Federal, State and Local VOC regulatory requirements.
- Use and store between 40°F and 100°F (4°C and 38°C).
- Store in original container only and close after each use.
- Shelf life expected to be at least 1 year.

LIMITATIONS:

- May etch, lighten, or alter the color of cement-based surfaces, metal, natural stone (such as marble, limestone and other acid sensitive stones) and tile.
- Do not mix with ammoniated cleaners or bleach as harmful fumes may result.
- Prevent product from contacting surrounding surfaces such as carpet, glass, landscaping, metal, paint and wood.

WARNINGS:

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. If product gets in eyes, flush with water for at least 15 minutes. If product gets on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting, seek medical attention.

KEEP OUT OF REACH OF CHILDREN

WARRANTY:

100% SATISFACTION GUARANTEED, when used as directed. Contact OMNI Sealers for exclusive remedy of either refund of purchase price or replacement of product. Proof of purchase within one year of purchase, required. Determining suitability of product for intended use shall be solely the responsibility of the user. There are no warranties, expressed or implied, including those of merchantability or fitness for a particular purpose, which is beyond the product description. In no case shall OMNI be liable for incidental or consequential damages.