



# SikaTile®-825 Epoxy Grout


## 100% SOLIDS EPOXY MORTAR AND GROUT

- Used for setting and grouting ceramic and quarry tile, pavers, mosaics
- Fill joint widths 1/16" to 3/8" (1.5 mm to 10 mm)
- Excellent setting material for moisture sensitive and resin backed stones
- High strength mortar that is stain resistant, impermeable, and shock resistant
- **Colors:** 12 colors - see back for details
- **Packaging:** 2 gal. commercial kit

### Standards

- Exceeds ANSI A118.3

#### Attributes Include:



**BUILDING TRUST**



# SikaTile® -825 Epoxy Grout

## 100% SOLIDS EPOXY MORTAR AND GROUT

### WHERE TO USE

- For interior and exterior applications in both residential and commercial applications in dry or wet conditions.
- For floors, walls, countertops, and submerged conditions.
- For application in submerged conditions (swimming pools, spas, water features and fountains), after 21 days.

### SUITABLE TILE TYPES:

- Brick and thin brick
- Cement-based precast terrazzo
- Impervious porcelain and glass tile
- Various marbles (green, black, and red)
- Natural stone tile, granite and slate
- Vitreous, semi-vitreous or non-vitreous tile:
  - Ceramic, mosaic, quarry, cement body tile

### COLORS AVAILABLE

00012 Navajo White



00030 Silver



00021 Canvas



00034 River Rock



00025 Tumbleweed



00035 Natural Gray



00150 Santa Fe



00038 Gray



00175 Dark Chocolate



00162 True Taupe



00191 Terracotta



00525 Black Sapphire



### FEATURES AND BENEFITS

- Used for setting and grouting ceramic and quarry tile, pavers, mosaics
- Fill joint widths 1/16" to 3/8" (1.5 mm to 10 mm)
- Excellent setting material for moisture sensitive and resin-backed stones
- High strength mortar that is stain resistant, impermeable, and chemical and shock resistant
- Stain resistant and color consistent grout
- Easy to apply with superior workability and water cleanability
- Non-sag and non-slump in joints, for use in both floor and wall applications
- For interior and exterior applications
- Mold and mildew resistant
- No sealer required

**NOTE:** Always refer to Current Product data Sheet and SDS for detailed performance specifications prior to use.

### APPROXIMATE COVERAGE

SikaTile®-825 Epoxy Grout Coverage in sqft. (m <sup>2</sup> ) per 1 gal. (3.79 L)*				
Tile Size	Grout Joint Width			
	1/16" (1.5 mm)	1/8" (3 mm)	1/4" (6 mm)	3/8" (10 mm)
1" x 1" x 1/4" (25 x 25 x 6 mm)	57 (5.2)	31 (2.8)	18 (1.7)	14 (1.3)
2" x 2" x 1/4" (50 x 50 x 6 mm)	108 (10.0)	57 (5.2)	31 (2.8)	22 (2.0)
4" x 4" x 3/8" (100 x 100 x 10 mm)	211 (19.6)	108 (10.0)	57 (5.2)	40 (3.7)
6" x 6" x 3/8" (150 x 150 x 10 mm)	141 (13.1)	72 (6.7)	38 (3.5)	26 (2.4)
8" x 8" x 3/8" (200 x 200 x 10 mm)	314 (29.2)	160 (14.8)	82 (7.6)	57 (5.2)
12" x 12" x 3/8" (300 x 300 x 10 mm)	278 (25.8)	141 (13.1)	72 (6.7)	49 (4.6)
18" x 18" x 3/8" (150 x 610 x 10 mm)	416 (38.6)	210 (19.5)	107 (9.9)	72 (6.7)
24" x 24" x 3/8" (610 x 610 x 10 mm)	622 (57.8)	313 (29.0)	158 (14.7)	107 (9.9)
6" x 24" x 3/8" (150 x 610 x 10 mm)	334 (31.0)	169 (15.7)	86 (8.0)	59 (5.4)
12" x 24" x 3/8" (300 x 610 x 10 mm)	554 (51.4)	279 (25.9)	141 (13.1)	95 (8.8)

\* Setting Coverage in sq. ft. (m<sup>2</sup>) per 2 Gallon Unit (7.58 L)

Trowel Size	3/16" x 1/4" V-Notch	1/4" x 1/4" Square Notch
Coverage	72 (6.7)	44 (4.1)

## FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: [www.SikaTile.com](http://www.SikaTile.com)

### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: 201-933-8800  
Fax: 201-933-6225

BUILDING TRUST

