



**Mastercool**® Inc.  
"World Class Quality"

1 ASPEN DRIVE, RANDOLPH, NJ 07869  
PHONE: 973-252-9119 / FAX: 973-252-2455  
WEB: WWW.MASTERCOOL.COM

## 98210-A ELECTRONIC CHARGING SCALE



### SPECIFICATIONS:

- 243 lbs (110 kg capacity)
- Accuracy:  
≤±0.05% of reading
- Resolution:  
0.05 lb / 0.5 oz / 0.01 kg
- Automatic Shut-off:  
After 3 hrs
- Operating Temperature:  
32 to 120°F (0 to 49°C)
- Battery Life: Approx. 40 hrs
- 9" x 9" (22 cm x 22 cm)  
platform

### 98210-A Accu-Charge II Electronic Charging Scale

#### FUNCTIONS:

- **CHARGE PROGRAMMING:** Allows user to program desired quantities. Before charge is complete, an alarm will sound allowing ample time to turn off refrigerant supply
- **PAUSE/CHARGE (Using the 98230 Charging Solenoid Module):** This feature allows user to stop and continue charging
- **TANK CAPACITY PROGRAMMING:** EMPTY/FULL tank feature allows user to know the amount of refrigerant in the tank at any time
- **REPEAT:** Allows user to charge previously stored amount