

## testo Smart Probes – AC & refrigeration test kit

2 x testo 549i high-pressure measuring instrument  
2 x testo 115i clamp thermometer  
in the testo Smart Case

---

Compact professional measuring instruments from the Testo Smart Probes series for use with smartphones/tablets

---

Application-specific menus: superheating/subcooling

---

Low refrigerant loss thanks to hoseless application

---

Measurement data analyzed and sent  
via testo Smart Probes App

---

More than 90 common refrigerants stored in the  
testo Smart Probes App, plus refrigerant updates

---

100 m Bluetooth® range for particularly flexible applications

---



 Bluetooth®  
+ App

testo Smart Probes App  
for free download



The compact AC & refrigeration test kit contains the testo 549i high-pressure measuring instrument as well as the testo 115i clamp thermometer (two of each). In conjunction with a smartphone or tablet, the refrigeration kit is ideally suited to servicing and troubleshooting on air conditioning and refrigeration systems, as well as their installation. Both measuring instruments can be quickly and easily attached directly at the pressure connection or the temperature measuring point. They also make it considerably easier to work on measuring points that are a long distance apart, thanks to wireless connection to a smartphone or tablet. The measuring values of both instruments are transmitted via Bluetooth® connection to the App installed on the terminal device enabling convenient

and flexible readout. In the App, measurement parameters (such as temperature or pressure) can be deleted, added or their order altered with just one click. It is also possible to change the displayed measurement parameters just as quickly. In addition, the App enables automatic calculation of evaporation and condensation temperatures. All measurement data are presented either as a diagram or a table. Finally, the measurement data report can be e-mailed directly as a pdf or Excel file. The handy testo Smart Case enables the measuring instruments to be conveniently transported and ensures that they are always to hand when they are needed.


## Technical data/accessories

### testo Smart Probes – AC & refrigeration test kit

testo Smart probes AC & refrigeration test kit for servicing, commissioning and troubleshooting on air conditioning and refrigeration systems. Consists of: 2 x testo 115i, 2 x testo 549i, testo Smart Case (refrigeration), batteries, calibration protocol



Order no. 0563 0002 10



#### testo Smart Probes App

The App turns your smartphone/tablet into the display for up to 6 Testo Smart Probes at the same time. Both the operation of the measuring instruments and the display of the readings are achieved by Bluetooth® via the testo Smart Probes App on your smartphone or tablet – irrespective of the measuring location. In addition, you can use the App to create measurement reports, add photos and comments to these and send them by e-mail. For iOS and Android.

	testo 115i	testo 549i
<b>Sensor type</b>	<b>NTC</b>	<b>Pressure</b>
Measuring range	-40 to +150 °C	-1 to 60 bar
Accuracy ±1 digit	±1.3 °C (-20 to +85 °C)	0.5% of full scale value
Resolution	0.1 °C	0.01 bar
Connection		7/16" – UNF
Overload rel.		60 bar
Compatibility	requires iOS 8.3 or newer / Android 4.3 or newer	
	requires mobile terminal device with Bluetooth® 4.0	
Bluetooth® range	up to 100 m	
Storage temperature	-20 to +60 °C	
Operating temperature	-20 to +50 °C	
Battery type	3 micro batteries AAA	
Battery life	150 hrs	130 hrs
Dimensions	183 x 90 x 30 mm	150 x 32 x 31 mm
Measurable media		CFC, HFC, HCFC, N, H <sub>2</sub> O, CO <sub>2</sub>

#### Accessories

#### Order no.

ISO relative pressure calibration certificate, 3 measuring points distributed over the measuring range	0520 0085	
ISO temperature calibration certificate, one-point calibration for clamp thermometer, calibration point +60 °C	0520 0072	
testo HVAC softcase with precise-fit compartments for testo Smart Probes (2 x testo 115i, testo 405i, testo 410i, testo 510i, 2 x testo 549i, 2 x testo 605i, testo 805i, testo 905i), dimensions 400 x 290 x 80 mm	0516 0283	

