

Bluetooth thermal anemometer with App

testo 405i

Compact professional measuring instrument from the Testo Smart Tools series, for use with smartphones/tablets

Measurement of air flow velocity and volume flow

Measurement data analysis and transmission via Smart Tools App

Telescopic shaft, extendable up to 400 mm

Space-saving and easy to transport



Bluetooth +
App

The Bluetooth-capable hot-wire anemometer testo 405i, in combination with a smartphone or tablet, is a compact measuring instrument for air flow velocities, temperatures and volume flows. Equipped with a telescopic shaft, extendable to 400 mm, it allows flexible applications in rooms and ducts. Via the App installed on the end device, users can comfortably read off their measurement values, configure volume flow measurements quickly and easily, and reliably determine timed and multi-point mean values.

The measurement protocols can then be directly sent as PDF or Excel files. In combination with the Bluetooth thermal hygrometer testo 605i, the testo 405i is suitable for determining cooling or heating performance.


Technical data/accessories

testo 405i

testo 405i, Bluetooth thermal anemometer with App, incl. batteries and calibration protocol



Order no. 0560 1405



Testo Smart Tools App

The App turns your smartphone/tablet into the display of the testo 405i. The operation of the measuring instrument as well as the display of the measurement values take place by Bluetooth via the Testo Smart Tools App on your smartphone or tablet – independently of the measurement location. In addition to this, you can use the App to create measurement reports, add photos and comments to these, and send them by e-mail. For iOS and Android.

Sensor type	Hot wire
Measuring range	0 to 20 m/s
Accuracy ±1 digit	±(0.05 m/s + 2.5 % of m.v.) (0 to 2 m/s) ±(0.15 m/s + 2.5 % of m.v.) (2 to 15 m/s)
Resolution	0.01 m/s

Sensor type	NTC
Measuring range	-20 to +60 °C
Accuracy ±1 digit	±0.5 °C
Resolution	0.1 °C

General technical data	
Compatibility	requires iOS 7.1 or newer / Android 4.3 or newer requires mobile end device with Bluetooth 4.0
Storage temperature	-20 to +60 °C
Operating temperature	-20 to +50 °C
Battery type	3 micro batteries AAA
Battery life	15 hrs
Dimensions	200 x 30 x 41 mm Telescope extendable to 400 mm
Warranty	2 years

Accessories	Order no.
testo Smart Case (VAC) for the storage and transport of testo 405i, testo 410i, testo 510i, testo 605i, testo 805i and testo 905i, dimensions 270 x 190 x 60 mm	0516 0260
ISO calibration certificate flow velocity, two-point calibration, calibration points 5; 10 m/s	0520 0094
ISO calibration certificate flow velocity, hot-wire/vane anemometer, Pitot tube; calibration points 1; 2; 5; 10 m/s	0520 0004

1981 1724/msp/1/08.2015

Subject to change, including technical modifications, without notice.

