Safety Data Sheet

N20 - Mag Wheel Cleaner

Page 1

Revision Date: 5/28/2015

Section 1. Product and Company Identification

Product Identifier N20 - Mag Wheel Cleaner

Product Use Description:

Thin dark brown liquid with an acidic odor for use as a wheel cleaning solution

Manufacturer or suppliers' details

P & S Sales, Inc Emergency Number: 800-255-3924 20943 Cabot Blvd. Customer Service: 510-732-2628 Hayward CA 94545 Business Fax: 510-732-2632

Section 2. Hazards Identification

GHS Classification

Skin Corrosion/Irritation: Category 1A

Eye Damage: Category 1

Hazardous to Aquatic Environment : Category 3

Acute toxicity (oral) : Category 3

Acute toxicity (Inhalation) : Category 3
Acute toxicity (dermal) : Category 1

GHS Label Elements

Hazard Pictograms







Hazard Word Danger

Hazard Statements

Causes severe skin burns and eye damage

Harmful to aquatic life Toxic if swallowed Toxic if inhaled

Fatal in contact with skin

Causes severe skin burns and eye damage

IF IN EYES:

Causes serious eye damage

Precautionary Statements

P260: Do not breathe dust/fume/gas/mist/vapous/spray

P262: Do not get in eyes, on skin, or on clothing

P264: Wash skin thoroughly after handling

P280: Wear protective gloves/protective clothing/eye protection/face protection

P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

Page 2

Revision Date: 5/28/2015

	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P310:	
P305+351+338:	breathing Immediately call a POISON CENTER or dector/physician
P310:	Immediately call a POISON CENTER or doctor/physician
. 010.	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if
P363:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P403+233:	present and easy to do - continue mising
1 103 1 2331	Immediately call a POISON CENTER or doctor/physician
P405:	Wash contaminated clothing before reuse
P501:	
. 501.	Store in a well ventilated place. Keep container tightly closed
	Store locked up

Dispose of contents/container to an approved waste disposal plant.

3. Composition Information on Ingredients

CAS Number	Wt %	Component Name
1341-49-7	1-5%	Ammonium Bifluoride
7664-38-2	10-20%	Phosphoric Acid
111-76-2	5-10%	2 Butoxy Ethanol
85536-14-7	3-5%	Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

4. First Aid Measures

First aid procedures should be pre-planned for fluoride compound emergencies.

Inhalation:

In case of accident by inhalation: remove casualty to fresh air and keep at rest.

- Oxygen or artificial respiration if needed.
- Victim to lie down in the recovery position, cover and keep him warm.
- Call a physician immediately
- Keep warm and in a quiet place.

Skin Contact: - Avoid contact with skin, wash quickly and thoroughly even for incidental contact. Damage from ammonium bifluoride is not apparent. If any symptoms occur contact a physician immediately.

- Take off contaminated clothing and shoes immediately. Wash before reuse.
- Wash off with plenty of water.
- Immediately apply calcium gluconate gel 2.5% and massage into the affected area using rubber gloves; continue to massage while repeatedly applying gel until 15 minutes after pain is relieved.
- If fingers/finger nails are touched, even if there is no pain, dip them in a bath of 5% calcium gluconate for 15 to 20 minutes

Eye Contact: - Immediate medical attention is required.

- Take victim immediately to hospital.
- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Rinse the eyes with a calcium gluconate 1% solution in physiological serum (10 ml of calcium gluconate 10% in 90 ml of physiological serum)
- In the case of difficulty of opening the lids, administer an analgesic eye wash (oxybuprocaine).

In case of ingestion - Call a physician immediately.

- Take victim immediately to hospital.
- If victim is conscious:
- If swallowed, rinse mouth with water (only if the person is conscious).
- Give to drink a 1% aqueous calcium gluconate solution.

Safety Data Sheet

Revision Date: 5/28/2015

Page

N20 - Mag Wheel Cleaner

- Do NOT induce vomiting.
- Artificial respiration and/or oxygen may be necessary.
- If victim is unconscious:
- Oxygen or artificial respiration if needed.

Note to Physician: For large exposures, systemic effects (hypocalcemia and hypomagnesia) may occur.

5. Fire Fighting Measures

5.1 Extinguishing media

Suitable extinguishing media - Not applicable no data available no data available

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Unsuitable extinguishing media - None.

5.2 Special hazards arising from the substance or mixture Specific hazards during fire fighting

- The product is not flammable.
- Not combustible.
- Heating can release hazardous gases.
- Gives off hydrogen by reaction with metals.

Hazardous combustion products:

- Hydrogen fluoride
- Ammonia
- Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment for fire-fighters

- Wear self-contained breathing apparatus and protective suit.
- Fire fighters must wear fire resistant personnel protective equipment.
- Wear chemical resistant oversuit

Further information

- Cool containers/tanks with water spray.
- Keep from any possible contact with water.
- Approach from upwind.
- Suppress (knock down) gases/vapors/mists with a water spray jet.
- After the fire, proceed rapidly with cleaning of surfaces exposed to the fumes in order to limit equipment damage.

6. Accidental Release Measures

Advice for non-emergency personnel

- Prevent further leakage or spillage if safe to do so.
- Keep away from incompatible products

Advice for emergency responders

- Immediately evacuate personnel to safe areas.
- Keep people away from and upwind of spill/leak.
- Wear self-contained breathing apparatus and protective suit.
- Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing.
- Suppress (knock down) gases/vapors/mists with a water spray jet.
- Avoid spraying the leak source.
- Ventilate the area.

Environmental precautions

- If the product contaminates rivers and lakes or drains inform respective authorities.
- Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up

Dam up.

- Soak up with inert absorbent material.
- Prevent product from entering sewage system.
- Keep in properly labeled containers.
- Keep in suitable, closed containers for disposal.

N20 - Mag Wheel Cleaner

Page 4

Revision Date: 5/28/2015

- Treat recovered material as described in the section "Disposal considerations".

7. Handling and Storage

Keep in a tightly closed container. Store in a cool, dry, ventilated area. Protect against physical damage. Separate from acids and alkalis. Do not store in metal containers, as contact with metal may release flammable hydrogen gas. Containers of this material may be hazardous when empty since they retain product residues (including dust and solids); observe all warnings and precautions listed for the product.

- Use only in an area equipped with a safety shower.
- Take off contaminated clothing and shoes immediately.
- Wash contaminated clothing before re-use.
- May not get in touch with:
- Leather
- Handle in accordance with good industrial hygiene and safety practice.

8. Exposure Controls and Personal Protection

1341-49-7 Ammonium Bifluoride	2.5 mg/m3 OSHA PEL TWA
	2.5 mg/m3 OSHA Table Z-1
	2.5 mg/m3 ACGIH TLV
	.5 ppm ACGIH TWA
7664-38-2 Phosphoric Acid	1 mg/m3 ACGIH TWA OSHA PFI
•	3 MĞ/M3 ACGIH STEL
111-76-2 2 Butoxy Ethanol	20 ppm ACGIH TWA
-	5 ppm. 24 mg/m3 NIOSH REL
	50 ppm OSHA Z-1 TWA
	240 mg/m3
85536-14-7 Benzenesulfonic acid, 4-C10-13-sec-alk	
derivatives	

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area.

If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest..

A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

Page 5

Revision Date: 5/28/2015

9. Physical and Chemical Properties

Flash Point none Upper Flamability Limit none
Auto Ignition none Lower Flamability Limit none

Physical State Liquid Color Brown Vapor Press unknown

pH < 1 Specific Gravity 1.144 Viscosity thin

Vapor Density (Air=1) 1 Melting Point °F unknown Odor Acid/Glycol

Water Solubility complete

10. Stability and Reactivity

Stability Stable Hazardous Polymerization Not Expected to Occur

Conditions to Avoid Reacts with acids to liberate hydrogen fluoride and base to liberate ammonia. Will corrode

VOC Content

glass, cement and most metals.

Hazardous Decomposition Products

Emits toxic fumes of hydrogen fluoride, nitric oxides, and ammonia when heated to decomposition. Upon contact with metal, this material may release hydrogen gas.

< 2%

11. Toxicological Information

Toxicological Data: for Ammonium Bibluoride

Acute toxicity LD50: 60 - 130 mg/kg - Rat

Acute oral toxicity no data available

Acute inhalation toxicity no data available

Acute dermal toxicity - sodium fluoride LD 10 : ca. 300 mg/kg - Mouse

Acute toxicity (other routes of administration) no data available

12. Ecological Information

Environmental Fate:

The methods for determining the biological degradability are not applicable to inorganic substances.

Environmental Toxicity:

LC50 - 96 h : 51 mg/l - Fishes, Salmo gairdneri Test substance: fluorides

EC50 - 96 h : 10.5 mg/l - Crustaceans, Mysidopsis Test substance: fluorides salt water EC50 - 48 h : 97 mg/l - Daphnia magna (Water flea) Test substance: fluorides Fresh water

EC50 - 96 h: 43 mg/l - Algae, Scenedesmus sp. Test substance: fluorides

LC50: 2.7 - 4.7 mg/l - 21 Days - Fishes, Salmo gairdneri Test substance: fluorides

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Although not a listed RCRA hazardous waste, this material may exhibit one or more characteristics of a hazardous waste and require appropriate analysis to determine specific disposal requirements. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

N20 - Mag Wheel Cleaner

Page 6

Revision Date: 5/28/2015

- Environmental Protection Agency
- Hazardous Waste YES
- RCRA Hazardous Waste (40 CFR 302)

14. Transportation Information

Domestic (Land, D.O.T.)

·

Proper Shipping Name: UN2922, Corrosive Liquid, Toxic, Phosphoric Acid, Hydrofluoric Acid), 8, (6.1), PG II Information reported for product/size: 32 oz up to 55 gallon drum.

International (Water, I.M.O.)

Proper Shipping Name: UN2922, Corrosive Liquid, Toxic, Phosphoric Acid, Hydrofluoric Acid), 8, (6.1), PG II Information reported for product/size: 32 oz up to 55 gallon drum.

15. Regulatory Information

OSHA Hazards: Acute Health Hazard, Chronic Health Hazard, Serious Eye Hazard, Serious Skin Hazard

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity - Hydrogen Fluoride, 7664-39-3, 3000 lb

SARA 304 Extremely Hazardous Substances Reportable Quantity

Hydrogen Fluoride, 7664-39-3, 3000 lb

SARA 311/312 Hazards: Acute Health Hazard, Chronic Health Hazard

SARA 302: Hydrogen Fluoride, 7664-39-3, 3000 lb

SARA 313: SARA 313: Hydrogen Fluoride, 7664-39-3, .3%

California Prop. 65: This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Clean Air Act (CAA) -

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489)

Clean Water Act -

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. Clean- Water Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307