# NTS-300-248UN

## Pure Sine Wave Inverters



#### Scene

The inverter works with a variety of products and is suitable for use in environments with temperatures ranging from  $-25^{\circ}\text{C}$  to  $+65^{\circ}\text{C}$  ( $-13^{\circ}\text{F}$  to  $+149^{\circ}\text{F}$ ) and with humidity less than 90%.

#### **Technical Specification**

### **Electrical Specification**

| AC Output Rated Power         | 300 W                                                    |
|-------------------------------|----------------------------------------------------------|
| AC Output Waveform            | Pure sine wave                                           |
| AC Output Frequency           | 50/60 Hz, can be adjusted by configuring button          |
| AC Output Alternating Voltage | 200/220/230/240 V, can be adjusted by configuring button |
| DC Input Direct Voltage       | 48 V                                                     |
| DC Input Direct Current       | 8 A                                                      |
| DC Input Frequency            | 93%                                                      |
| DC Input Battery Type         | Lead-acid Battery, Lithium Battery                       |
| EMC                           | CLASS A                                                  |

# Safety Performance

| Salety Performance                     |            |
|----------------------------------------|------------|
| Battery Low Voltage Alarm              | 44 ± 1 VDC |
| Battery Low Voltage Shutdown           | 40 ± 1 VDC |
| Battery High Voltage Alarm             | 62 ± 1 VDC |
| Battery High Voltage Shutdown          | 66 ± 1 VDC |
| Battery Reverse Polarity<br>Protection | Yes        |
| Overtemperature Protection             | Yes        |
| Output Short Circuit Protection        | Yes        |
| Output Overvoltage Protection          | Yes        |
|                                        |            |

- Uses true sine wave output with THD <3%.
- Supports 40–66 VDC wide voltage input and is suitable for 48 V storage battery input in solar systems.
- Up to 93% full-load efficiency.
- Supports various protections, including low voltage alert and low voltage shutdown of storage battery, output short circuit protection, overload protection, overvoltage protection, over temperature protection and polarity protection.
- · Adjustable output voltage.
- Adjustable output frequency to 50 Hz and 60 Hz.

#### Others

| Product Dimensions    | 210 mm $\times$ 130 mm $\times$ 55 mm (8.27" $\times$ 5.12" $\times$ 2.17") (L $\times$ W $\times$ H)   |
|-----------------------|---------------------------------------------------------------------------------------------------------|
| Net Weight            | 1.3 kg (2.87 lb)                                                                                        |
| Packaging Dimensions  | 280 mm $\times$ 176 mm $\times$ 110 mm (11.02" $\times$ 6.93" $\times$ 4.33") (L $\times$ W $\times$ H) |
| Operating Temperature | -25°C to +65°C (-13 °F to +149 °F)                                                                      |
| Operating Humidity    | 20%–90% (RH) (non-condensing)                                                                           |
| Storage Temperature   | −30 °C to +70 °C (−22 °F to +158 °F)                                                                    |
| Storage Humidity      | 10%–95% (RH) (non-condensing)                                                                           |
| Accessory             | 1 × user's manual                                                                                       |
| Certifications        | CE                                                                                                      |

#### Dimensions (mm[inch])

