
## **AQUAvalve**

Simple care guidelines

## Your 80Pot XL system set-up guidelines







on the hole below it. Hold at eye level to check the position is correct

## **Ensuring that the AQUAvalve5 floods** and drains correctly



Making sure your AQUAvalve5 floods and drains correctly is simply achieved and only takes a few seconds.



Hold the AQUAvalve5 at eye level so that you can see the silicone fitted to the top float resting on the hole below it.



The silicone must create a tight seal when touching the hole.

If it looks like it is not sitting parallel on the 4 hole below, simply lift the top float and apply pressure to one side of the silicone, drop the float and hold at eye level again. Repeat the procedure if necessary.

## Care and maintenance

At the end of your growing season, clean 1 the AQUAvalve5 using warm soapy water. Using an old tooth brush will help.


> The AQUAvalve5 is easily disassembled. The top float will slide all the way across and the bottom float is unclipped from its pivoting position. The circular discs fitted to the top float can also be removed by using pliers to grip the raised point.


At this point is it advisable to remove the silicones to avoid them being lost.

It is also handy to have a paper clip or pipe 2 cleaner to hand so that you can push it through the AQUAvalve5 nozzle, this will remove any lime scale build up that may have occurred during the growing season.

> Blowing through the AQUAvalve5 nozzle will also help to remove any build up. Do not under any circumstances use a drill & drill bit to clear the AQUAvalve5 nozzle

This will potentially damage the AQUAvalve5 beyond repair.





Advice