











	Dimmable E12 Candle	CREE COB	4.5W	ww:270lm cw:300lm	\$6.1	Dimmable	cULus	60	1: Qty/ctn: 120pcs/ctn 2: Gross Weight: 10.5KG 3: Size of carton: 51×32×30cm
	Size: D35.3xL105mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 200°								
CA04E12XXKCR	Working Tem:-20--+40°C								
	Dimmable E14 Candle	CREE COB	4.5W	ww:270lm cw:300lm	\$6.1	Dimmable	cULus	360	1: Qty/ctn: 120pcs/ctn 2: Gross Weight: 10.5KG 3: Size of carton: 51×32×30cm
	Size: D35.3xL107.6mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 200°								
CA04E14XXKCR	Working Tem:-20--+40°C								

	Dimmable PAR20	CREE COB	8w	CRI 80 540lm	\$9.70	Dimmable	UL Energy Star 3000K 40deg)	100	1: Qty: 100pcs/ctn 2: Gross Weight: 21KG 3: Size of carton: 38×38×49cm
	Size: D63.5xL90mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P208E26XXKCY Y	Working Tem:-20--+40°C								
	Dimmable PAR30	CREE COB	13w	CRI 80 800lm	\$14.00	Dimmable	UL Energy Star (2700K 3000K 40deg)	100	1: Qty: 25pcs/ctn 2: Gross Weight: 11KG 3: Size of carton: 52×52×18cm
	Size: D95xL115mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P313E26XXKCY Y	Working Tem:-20--+40°C								
	Dimmable PAR38	CREE COB	17w	CRI 80 1200lm	\$18.50	Dimmable	UL Energy Star (2700K 3000K 40deg)	100	1: Qty: 16pcs/ctn 2: Gross Weight: 12KG 3: Size of carton: 56×56×19cm
	Size: D118xL132mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P417E26XXKCY Y	Working Tem:-20--+40°C								
	Dimmable PAR30	CREE COB	13w	CRI 80 800lm	\$14.00	Dimmable	cULus	100	1: Qty: 25pcs/ctn 2: Gross Weight: 11KG 3: Size of carton: 52×52×18cm
	Size: D95xL115mm								
	Voltage: AC277V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P313E26XXKCY YH	Working Tem:-20--+40°C								
	Dimmable PAR38	CREE COB	17w	CRI 80 1200lm	\$18.50	Dimmable	cULus	100	1: Qty: 16pcs/ctn 2: Gross Weight: 12KG 3: Size of carton: 56×56×19cm
	Size: D118xL132mm								
	Voltage: AC277V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P417E26XXKCY YH	Working Tem:-20--+40°C								
	Dimmable BR20	12pcs Lumileds	7W	CRI80 530lm	\$7.50	Dimmable	cULus	100	1: Qty: 100pcs/ctn 2: Gross Weight: 20KG 3: Size of carton: 38×38×49cm
	Size: D63.5xL96.5mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 120°								
BR07E26XXX	Working Tem:-20--+40°C								

	Dimmable BR30	CREE COB	13W	CRI80 850lm	\$9.00	Dimmable	cULus Star Energy (CRI80 3000K)	100	1: Qty: 25pcs/ctn 2: Gross Weight: 12.5KG 3: Size of carton: 55x55x20cm
	Size: D95.5xL133.5mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 120°								
BR13E26XXKA	Working Tem:-20--+40°C								
	Dimmable BR40	SHARP COB	15w	CRI80 1000lm	\$16.50	Dimmable	cULus	100	1: Qty: 24pcs/ctn 2: Gross Weight: 22KG 3: Size of carton: 64x52x33cm
	Size: D127xL162mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 120°								
BR15E26XXKSP	Working Tem:-20--+40°C								
	Dimmable BR30	CREE COB	13W	CRI80 850lm	\$11.00	Dimmable	cULus	100	1: Qty: 25pcs/ctn 2: Gross Weight: 12.5KG 3: Size of carton: 55x55x20cm
	Size: D95.5xL133.5mm								
	Voltage: AC277V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 120°								
BR13E26XXKCYH	Working Tem:-20--+40°C								
	Dimmable BR40	CREE COB	17w	CRI80 1000lm	\$16.50	Dimmable	cULus	100	1: Qty: 24pcs/ctn 2: Gross Weight: 22KG 3: Size of carton: 64x52x33cm
	Size: D127xL162mm								
	Voltage: AC277V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 120°								
BR17E26XXKCYH	Working Tem:-20--+40°C								




Remarks:

- EX-WORKS cost
- This quote is based on Neutral Package.
- Warranty is 3-5 years and vary on different products, please ask for warranty policy from sales.
- The "XX" denotes Color temperature which can be " 27, 30, 40, 50K",
"YY" denotes beam angle which can be "SP" for 15°, "NFL" for 25°, "FL" for 40°, "WFL" for 100°
- "H" denotes High voltage which is " 277VAC"
- CRI90 is 10% less lumens than CRI80 type

Picture	Specification	LED Brand	Power	Lumens	Unit price	Dimmable Function	Certificate	MOQ (pcs)	Packing
					<2000pcs				
	Dimmable MR16	Lumildes LUXEON 3030 (CRI80 & 90)	7W	CRI80: 520lm CRI90: 460lm	US\$5.7	Dimmable	cULus	100	1: Qty/ctn: 200pcs/ctn 2: Gross Weight: 16kg 3: Size of carton: 55.5x55.5x17.5cm
	Size: D50xL45.5mm								
	Voltage: AC/DC 12V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 25/40								
MR07XXKCYYBZZ	Working Tem:-20--+40°C								
	Dimmable GU10	Lumildes LUXEON 3030 (CRI80 & 90)	7W	CRI80: 550lm CRI90: 520lm	US\$5.7	Dimmable	cULus Energy Star (CRI90 2700K/3000K @40de)	100	1: Qty/ctn: 200pcs/ctn 2: Gross Weight: 17.5kg 3: Size of carton: 55.5x55.5x17.5cm
	Size: D50xL54mm								
	Voltage: AC 120V / 230V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 25/40								
GU07XXKCYYBZZ	Working Tem:-20--+40°C								
	Dimmable PAR16	Lumildes LUXEON 3030 (CRI80 & 90)	7W	CRI80: 550lm CRI90: 520lm	US\$5.7	Dimmable	cULus Energy Star (CRI90 2700K/3000K @40de)	100	1: Qty/ctn: 200pcs/ctn 2: Gross Weight: 19.5kg 3: Size of carton: 55.5x55.5x17.5cm
	Size: D50xL63mm								
	Voltage: AC 120V / 230V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 25/40								
P107XXKCYYBZZ	Working Tem:-20--+40°C								

Remarks:






- EX-WORKS cost
- This quote is based on Neutral Package.
- Warranty is 3-5 years and vary on different products, please ask for warranty policy from sales.
- The "XX" denotes Color temperature which can be " 27, 30, 40, 50, 60K"
"YY" denotes beam angle which can be "SP" for 15°, "NFL" for 25°, "FL" for 40° and "WFL" for 100°
- CRI90 is 10% less lumens than CRI80 type

Picture	Specification	LED Brand	Power	Lumens	Unit price	Dimmable	Certificate	MOQ (pcs)	Packing
					<2000pcs				
	Dimmable MR16	Luminus COB (CRI80 & 90)	7W	ww: 510lm cw: 550lm	US\$6.5	Dimmable	cULus Energy Star (CRI80 2700/3000/ 4000K @38deg)	100	1: Qty/ctn: 200pcs/ctn 2: Gross Weight: 16kg 3: Size of carton: 55.5x55.5x17.5cm
	Size: D50xL52mm								
	Voltage: AC/DC 12V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
MR07XXKYYAZZ	Working Tem:-20--+40°C								
	Dimmable GU10	Luminus COB (CRI80 & 90)	7W	ww: 510lm cw: 550lm	US\$6.5	Dimmable	cULus Energy Star (CRI80 2700/3000/ 4000K @38deg)	100	1: Qty/ctn: 200pcs/ctn 2: Gross Weight: 17.5kg 3: Size of carton: 55.5x55.5x17.5cm
	Size: D50xL60.8mm								
	Voltage: AC 120V / 230V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
GU07XXKYYAZZ	Working Tem:-20--+40°C								
	Dimmable PAR16	Luminus COB (CRI80 & 90)	7W	ww: 510lm cw: 550lm	US\$6.5	Dimmable	cULus Energy Star (CRI80 2700/3000/ 4000K @38deg)	100	1: Qty/ctn: 200pcs/ctn 2: Gross Weight: 19.5kg 3: Size of carton: 55.5x55.5x17.5cm
	Size: D50xL70mm								
	Voltage: AC 120V / 230V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P107XXKYYAZZ	Working Tem:-20--+40°C								

Remarks:






- EX-WORKS cost
- This quote is based on Neutral Package.
- Warranty is 3-5 years and vary on different products, please ask for warranty policy from sales.
- The "XX" denotes Color temperature which can be " 27, 30, 40, 50K",
"YY" denotes beam angle which can be "SP" for 15°, "NFL" for 25°, "FL" for 40°, "WFL" for 100°
1st " Z" denotes housing finish which can be " W" for white or "B" for Black... ; 2nd "Z" denotes CRI which can be " H" for CRI80 or "U" for CRI90
- CRI90 is 10% less lumens than CRI80 type

Picture	Specification	LED Brand	Power	Lumens	Unit price	Dimmable	Certificate	MOQ (pcs)	Packing
					<20000pcs				
	Dimmable PAR20	CREE COB	8w	CRI 80 535lm (2700K)	US\$8.20	Dimmable	cULus Energy Star (2700K,3000K,4000K,5000K)	100	1: Qty: 100pcs/ctn 2: Gross Weight: 17.5KG 3: Size of carton: 38x38x49cm
	Size: D63.5xL90mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P208E26XXKCYAWH	Working Tem:-20--+40℃								
	Dimmable PAR30	CREE COB	13w	CRI 80 815lm (2700K)	US\$9.50	Dimmable	cULus Energy Star (2700K,3000K,4000K,5000K)	100	1: Qty: 25pcs/ctn 2: Gross Weight: 11KG 3: Size of carton: 52x52x18cm
	Size: D95xL115mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P313E26XXKCYAWH	Working Tem:-20--+40℃								
Picture	Specification	LED Brand	Power	Lumens	Unit price	Dimmable	Certificate	MOQ (pcs)	Packing
					<10000pcs				
	Dimmable PAR38	CREE COB	15W	CRI 80 950lm (2700K)	US\$12.50	Dimmable	cULus Energy Star Pending	100	1: Qty: 16pcs/ctn 2: Gross Weight:8KG 3: Size of carton: 56x56x19cm
	Size: D118xL132mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P415E26XXKCYAWH	Working Tem:-20--+40℃								
	Dimmable PAR38	CREE COB	17W	CRI 80 1200lm (2700K)	US\$12.80	Dimmable	cULus Energy Star (2700K,3000K,4000K,5000K)	100	1: Qty: 16pcs/ctn 2: Gross Weight: 8KG 3: Size of carton: 56x56x19cm
	Size: D118xL132mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P417E26XXKCYAWH	Working Tem:-20--+40℃								
Picture	Specification	LED Brand	Power	Lumens	Unit price	Dimming	Certificate	MOQ (pcs)	Packing
					<5000pcs	Function			
	Dimmable PAR20	Luminus COB	8w	CRI 90 545lm (2700K)	US\$7.70	Dimmable	cULus Energy Star 2700K	100	1: Qty: 100pcs/ctn 2: Gross Weight: 21KG 3: Size of carton: 38x38x49cm
	Size: D63.5xL90mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P208E26XXKCYAWU	Working Tem:-20--+40℃								
	Dimmable PAR30	CREE COB	13w	CRI 90 830lm (2700K)	US\$10.50	Dimmable	cULus Energy Star (2700K CRI93)	100	1: Qty: 25pcs/ctn 2: Gross Weight: 11KG 3: Size of carton: 52x52x18cm
	Size: D95xL115mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P313E26XXKCYAWU	Working Tem:-20--+40℃								
	Dimmable PAR38	CREE COB	17W	CRI 90 950lm (2700k)	US\$14.10	Dimmable	cULus Energy Star (2700K ,3000K)	100	1: Qty: 16pcs/ctn 2: Gross Weight: 12KG 3: Size of carton: 56x56x19cm
	Size: D118xL132mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P417E26XXKCYAWU	Working Tem:-20--+40℃								

	Dimmable GU24 PAR20	CREE COB	8w	CRI 80 535lm (2700K)	US\$7.70	Dimmable	cULus	100	1: Qty: 100pcs/ctn 2: Gross Weight: 21KG 3: Size of carton: 38x38x49cm
	Size: D63.5xL90mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P208GUXKCYAWH	Working Tem:-20--+40°C								
	Dimmable Short Neck Par30	CREE COB	13w	CRI 80 815lm (2700K)	US\$10.20	Dimmable	cULus	100	1: Qty: 25pcs/ctn 2: Gross Weight: 11KG 3: Size of carton: 52x52x18cm
	Size: D95xL87mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P313E26XXKCYAWHS	Working Tem:-20--+40°C								
	Dimmable GU24 Par30	CREE COB	13w	CRI 80 815lm (2700K)	US\$10.20	Dimmable	cULus	100	1: Qty: 16pcs/ctn 2: Gross Weight: 12KG 3: Size of carton: 56x56x19cm
	Size: D95xL92mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P313GUXKCYAWH	Working Tem:-20--+40°C								
	Dimmable GU24 PAR38	CREE COB	17W	CRI 80 1200lm (2700K)	US\$14.70	Dimmable	cULus	100	1: Qty: 16pcs/ctn 2: Gross Weight: 12KG 3: Size of carton: 56x56x19cm
	Size: D118xL mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50K								
	Beam Angle: 25/40								
P417GUXKCYAWH	Working Tem:-20--+40°C								
	LED Waterproof PAR38	CREE COB	17W	1300lm (3000K)	\$14.5	cULus	YES	100	1: Qty: 16 pcs/ctn 2: Gross Weight: KG 3: Size of carton:
	Size: D120xL128.8mm								
	Voltage: AC 120V								
	PF>0.90 CRI>75								
	CCT: 27/30/40/50K								
	Working Tem:-20--+40°C								
P417E26XXKCYEZZ	WET Location								

Remarks:

1. EX-WORKS cost
2. This quote is based on Neutral Package.
3. Warranty is 3-5 years and vary on different products, please ask for warranty policy from sales.
4. The "XX" denotes Color temperature which can be " 27, 30, 40, 50K",
"YY" denotes beam angle which can be "SP" for 15°, "NFL" for 25°, "FL" for 40°, "WFL" for 100°
5. "H" denotes High voltage which is " 277VAC"
6. CRI90 is 10% less lumens than CRI80 type

Picture	Specification	LED Brand	Power	Lumens	Unit price	Dimmable	Certificate	MOQ (pcs)	Packing
					<5000pcs				
	Dimmable BR20	Lumileds luxeon 3030	8W (Eqv. To 50W)	550lm	US\$6.5	Dimmable	cULus Energy Star PENDING (2700/3000/ 4000K)	100	1: Qty: 25pcs/ctn 2: Gross Weight: 17.5KG 3: Size of carton: 36x36x46.5cm
	Size: D63xL96mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 120°								
BR08E26XXKAZZ	Working Tem:-20--+40℃								
	Dimmable BR30	Lumileds luxeon 3030	9W (Eqv. To 65W)	680lm	US\$6.9	Dimmable	cULus Energy Star (2700/3000/ 4000K)	100	1: Qty: 25pcs/ctn 2: Gross Weight: 9KG 3: Size of carton: 51x51x17cm
	Size: D95xL133mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 120°								
BR09E26XXKAZZ	Working Tem:-20--+40℃								
	Dimmable BR30	Lumileds luxeon 3030	14W (Eqv. To 85W)	1050lm	US\$9.5	Dimmable	cULus Energy Star (2700/3000/ 4000K)	100	1: Qty: 25pcs/ctn 2: Gross Weight: 9KG 3: Size of carton: 51x51x17cm
	Size: D95xL133mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 120°								
BR13E26XXKAZZ	Working Tem:-20--+40℃								
	Dimmable BR40	Lumileds luxeon 3030	15W (Eqv. To 85W)	1070lm	US\$12.0	Dimmable	cULus Energy Star PENDING (2700/3000/ 4000K)	100	1: Qty:16 pcs/ctn 2: Gross Weight: 9KG 3: Size of carton: 52x52x19.5cm
	Size: D120xL156mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 120°								
BR15E26XXKAZZ	Working Tem:-20--+40℃								
	Dimmable BR40	Lumileds luxeon 3030	17W	1200lm	US\$13.0	Dimmable	cULus	100	1: Qty:16 pcs/ctn 2: Gross Weight: 9KG 3: Size of carton: 52x52x19.5cm
	Size: D120xL156mm								
	Voltage: AC 120V								
	PF>0.90 CRI>80								
	CCT: 27/30/40/50/60K								
	Beam Angle: 120°								
BR17E26XXKAZZ	Working Tem:-20--+40℃								

Remarks:

1. EX-WORKS cost
2. This quote is based on Neutral Package.
3. Warranty is 3-5 years and vary on different products, please ask for warranty policy from sales.
4. The "XX" denotes Color temperature which can be " 27, 30, 40, 50 and 60K"

"YY" denotes beam angle which can be "SP" for 15°, "NFL" for 25°, "FL" for 40°, "WFL" for 100°

1st "Z" denotes housing finish which can be "W" for white or "B" for Black...; 2nd "Z" denotes CRI which can be "H" for CRI80 or "U" for CRI90

5. CRI90 is 10% less lumens than CRI80 type

Picture	Specification	LED Brand	Power	Lumens	Unit price	Certificates	Dimmable Function	MOQ (pcs)	Packing
					<2000pcs				
	LED G24Q/G24D BR20	Lumileds 3030	8W	580lm (3000K)	\$8.7	cULus	N/A	100	1: Qty: 100 pcs/ctn 2: Gross Weight: KG 3: Size of carton:
	Size: D63xL100mm								
	Voltage: AC 120-277V								
	PF>0.80 CRI>80								
	CCT: 27/30/40/50/60K								
	Working Tem:-20--+40°C								
BR08G24XXKAZZ	Beam Angle: 120°								
	LED G24Q/G24D BR30	Lumileds 3030	9W	700LM (3000K)	\$9.3	cULus	N/A	100	1: Qty: 100 pcs/ctn 2: Gross Weight: KG 3: Size of carton:
	Size: D95xL132mm								
	Voltage: AC 120-277V								
	PF>0.80 CRI>80								
	CCT: 27/30/40/50/60K								
	Working Tem:-20--+40°C								
BR09G24XXKAZZ	Beam Angle: 120°								
	LED G24Q/G24D BR30	Lumileds 3030	13W	1070LM (3000K)	\$11.4	cULus	N/A	100	1: Qty: 25 pcs/ctn 2: Gross Weight: KG 3: Size of carton:
	Size: D95xL132mm								
	Voltage: AC 120-277V								
	PF>0.80 CRI>80								
	CCT: 27/30/40/50/60K								
	Working Tem:-20--+40°C								
BR13G24XXKAZZ	Beam Angle: 120°								
	LED G24Q/G24D BR30	Lumileds 3030	13W	1070LM (3000K)	\$11.4	cULus	N/A	100	1: Qty: 25 pcs/ctn 2: Gross Weight: KG 3: Size of carton:
	Size: D95xL147mm								
	Voltage: AC 120-277V								
	PF>0.80 CRI>80								
	CCT: 27/30/40/50/60K								
	Working Tem:-20--+40°C								
BR13G24XXKBZZ	Beam Angle: 120°								
	LED G24Q/G24D BR40	Lumileds 3030	15w	1080LM (3000K)	\$13.0	cULus	N/A	100	1: Qty: 16 pcs/ctn 2: Gross Weight: KG 3: Size of carton:
	Size: D120xL152mm								
	Voltage: AC 120-277V								
	PF>0.80 CRI>80								
	CCT: 27/30/40/50/60K								
	Working Tem:-20--+40°C								
BR15G24XXKAZZ	Beam Angle: 120°								
	LED G24Q/G24D BR40	Lumileds 3030	17w	1400LM (3000K)	\$15.0		N/A	100	1: Qty: 16 pcs/ctn 2: Gross Weight: KG 3: Size of carton:
	Size: D120xL152mm								
	Voltage: AC 120-277V								
	PF>0.80 CRI>80								
	CCT: 27/30/40/50/60K								
	Working Tem:-20--+40°C								
BR17G24XXKAZZ	Beam Angle: 120°								

	Dimmable E26 PL	Epistar	12W (Omni-directional)	CRI 80 950lm	US\$11.50	cULus	Dimmable	100	1: Qty/ctn: pcs/ctn 2: Gross Weight: KG 3: Size of carton:
	Size: D52xL190mm								
	PF>0.80 CRI>80								
	Voltage: AC 120V								
	CCT: 27/30/40/50/60K								
Working Tem:-20--+40°C									
PL12E26XXK	Beam Angle: 280°								
	LED G24Q PL	Epistar	9W (Omni-directional)	CRI 80 710lm (2700K)	US\$10.70	cULus	N/A	100	1: Qty/ctn: 100pcs/ctn 2: Gross Weight: 13KG 3: Size of carton: 46x46x23cm
	Size: D35.5xL173mm								
	PF>0.80 CRI>80								
	Voltage: AC 120-277V								
	CCT: 27/30/40/50/60K								
Working Tem:-20--+40°C									
PL09G24XXK	Beam Angle: 280°								
	LED G24D PL	Epistar	9W (Omni-directional)	CRI 80 710lm (2700K)	US\$10.70	cULus	N/A	100	1: Qty/ctn: 100pcs/ctn 2: Gross Weight: 13KG 3: Size of carton: 46x46x23cm
	Size: D35.5xL173mm								
	PF>0.80 CRI>80								
	Voltage: AC 120-277V								
	CCT: 27/30/40/50/60K								
Working Tem:-20--+40°C									
PL09G24XXKD	Beam Angle: 280°								
	LED G24Q/G24D PL	Epistar	11W (Omni-directional)	CRI 80 950lm (4000K)	US\$11.00	cULus	N/A	100	1: Qty/ctn: 100pcs/ctn 2: Gross Weight: 13KG 3: Size of carton: 46x46x23cm
	Size: D37.5xL180.4mm								
	PF>0.80 CRI>80								
	Voltage: AC 120-277V								
	CCT: 27/30/40/50/60K								
Working Tem:-20--+40°C									
PL11G24XXKAZZ	Beam Angle: 280°								
	LED G24Q3/G24D3 PL	Lumileds 3030	9W	CRI 80 950lm (4000K)	US\$9.30	cULus	N/A	100	1: Qty/ctn: 2: Gross Weight: 3: Size of carton:
	Size: D35.5xL158.5mm								
	PF>0.80 CRI>80								
	Voltage: AC 120-277V								
	CCT: 27/30/40/50/60K								
Working Tem:-20--+40°C									
PL09G24XXKBZZ	Beam Angle: 120°								
	LED G24Q3/G24D3 PL	Lumileds 3030	12W	CRI 80 1150lm (4000K)	US\$9.70	cULus	N/A	100	1: Qty/ctn: 2: Gross Weight: 3: Size of carton:
	Size: D35.5xL178.3mm								
	PF>0.80 CRI>80								
	Voltage: AC 120-277V								
	CCT: 27/30/40/50/60K								
Working Tem:-20--+40°C									
PL12G24XXKBZZ	Beam Angle: 120°								

Remarks:

1. EX-WORKS cost
2. This quote is based on Neutral Package.
3. Warranty is 3-5 years and vary on different products, please ask for warranty policy from sales.
4. The "XX" denotes Color temperature which can be " 27, 30, 40, 50, 60K"

1st " Z" denotes Lamp base type which can be " (G24)Q" or "(G24)D" ; 2nd "Z" denotes CRI which can be " H" for CRI80 or "U" for CRI90