



This wallpaper is hand screen printed in the USA, using vinly inks on clay-coated paper. This is a handmade product and should be handled with care.

PRODUCT DETAILS:

- Horizontal repeat: 27-28”
- Vertical repeat varies by design
- All measurements on the website
- Double roll is 10 yards (30 feet)

CONTACT US:

- We'd love to answer any of your questions!
- info@relativitytextiles.com
- www.relativitytextiles.com

PLEASE KEEP THIS INFORMATION SHEET!

This product is designed to be installed by a competent, professional paperhanger.

Our website lists proper hanging instructions as well as the products we recommend such as primer and paste.

PREPARE YOUR WALLS CAREFULLY

This paper may allow some show through – all surfaces must be smooth and sound, free of dust and peeling of inferior paint. Use of a pulp or acid-free liner is necessary. Writing on the wall to aid in installation should be done with light pencil. Never use ball point pen or marker as they will show through.

OLD WALLS: Remove existing wallcoverings, sand. Wash and clean thoroughly to disinfect, eliminate mold and bacteria. Patch and sand as necessary to achieve a smooth surface. Prime with a universal wallcovering primer (T9000, Sheildz, 1-23). *Do not use oil-based primers.*

NEW WALLS: Smooth, eliminate dust, and ensure room temperature (55 degrees F or warmer) for at least 12 hours prior to installation. Properly prime walls: Latex paints must be cured with a product such as Gardz. New plaster must be properly cured (60-90 days) and feel cool to the touch.

(Please refer to the back for hanging instructions)

HANGING INSTRUCTIONS (BUTT SEAMS)

1. After you have prepared the walls as per instructions on the front, roll adhesive on the back of the panel by hand or use a pasting machine. Do not paste the wall. We recommend a clear premixed adhesive. *Do not use clay-based adhesive!* Wheat and cellulose adhesives are also not recommended. A light weight clear paste is best and can be found on our website.
2. Carefully “book” the paper; lay ends of panel in onto itself without creasing. Adhesive side of panel should be completely stuck to itself. Allow a 2-3 minutes max for booking.
3. Measure the wall and panel width to determine the edge of the first panel. Use a level to draw plum line. Unfold roll and place the top of the panel on the wall. Start from the top but match at eye level.
4. Using broad smooth strokes work excess paste and trapped air from center out left and right, up and down until panel is smooth. Avoid burnishing the face of the material. Use a wallcovering brush to gently smooth the wallcovering onto the wall. If using a plastic scraper, be careful not to apply too much pressure.
5. Repeat process with consecutive panels. Butt the edges tightly at the pattern match without overlapping. Cut ceiling and floor cuts before moving to next panel.
6. Do not rub. Do not allow the adhesive to dry on surface as it may leave a white residue. Wash off excess paste from face of wallcovering as you hang it with a cellulose sponge. The cellulose sponge must be rinsed in clean water after every use. Even a rough cloth or towel can cause ink to fleck so a paper towel or soft sponge is best. No scrubbing, abrasive or solvent cleaners. Use seam roller to make sure all seams are bonded well.
7. After three panels are smoothed to wall surface and excess paste removed, examine the installed panels for color uniformity. *Any objectionable variations in colormatch, pattern match, should be immediately communicated to the printer for inspection before proceeding further with installation.*
8. After installation is complete, minor blisters like small bubbles may be present. Please allow 7 days for adhesive to fully cure. As wallpaper cures it will tighten like a drum and pull taught any minor blisters. Do not try to press them down with your finger. The walls and wallcovering

RETURN POLICY

Inspect your product before hanging for any obvious flaws and then again after hanging 3 panels.

Returns must be made within 14 days of receiving the product and the reason for return should be communicated to your sales rep. or a Relativity staff member by phone or email right away.

Please retain the original packaging/box for return shipping. Wallpaper that is returned without its original packaging, including the shrink wrap and label, may not be accepted.

Please refer to our website for any more information on our Return Policy.