

Model S0480-BF

Barrier Free, Wall Mounted Eye/Face Wash,
Stainless Steel Shrouded Bowl



SPECIFICATIONS:

Model S0480-BF is a barrier free wall mounted eye/face wash, with a stainless steel bowl and shrouded wrap around skirt, ABS plastic eye/face wash spray heads, an inline strainer and a stay-open 1/2" ball valve with a push handle.

Barrier Free fixture design conforms with ADA Standards for Knee and Toe Clearance, and Height and Reach Range. (2010 Standard Section: 306, 308).

STANDARD EQUIPMENT:

Spray Head Assembly: ABS yellow plastic Eye/Face Wash heads with integral flip dust covers, internal flow controls and filters to remove debris from the water. An anti-microbial agent is molded into the ABS material, providing integrated protection.

Valve: 1/2" NPT chrome plated brass stay-open ball valve with a stainless steel push handle and a 50 mesh inline strainer.

Water Supply: 1/2" NPT female threaded, chrome plated brass inlet.

Waste: Chrome plated brass, 1-1/4" OD tailpiece.

Bowl: 18 gage stainless steel, 11-3/4" diameter bowl with a shrouded wrap around skirt.

Flow / Pressure Rates: Eye-Face Wash exceeds minimum water flow of 3.0 GPM (11.4L) at 30 PSI (2.0 bar).

Universal Sign: ANSI compliant, vertical identification sign.

Weekly Test Tag: A waterproof test card to record the date and inspector's name for weekly functional testing of the unit.

□ **Model:** S0480-BF



OPTIONAL ACCESSORIES:

Additional costs may be incurred

- - ET71-1-BVS-OTG Thermostatic mixing valve is ASSE Listed per the ASSE 1071 standard. The tepid output water complies with ANSI Z358.1 standard. Valve includes Ball Valve Shut-offs and Outlet Temperature Gauge
- - FLW2 Flow switch, single pole
- - FPV Freeze protection valve
- - MS1 MAP (magnetically actuated proximity) switch, for one (1) actuator
- - PT1 P-trap, chrome plated brass with 1-1/4" OD waste outlet
- - SDC Stainless steel dust covers
- - SPV Scald protection valve
- - SV2 Stainless steel ball valve.
- "1" Auxiliary hand-held drench hose with a self-closing valve (Use model S0481-BF)



Safety Manufacturing® assumes no responsibility for use of void or superseded data. © Copyright Safety Manufacturing, City of Industry, CA. A Morris Group International® Brand. Please visit www.safetymfg.com for most current specifications.

Submital # **S0480-BF**
[CMB] Date: 11/05/2024

Product carries the following certifications:



[Link To 3rd Party Certification](#)

Test rating conditions are compliant to ANSI Z358.1




SAFETY MFG
15125 Proctor Ave.
City of Industry, CA
91746 U.S.A.
Phone 800-591-9372

www.safetymfg.com

TECHNICAL DIMENSIONS

All dimensions are subject to manufacturer's tolerance of plus or minus 1/2" nominal and subject to change without notice. Safety Manufacturing® assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. © Safety Manufacturing®, A Morris Group International® Brand. Please visit www.safetymfg.com for most current specifications.

□ Model S0480-BF : Barrier Free, Wall Mounted Eye/Face Wash, Stainless Steel Shrouded Bowl



GENERAL NOTES: (ANSI Z358.1 STATEMENTS PROVIDED AS REFERENCE ONLY AND SUBJECT TO CHANGE.)


1. ALL DIMENSIONS ARE INCHES [MM].

*2. ANSI Z358.1 REQUIRES NOZZLES TO BE MOUNTED BETWEEN 33" - 45" [838 - 1143] ABOVE THE FINISHED FLOOR.

3. ANSI Z358.1 REQUIRES SUPPLY WORKING PRESSURE OF 30 PSI TO 80 PSI.

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

S0480-BF REV: 11/05/2024

SELECTION SUMMARY & APPROVAL FOR MANUFACTURING	Model Number & Options _____	Quantity _____	 800-591-9372 www.safetymfg.com
	Company _____		
	Contact _____ Title _____		
	Signature (Approval for Manufacturing) _____		
	Date _____		