

CALL FREE ON 0800 05 999 07 or EMAIL sales@mattingltd.com



Flexi Dot Vinyl Flooring

Tough Slip Resistant Matting Solution



Flexi Dot is a light duty and attractive vinyl flooring with a dot pattern. It is a highly functional multipurpose flooring that due to the large roll format can cover big areas with ease.

Eco Dot is an ecological and more economical version of Flexi Dot manufactured from 100% recycled factory waste.

Flexi Dot Extra is an extra thick version of the popular Eco Dot vinyl floor for heavier traffic areas



Main Benefits

- ▣ Feature Design Surface
- ▣ Hard wearing
- ▣ Option of economical version Eco Dot
- ▣ Option of thicker version Flexi Dot Extra
- ▣ Chemical, oil and acid resistant
- ▣ Easy to cut on site
- ▣ Contours to uneven surfaces
- ▣ Quick to install
- ▣ Supplied in convenient rolls

Flexi Dot and Eco Dot is available in a roll width of 25Mtrs, Flexi Dot Extra and Eco Dot Extra rolls are 20Mtrs. Roll widths for all Flexi Dot products are 98cm wide with a height of 1.6mm for Flexi and Eco Dot and 2.5mm for Flexi and Eco Dot Extra. Flexi Dot and Extra are available in Blue and Red, Eco Dot and Extra available in Grey or Black.



Matting Ltd
Company reg - 08599377
Vat - 166 4588 70
Call:0800 0599907 email: sales@mattingltd.com

Technical data sheet FlexiDot Vinyl Flooring



Size and weight Flexi Dot and Eco Dot	Length 0+.03	Height +/- 0.5	Widths in cm	Weight
	Metres	Millimetres	+/- 1	Kg/m ²
	25	1.6	98	2.4

Size and weight Flexi Dot and Eco Dot Extra	Length 0+.03	Height +/- 0.5	Widths in cm	Weight
	Metres	Millimetres	+/- 1	Kg/m ²
	20	2.5	98	3.8

General

APPEARANCES	Continuous sheet format with circled patterns		
COLOURS	Flexi Dot / Flexi Dot Extra – Blue or Red	Eco Dot / Eco Dot Extra - Grey or Black	
DURABILITY	Continuous extruded sheet with high scuff resistance		
WORKABILITY	Available in rolls for easy installation. Flexible Construction, is easy to cut and shape on site		
USES	Indoor or outdoor use for floor protection and floor enhancement		

Technical Data

CHEMICAL	Resistant to most acids, alkalines and oils. (For detailed chemical resistance analysis please see www.plastexmatting.com/matfax/doc.php?doc_id=154&action=inline)
COMPOSITION	Flexible DINP Plasticised Polyvinyl Chloride (PVC).
ENVIRONMENT	The manufacturer does not use any substances currently included in the SVHC (substances of Very High Concern) list under R.E.A.C.H. in any matting products.
FIRE	EN ISO 13501 – 1: 2007 – Bfl- S1
HYGIENE	Non-porous PVC – Inhibits the growth of bacteria
REVERSION	Thermoplastic shrinkage can result in size reductions of up to 2%. Accelerated in hot environments
THERMAL	Functional -23°C + 60°C (slight size variation may occur at temperature extremes).
UV Light	Resistant to PVC degradation; uncoloured PVC material BS EN607=Delta E1.02
WARRANTY	1-2 years manufactures warranty – Please ask for further details and terms.