

CALL FREE ON 0800 05 999 07 or EMAIL [sales@mattingltd.com](mailto:sales@mattingltd.com)



## Flexi Button Vinyl Flooring

### Heavy Duty Deep Stud Matting



Flexi Button is a multi-purpose, heavy duty sheet Vinyl suited for commercial and medium duty industrial applications. It features a distinctive deep stud design for enhanced slip resistance.

Flexi Button is easy to clean and slip resistant. It is formulated to cope with light spillages and is Chemical, oil and acid resistant.

#### **Main Benefits**

- Good slip resistance
- Very hard wearing
- Chemical, oil and acid resistant
- Convenient sheet vinyl system
- Easy to clean and maintain
- High scuff resistance
- Easy to cut on site
- Contours to uneven surfaces
- Deep stud design
- Quick to install



Flexi Button Sheet Vinyl flooring is available in a roll width of 98cm. Rolls are a standard length of 20Mtrs and stand 3.3mm high. Flexi Button sheet vinyl floorings is available in homogenous standard colours of black, blue and dark grey.



Matting Ltd  
Company reg - 08599377  
Vat - 166 4588 70  
Call:0800 0599907 email: [sales@mattingltd.com](mailto:sales@mattingltd.com)

## Technical data sheet Flexi Button Vinyl Flooring



Size and weight Flexi Button	Length 0+.03	Height +/- 0.5	Widths in cm	Weight
	Metres	Millimetres	+/- 1	Kg/m <sup>2</sup>
	20	3.3	98	4.3

### **General**

APPEARANCES	Continuous sheet format with circled patterns
COLOURS	Black, Blue or Dark Grey
DURABILITY	Continuous extruded sheet with high scuff resistance
WORKABILITY	Available in rolls for easy installation. Flexible Construction, is easy to cut and shape on site
USES	Indoor or outdoor use for floor protection and floor enhancement

### **Technical Data**

CHEMICAL	Resistant to most acids, alkalines and oils. ( For detailed chemical resistance analysis please see <a href="http://www.plastexmatting.com/matfax/doc.php?doc_id=154&amp;action=inline">www.plastexmatting.com/matfax/doc.php?doc_id=154&amp;action=inline</a> )
COMPOSITION	Flexible DINP Plasticised Polyvinyl Chloride (PVC).
ENVIRONMENT	The manufacturer does not use any substances currently included in the SVHC ( substances of Very High Concern) list under R.E.A.C.H. in any matting products.
FIRE	EN ISO 13501 – 1: 2007 – Bfl- S1
HYGIENE	Non-porous PVC – Inhibits the growth of bacteria
REVERSION	Thermoplastic shrinkage can result in size reductions of up to 2%. Accelerated in hot environments
THERMAL	Functional -23°C + 60°C (slight size variation may occur at temperature extremes).
UV Light	Resistant to PVC degradation; uncoloured PVC material BS EN607=Delta E1.02
WARRANTY	1-2 years manufactures warranty – Please ask for further details and terms.