

CALL FREE ON 0800 05 999 07 or EMAIL sales@mattingltd.com



Flexigrid Matting

Tough Slip Resistant Matting Solution



Flexigrid is the heavy duty matting solution for industry. Combining a higher profile with an open grid and an aggressive grip surface. Flexigrid delivers slip resistance and drainage where spillage, debris and metal shards are an issue.

Made from 100% recycled materials Flexigrid is the perfect solution for safety in tough environments

Main Benefits

- Very high slip resistance
- Exceptionally hard wearing
- Made from 100% recycled materials
- Chemical, oil and acid resistant
- Loose lay yet stable underfoot
- Easy to clean and maintain
- Excellent drainage certification
- UV resistant
- Hygienic
- Excellent cushioning, thermal and noise reducing properties





Flexigrid matting is available in two roll widths 60cm or 91cm. Rolls can be either 5 or 10 metres long each 20mm high. There is the option for modules with fitted edges to 3 sides and 180cmx60cm or 180cmx91cm. Flexigrid matting is available in homogenous standard colour of black.



Matting Ltd
Company reg - 08599377
Vat - 166 4588 70
Call:0800 0599907 email: sales@mattingltd.com

Technical data sheet Flexigrid matting



Size and weight Flexigrid	Length 0+.03	Height +/- 0.5	Widths in cm		Weight
	Metres	Millimetres	+/- 1		Kg/m ²
	1.8 or 5 or 10	20	60	91	9.8

General

APPEARANCES	Open grid "Duckboard" design with textured surface.
COLOURS	Black homogeneous stable colour.
DURABILITY	One piece welded construction for long life and minimal maintenance
INSTALLATION	Loose laid
WORKABILITY	Available in rolls for easy installation. Flexible Construction, is easy to cut and shape on site
USES	Heavy duty for indoor and outdoor locations.

Technical Data

ACOUSTIC	Excellent sound absorption properties
CHEMICAL	Resistant to most acids, alkalines and oils. (For detailed chemical resistance analysis please see www.plastexmatting.com/matfax/doc.php?doc_id=154&action=inline)
COMPOSITION	Flexible DINP Plasticised Polyvinyl Chloride (PVC).
ENVIRONMENT	The manufacturer does not use any substances currently included in the SVHC (substances of Very High Concern) list under R.E.A.C.H. in any matting products.
FIRE	DIN4102 Part1-Classification B2
HYGIENE	Non-porous PVC – Inhibits the growth of bacteria
REVERSION	Thermoplastic shrinkage can result in size reductions of up to 2%. Accelerated in hot environments
SLIP RESISTANCE	ASTM F 1677 (Dry/Wet) (0.6/0.52) DIN 51130 R11, V10
THERMAL	Functional -23°C + 60°C (slight size variation may occur at temperature extremes).
UV Light	Resistant to PVC degradation; uncoloured PVC material BS EN607=Delta E1.02
WARRANTY	4 years manufactures warranty – Please ask for further details and terms.