

CALL FREE ON 0800 05 999 07 or EMAIL [sales@mattingltd.com](mailto:sales@mattingltd.com)



## Floorline Comfort Matting

### Slip resistant, Economical & Self Draining Safety Matting



Floorline matting is light, soft underfoot and decorative. Floorline is simple to roll for cleaning purposes and ideal for bar and catering areas where occasional spillage may occur.

Thanks to a slip resistant surface and open grid design for effective liquid drainage, it's a great performer. This economical matting insulates against cold, hard floors and reduces standing fatigue.

#### Main Benefits

- High slip resistance
- Loose lay yet stable underfoot
- Cushioned surface
- Economical alternative
- Easy to clean and maintain
- Long lasting
- Ideal for normal footwear
- Very good drainage
- Suitable for many applications




Floorline wet area matting is available in two roll widths 60cm or 90cm. All the rolls are 10 metres long and the grid stands at 6mm high. Floorline wet area matting is available in homogenous standard colours of Red\*, Blue, Green, Beige or white.

\* Red colour is not colourfast in direct sunlight.



Matting Ltd  
Company reg - 08599377  
Vat - 166 4588 70  
Call: 0800 0599907 email: [sales@mattingltd.com](mailto:sales@mattingltd.com)

## Technical data sheet Floorline comfort matting



Size and weight Floorline wet area matting	Length 0+.03	Height +/- 0.5	Widths in cm		Weight
	Metres	Millimetres	+/- 1		Kg/m <sup>2</sup>
	10	6	60	91	5.5

### General

APPEARANCES	Open grid "duckboard" design with hollow cushioned surface.
COLOURS	Available in homogenous standard colours: Red, Blue, Green, Beige and White. Please note Red colour is not colour fast in direct sunlight. Other colours available on request.
DURABILITY	One piece welded construction for long life and minimal maintenance
INSTALLATION	Loose laid, supplied in roll format for easy installation.
WORKABILITY	Available in rolls for easy installation. Flexible Construction, is easy to cut and shape on site
USES	All locations, both inside and outside. Red colour is not colourfast in direct sunlight.

### Technical Data

ACOUSTIC	Excellent sound absorption properties
CHEMICAL	Resistant to most acids, alkalines and oils. ( For detailed chemical resistance analysis please see <a href="http://www.plastexmatting.com/matfax/doc.php?doc_id=154&amp;action=inline">www.plastexmatting.com/matfax/doc.php?doc_id=154&amp;action=inline</a> )
COMPOSITION	Flexible DINP plasticised Polyvinyl Chloride ( PVC )
ENVIRONMENT	The manufacturer does not use any substances currently included in the SVHC (substances of Very High Concern) list under R.E.A.C.H. in any matting products. All PVC grid products are 100% recyclable.
FIRE	Din 4102 Part1- Classification B2 BS 2782 Part 1, Method 140A: 1992 (ISO 1210: 1992)
HYGIENE	Non-porous 100% Virgin PVC – Inhibits the growth of bacteria
REVERSION	Thermoplastic shrinkage can result in size reductions of up to 2%. Accelerated in hot environments
SLIP RESISTANCE	ASTM F 1677 (Dry/Wet) (0.6/0.5) DIN 51097 Classification C DIN51130 R11, V10
THERMAL	Functional -23°C + 60°C (slight size variation may occur at temperature extremes).
UV Light	Resistant to PVC degradation; uncoloured PVC material BS EN607=Delta E1.02
WARRANTY	1 years manufactures warranty – Please ask for further details and terms