

CALL FREE ON 0800 05 999 07 or EMAIL [sales@mattingltd.co.uk](mailto:sales@mattingltd.co.uk)



## Floorline Wet Area Matting

### Slip resistant, Economical & Self Draining Safety Matting



Floorline wet area matting provides an economical alternative for lighter duty applications, providing slip resistance inside or out. The open grid slip resistant surface provides effective safety underfoot in light traffic changing areas and swimming pool surrounds. Floorline wet area matting is resistant to UV degradation.

#### **Main Benefits**

- High slip resistance
- Loose lay yet stable underfoot
- Cushioned surface
- Economical alternative
- Easy to clean and maintain
- Long lasting
- UV resistant
- Very good drainage
- Suitable for many applications



Floorline wet area matting is available in two roll widths 60cm or 90cm. All the rolls are 10 metres long and the grid stands at 6mm high. Floorline wet area matting is available in homogenous standard colours of Red\*, Blue, Green, Beige or white.


\* Red colour is not colourfast in direct sunlight.



Matting Ltd  
Company reg – 08599377  
Vat – 166 4588 70  
Call:0800 0599907 email: [sales@mattingltd.co.uk](mailto:sales@mattingltd.co.uk)

**CALL FREE ON 0800 05 999 07 or EMAIL [sales@mattingltd.co.uk](mailto:sales@mattingltd.co.uk)**

## **Technical data sheet Floorline wet area matting**



Size and weight Floorline wet area matting	Length 0+.03	Height +/- 0.5	Widths in cm		Weight
	Metres	Millimetres	+/- 1		Kg/m <sup>2</sup>
	10	6	60	91	5.5

### **General**

APPEARANCES	Open grid "duckboard" design with hollow cushioned surface.
COLOURS	Available in homogenous standard colours: Red, Blue, Green, Beige and White. Please note Red colour is not colour fast in direct sunlight. Other colours available on request.
DURABILITY	One piece welded construction for long life and minimal maintenance
INSTALLATION	Loose laid, supplied in roll format for easy installation.
WORKABILITY	Available in rolls for easy installation. Flexible Construction, is easy to cut and shape on site
USES	All locations, both inside and outside. Red colour is not colourfast in direct sunlight.

### **Technical Data**

ACOUSTIC	Excellent sound absorption properties
CHEMICAL	Resistant to most acids, alkalines and oils. ( For detailed chemical resistance analysis please see <a href="http://www.plastexmatting.com/matfax/doc.php?doc_id=154&amp;action=inline">www.plastexmatting.com/matfax/doc.php?doc_id=154&amp;action=inline</a> )
COMPOSITION	Flexible DINP plasticised Polyvinyl Chloride ( PVC )
ENVIRONMENT	The manufacturer does not use any substances currently included in the SVHC (substances of Very High Concern) list under R.E.A.C.H. in any matting products. All PVC grid products are 100% recyclable.
FIRE	Din 4102 Part1- Classification B2 BS 2782 Part 1, Method 140A: 1992 (ISO 1210: 1992)
HYGIENE	Non-porous 100% Virgin PVC – Inhibits the growth of bacteria
REVERSION	Thermoplastic shrinkage can result in size reductions of up to 2%. Accelerated in hot environments
SLIP RESISTANCE	ASTM F 1677 (Dry/Wet) (0.6/0.5) DIN 51097 Classification C DIN51130 R11, V10
THERMAL	Functional -23°C + 60°C (slight size variation may occur at temperature extremes).
UV Light	Resistant to PVC degradation; uncoloured PVC material BS EN607=Delta E1.02
WARRANTY	1 years manufactures warranty – Please ask for further details and terms