

CALL FREE ON 0800 05 999 07 or EMAIL [sales@mattingltd.com](mailto:sales@mattingltd.com)



## Spark Safe Matting

### Anti-Fatigue Hot Works Matting Solution



Spark Safe has been developed primarily for the use of operatives welding or undertaking other forms of hot works. Spark Safe is a two part, all rubber constructed anti-fatigue matting with special heat repellent properties to withstand sparks and hot metal fragments

#### **Main Benefits**

- Fatigue reducing
- Slip resistant
- Heat repellent surface
- Wear resistant
- All rubber roll construction
- Loose lay yet stable underfoot
- Easy to clean and maintain




Spark Safe matting is available in modules 60cmx91cm or 91cmx150cm with bevelled edge on 4 sides. It is also available in a roll 18mtrs x 91cm. All Spark Safe matting is 10cm high. Spark Safe matting is available in homogenous standard colour of black.



Matting Ltd  
Company reg – 08599377  
Vat – 166 4588 70  
Call:0800 0599907 email: [sales@mattingltd.com](mailto:sales@mattingltd.com)

**CALL FREE ON 0800 05 999 07 or EMAIL [sales@mattingltd.com](mailto:sales@mattingltd.com)**

## **Technical data sheet Spark Safe matting**



Size and weight Spark Safe	Length 0+.03	Height +/- 0.5	Widths in cm	Weight
	Metres	Millimetres	+/- 1	Kg/m <sup>2</sup>
	<b>18</b> Also available in Modules <b>60cmx91cm and</b> <b>150cmx91cm</b>		<b>10</b>	<b>91</b>

### **General**

APPEARANCES Foam layer glued to top anti-spark layer.

COLOURS Black

DURABILITY 100% Rubber two part matting

INSTALLATION Loose laid

WORKABILITY Available in rolls for easy installation. Flexible Construction, is easy to cut and shape on site

USES Anti-Fatigue mat for hot works area.

### **Technical Data**

ACOUSTIC Excellent sound absorption properties

COMPOSITION Rubber foam with rubber wear layer.

FIRE ASTM D2859, DOC-FF-1-70

REVERSION Thermoplastic shrinkage can result in size reductions of up to 2%. Accelerated in hot environments

Anti-Fatigue Resilience ASTM 2362 score=35

THERMAL Functional -23°C + 60°C (slight size variation may occur at temperature extremes).

UV Light Resistant to PVC degradation.

WARRANTY 1 years manufactures warranty – Please ask for further details and terms.