

CALL FREE ON 0800 05 999 07 or EMAIL sales@mattingltd.com



Tuff Spun Matting

Economy Anti-Fatigue Matting Solution



Tuff Spun is a good value, hard working, anti-fatigue matting. Constructed of closed cell PVC foam with a ribbed slip resistant surface for lighter duty work. Tuff Spun also reduces impact noise and protects items accidentally dropped. Tuff Spun is available with yellow edging

Main Benefits

- Fatigue reducing
- REACH compliant vinyl foam
- Slip resistant
- Homogenous closed cell foam
- Light wear resistant
- All rubber roll construction
- Loose lay yet stable underfoot
- Noise reduction



Tuff Spun matting is available in modules 60cmx91cm, 91cmx150cm or 91cmx300cm. It is also available in a roll 18mtrs x 91cm in grey and yellow edged. In black it is available in 18mtr rolls by 60cm, 91cm or 122cm. Tuff spun is available in grey, black or Tuff Spun Plus which is black with a yellow edging.



Matting Ltd
Company reg - 08599377
Vat - 166 4588 70
Call:0800 0599907 email: sales@mattingltd.com

CALL FREE ON 0800 05 999 07 or EMAIL sales@mattingltd.com

Technical data sheet Tuff Spun matting



Size and weight Tuff Spun	Length 0+.03	Height +/- 0.5	Widths in cm	Weight
	Metres	Millimetres	+/- 1	Kg/m ²
	18 Also available in Modules 60cmx91cm 150cmx91cm 300cmx91cm	9	91cm Black available 60,91 or 122cm	3.3

General

APPEARANCES	Single layer of foam with ribbed surface
COLOURS	Black, grey or black with yellow edge
DURABILITY	Extruded vinyl foam
INSTALLATION	Loose laid
WORKABILITY	Available in rolls for easy installation. Flexible Construction, is easy to cut and shape on site
USES	Anti-Fatigue mat for indoor use, dry area.

Technical Data

ACOUSTIC	Excellent sound absorption properties
COMPOSITION	Vinyl foam
FIRE	ASTM D2859, DOC-FF-1-70
REVERSION	Thermoplastic shrinkage can result in size reductions of up to 2%. Accelerated in hot environments
WEAR RATINGS	ASTM D4060 @ 1000cycles <1g
THERMAL	Functional -23°C + 60°C (slight size variation may occur at temperature extremes).
UV Light	Resistant to PVC degradation.
WARRANTY	1 years manufactures warranty – Please ask for further details and terms.