#### CALL FREE ON 0800 05 999 07 or EMAIL sales@mattingltd.com

# MATTINGLTD

# Zed Land Matting


## **Best selling Anti-Fatigue Matting Solution**



Zed Land is a patented foam construction giving superior resilience. Made from high molecular density foam with 'bounce' properties up to 4 times as effective as standard foam matting. Standing employees working on Zed Land will feel better and have improved productivity. Dropped components will also be protected from accidental damage.

#### Main Benefits

- Fatigue reducing
- High wear resistance
- Slip resistant
- High performance in cold environments
- Patented foam construction
- Loose lay yet stable underfoot
- Noise reduction




Zed Land matting is available in modules 60cmx91cm, 91cmx150cm or 91cmx300cm. It is also available in a roll 18mtrs x 91cm. Zed Land is available in the standard colours of Blue or Dark Grey.



Matting Ltd Company reg – 08599377 Vat – 166 4588 70 Call:0800 0599907 email: sales@mattingltd.com

### CALL FREE ON 0800 05 999 07 or EMAIL sales@mattingltd.com

# **Technical data sheet Zed Land matting**







		Length 0+.03	Height +/- 0.5	Widths in cm	Weight
Size and weight Zed Land		Metres 18 Also available in Modules 60cmx91cm 150cmx91cm 300cmx91cm	Millimetres 9	+/- 1	Kg/m²
				91cm	3.3
<u>General</u> APPEARANCES	Single I	ayer of foam.			
COLOURS	Blue or Dark Grey				
DURABILITY	Extruded vinyl foam				
INSTALLATION	Loose laid				
WORKABILITY	Available in rolls for easy installation. Flexible Construction, is easy to cut and shape on site				
USES	Anti-Fatigue mat for indoor use, dry area.				
Technical Data					
ACOUSTIC	Excellent sound absorption properties				
ANTI-FATIGUE	Resilience ASTM 2362 = 33				
COMPOSITION	Vinyl foam				
ELECTROSTATIC DISCHARGE (ESD)	Zed Land = 10 <sup>9</sup>				
FIRE	ASTM D2859, DOC-FF-1-70				
REVERSION	Thermoplastic shrinkage can result in size reductions of up to 2%. Accelerated in hot environments				
THERMAL	Functional $-23^{\circ}C + 60^{\circ}C$ (slight size variation may occur at temperature extremes).				
UV LIGHT	Resistant to PVC degradation.				
WEAR RATINGS	ASTM D4060 @1000 cycles <0.5g				
WARRANTY	Total confidence warranty – Please ask for further details and terms.				



Matting Ltd Company reg – 08599377 Vat – 166 4588 70 Call:0800 0599907 email: sales@mattingltd.com