



# BC SEAL BAND

Article Code see DDT  
Date of issue 17.05.2010  
Revision nr. 01  
Page 1 of 2

Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italia Tel. +39 02/267.00.605 – Fax +39 02/267.00.621 –  
[info@winklerchimica.com](mailto:info@winklerchimica.com) [www.winklerchimica.com](http://www.winklerchimica.com)

## DESCRIPTION

Self adhesive band based on butylic mastic covered with non-woven which allows the deformation of the product. The adhesive side is protected by peel off support.

## APPLICATION FIELDS

Sealing of wall-floor joints under tile. The non-woven covering adapts to the support form and can be covered by tile adhesive or other covering, or paints. Joints waterproofing. Slits reparation in cement or fiber-cement.

## TECHNICAL CHARACTERISTICS

NON WOVEN COVERING		
Nature		100% polypropylene
Mass m <sup>2</sup>	D 45 1012	50 g/m <sup>2</sup>
Break resistance	Lengthwise	90 N/5 cm
	Transversal	65 N/5 cm
Water-repellent		yes

ADHESIVE BUTYLIC MASTIC		
Solids content by weight		> 99%
Drip resistance	Butyl at 5°C ISO 7390	≤ 3 mm
	Butyl at 70°C ISO 7390	≤ 3 mm
Reaction a -30°C	D 421313	No detach
Strain resistance	Hot, pierced plate method D 45 5256	No strain
Peeling a 90°	On steel MEL 052	≥ 4 N/cm
Temperature	Application temperature	+ 5°C ≤ T ≤ +40°C
	Hold break	- 30°C ≤ T ≤ +80°C

## APPLICATION

### Supports preparation

Verify the compatibility of mastic with different supports in terms of adhesion and chemical compatibility.

Application surfaces must be clean, dry and free from dust.

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. WINKLER S.r.l. reserves the right to modify and up-date said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.



# BC SEAL BAND

Article Code see DDT  
Date of issue 17.05.2010  
Revision nr. 01  
Page 2 of 2

Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italia Tel. +39 02/267.00.605 – Fax +39 02/267.00.621 –  
[info@winklerchimica.com](mailto:info@winklerchimica.com) [www.winklerchimica.com](http://www.winklerchimica.com)

## APPLICATION

Remove the protection, put the band on the support avoiding the formation of air bubbles between the butyl and the support.

For joints superimpose the products of at least 5 cm.

The non-woven support can be repainted but, given the extreme flexibility of butylic mastic, the painted layer, covering the non-woven could present light cracks. The covering, adhesives or paints which cover the non-woven must be compatible with it. Butylic mastic is susceptible to solvents.

## PACKAGING

### Colour:

Non-woven: white

Butyl: grey

## IMPORTANT INFORMATION

Avoid contact with skin.

Keep away from children.

## STORAGE

The product has 12 months stability from the production date if properly packed and not opened. Store in a ventilated room sheltered from dampness at a maximum temperature of 30°C.

## SAFETY INSTRUCTIONS

### PRECAUTIONS

For information about safety, user must refer to the most recent Safety Data Sheet, edited in accordance with the regulations in force, which contains physical, toxic and other data about the product in use.

### ECOLOGY

Do not through out the product and/or empty containers in the environment. Consult the most recent Safety Data Sheet for further information about disposals.

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. WINKLER S.r.l. reserves the right to modify and up-date said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.