

# Wire Solutions

## Casters • Dolly Bases

**Stem Casters:** For use with posts. Non-marking polyurethane.

SIZE	WT.	CAPACITY	SWIVEL	RIGID	SWIVEL W/BRAKE
(inches)	(lbs.)	(lbs.)	Model #	Model #	Model #
5 x 1.25	2	250	5C	5CR	5CB



5C

5CB

**Plate Casters:** For use with dollies.  
5" Casters: Non-marking polyurethane.

SIZE	WT.	CAPACITY	SWIVEL	RIGID	SWIVEL W/BRAKE
(inches)	(lbs.)	(lbs.)	Model #	Model #	Model #
5 x 1.25	2	250	C5	C5R	C5B



C5

C5B

6" Casters: Premium ergonomic elastomere non-marking casters.  
For heavy-duty transport.

SIZE	WT.	CAPACITY	SWIVEL	RIGID	SWIVEL W/BRAKE	4 - POSITION DIRECTION LOCK
(inches)	(lbs.)	(lbs.)	Model #	Model #	Model #	Model #
6 x 2	4	800	31-76XSR	31-76RXSR	31-76BXSXR	31-76FPXSXR



31-76R XSR

31-76B XSR

Many other casters available to suit specialty applications

**Donut Bumpers:** For use with stem casters. Non-marking polyurethane.

SIZE	WT.	MODEL #
(inches)	(lbs.)	
3.5	.25	RDB325



RDB325

THP9448NSCH

Closed Dolly with Stainless Insert



THP9448CH Open Dolly

### Dolly Bases

DIMENSIONS	WT.	OPEN	SOLID EPOXY INSERT	SOLID STAINLESS INSERT
(inches)	(lbs.)	Model #	Model #	Model #
18 x 36	30	THP9836CH	THP9836NTCH	THP9836NSCH
18 x 48	40	THP9848CH	THP9848NTCH	THP9848NSCH
18 x 60	50	THP9860CH	THP9860NTCH	THP9860NSCH
18 x 72	60	THP9872CH	THP9872NTCH	THP9872NSCH
24 x 36	40	THP9436CH	THP9436NTCH	THP9436NSCH
24 x 48	53	THP9448CH	THP9448NTCH	THP9448NSCH
24 x 60	67	THP9460CH	THP9460NTCH	THP9460NSCH
24 x 72	80	THP9472CH	THP9472NTCH	THP9472NSCH

### Dolly Bases

Heavy-duty all-welded dolly fabricated with integral C-channel welded to steel plate frame. Non-marking wrap-around bumper.

Dollies are available in three styles: Open, premium epoxy-coated solid insert or stainless steel solid insert. Inserts adhere to infection control standards and function as solid bottom shelves which eliminates the additional wire shelf requirement.

### Other Standard Sizes Available on Request:

- Depth: 21"
- Widths: 42" and 54"