

Wire Solutions

Casters • Dolly Bases

Stem Casters: For use with posts. Non-marking polyurethane.

SIZE	WT.	CAPACITY	SWIVEL	RIGID	SWIVEL W/BRAKE
(inches)	(lbs.)	(lbs.)	Model #	Model #	Model #
5 x 1.25	2	250	5C	5CR	5CB



5C

5CB

Plate Casters: For use with dollies.
5" Casters: Non-marking polyurethane.

SIZE	WT.	CAPACITY	SWIVEL	RIGID	SWIVEL W/BRAKE
(inches)	(lbs.)	(lbs.)	Model #	Model #	Model #
5 x 1.25	2	250	C5	C5R	C5B



C5

C5B

6" Casters: Premium ergonomic elastomere non-marking casters.
For heavy-duty transport.

SIZE	WT.	CAPACITY	SWIVEL	RIGID	SWIVEL W/BRAKE	4 - POSITION DIRECTION LOCK
(inches)	(lbs.)	(lbs.)	Model #	Model #	Model #	Model #
6 x 2	4	800	31-76XSR	31-76RXSR	31-76BXSXR	31-76FPXSXR

Many other casters available to suit specialty applications



31-76R XSR

31-76B XSR

Donut Bumpers: For use with stem casters. Non-marking polyurethane.

SIZE	WT.	MODEL #
(inches)	(lbs.)	
3.5	.25	RDB325



RDB325

THP9448NSCH

Closed Dolly with Stainless Insert



THP9448CH Open Dolly

Dolly Bases

DIMENSIONS	WT.	OPEN	SOLID EPOXY INSERT	SOLID STAINLESS INSERT
(inches)	(lbs.)	Model #	Model #	Model #
18 x 36	30	THP9836CH	THP9836NTCH	THP9836NSCH
18 x 48	40	THP9848CH	THP9848NTCH	THP9848NSCH
18 x 60	50	THP9860CH	THP9860NTCH	THP9860NSCH
18 x 72	60	THP9872CH	THP9872NTCH	THP9872NSCH
24 x 36	40	THP9436CH	THP9436NTCH	THP9436NSCH
24 x 48	53	THP9448CH	THP9448NTCH	THP9448NSCH
24 x 60	67	THP9460CH	THP9460NTCH	THP9460NSCH
24 x 72	80	THP9472CH	THP9472NTCH	THP9472NSCH

Dolly Bases

Heavy-duty all-welded dolly fabricated with integral C-channel welded to steel plate frame. Non-marking wrap-around bumper.

Dollies are available in three styles: Open, premium epoxy-coated solid insert or stainless steel solid insert. Inserts adhere to infection control standards and function as solid bottom shelves which eliminates the additional wire shelf requirement.

Other Standard Sizes Available on Request:

- Depth: 21"
- Widths: 42" and 54"

1



SLFR-V
Frame for trays

2



B36-V
Top basket

3



PSCAP-V
Stainless dust cover

4




BTO-V
Wire top shelf

5



TU1620CVR-V
Stainless steel cover for wire shelf

6



TU1620RPS-V
Wire shelf

7



FR68-VHD
Frame

8



REDSTOP
Safety stop

9



INSERT-V
Dust shield

10



TOP-SINGLE-H-V
Stainless steel top with push handle

Par Stor Accessories

MODEL NUMBER	REFERENCE # PHOTO	DIMENSIONS	DESCRIPTION
TU1620RPS-V	5	24 x 15.5 x 3	Chrome wire shelf for slides. Has 2" h lip in rear, 1" h lip in front for labeling. Occupies 2 slots.
TTU1620RPS-V	5	24 x 15.5 x 3	White wire shelf for slides. Has 2" h lip in rear, 1" h lip in front for labeling. Occupies 2 slots.
TU1620CVR-V	5	23.25 x 14.25 x 1.25	Stainless steel cover for wire shelf. Converts wire shelf to solid.
SLFR-V	1	23.75 x 15.75 x 1	Frame required for trays.
BTO-V	4	24.5 x 18.5 x 3	Wire shelf for top of PS68, 2" h lip in rear, 1" h lip in front for labeling.
B20-V	2		Basket for top of single PS68 or Open Par Cart. Sits on top of unit, thus adding height.
B36-V	2	19.75 x 35 x 9	Basket for top of double PS68 or Open Par Cart. Sits on top of unit, thus adding height. Front of basket is slanted and 5" h.
SL-V	N/A	24 long	Slides (pair).
SLT-V	N/A	24 long	Slides for slanting (pair), includes safety stop. Can slant up to 4 slots.
TOP-SINGLE-V	10	24 x 20 x 1	Stainless top for single PS68.
TOP-SINGLE-H-V	10	26.75 x 20 x 1	Stainless top with push handle in front, or single PS68. 16.75" w handle protrudes 2.25".
TOP-DOUBLE-V	10	24.5 x 39 x 1	Stainless top for a double PS68.
TOP-DOUBLE-B-V	10	24.5 x 39 x 1	Top four open Par Cart epoxy coated blue.
LH3	N/A	3L x 1H	Bin Tag (label holder) four baskets. Specify white, yellow, green, red or blue.
LH132PS	N/A	13.86L x 2H	Label holder clear.
LH134PS	N/A	13.86L x 4H	Label holder clear.

Par Stor® Accessories Continued

MODEL NUMBER	REFERENCE # PHOTO	DIMENSIONS	DESCRIPTION
PNC320-V	N/A	24.5 x 38.5 x 35	Cart cover for 320-V. Must specify colour and type of closure.
PNC600-V	N/A	24.5 x 20 x 66	Cart cover with two handle cut outs for 600H-V. Must specify colour and type of closure.
5C	N/A	5	Caster, swivel for PS68. Not for Par Cart.
5CB	N/A	5	Caster, brake for PS68. Not for Par Cart.
PSLF	N/A		Leveling foot for PS68.
CB18JB-V	N/A	0.5 x 1.5 x 17.5	Standard cross bar for PS68 frame.
INSERT-V	9	19.5 x 21.75	Bottom dust shield for PS68.
PSCAP-V	3	24.75 x 16.875	Stainless steel dust cover for top of a PS68.
REDSTOP	8		Red safety stop with hardware (included in slant slide).
FR31-VHD	7	24 x 31.5	Stationary PS68 frame, 24 slots. No cross bars or leveling feet.
FR68-VHD	7	24 x 68	Stationary PS68 frame, 57 slots. No cross bars or leveling feet.

Materials

PAR STOR

- Frame is 1" square 12-gauge cold rolled steel, nickel/chrome plated
- Cross bar is .625" square, 12-gauge steel tube
- Each stationary frame has .75" height adjustable floor foot bolts
- Casters are 5"; two swivel and two swivel brake
- Slides are ball bearing full-extension
- Bottom dust shield is plastic

PAR CART

- Frame is 1" square 16-gauge tube, epoxy coated gray
- Integrated dolly is 1" x 2" 16-gauge tube, epoxy coated gray
- Floor is 18 gage, epoxy coated gray
- Casters are 5"; two swivel and two swivel brake
- Donut bumper is rubber
- Enclosure panels are steel epoxy coated blue
- Door is .375" clear acrylic
- Door hinges (3) are steel pin style
- Slides are ball bearing full-extension

WEIGHT LOADS

- Each slide has a 50 lb. test load capacity