

1



SLFR-V
Frame for trays

2



B36-V
Top basket

3



PSCAP-V
Stainless dust cover

4




BTO-V
Wire top shelf

5



TU1620CVR-V
Stainless steel cover for wire shelf

6



TU1620RPS-V
Wire shelf

7



FR68-VHD
Frame

8



REDSTOP
Safety stop

9



INSERT-V
Dust shield

10



TOP-SINGLE-H-V
Stainless steel top with push handle

Par Stor Accessories

MODEL NUMBER	REFERENCE # PHOTO	DIMENSIONS	DESCRIPTION
TU1620RPS-V	5	24 x 15.5 x 3	Chrome wire shelf for slides. Has 2" h lip in rear, 1" h lip in front for labeling. Occupies 2 slots.
TTU1620RPS-V	5	24 x 15.5 x 3	White wire shelf for slides. Has 2" h lip in rear, 1" h lip in front for labeling. Occupies 2 slots.
TU1620CVR-V	5	23.25 x 14.25 x 1.25	Stainless steel cover for wire shelf. Converts wire shelf to solid.
SLFR-V	1	23.75 x 15.75 x 1	Frame required for trays.
BTO-V	4	24.5 x 18.5 x 3	Wire shelf for top of PS68, 2" h lip in rear, 1" h lip in front for labeling.
B20-V	2		Basket for top of single PS68 or Open Par Cart. Sits on top of unit, thus adding height.
B36-V	2	19.75 x 35 x 9	Basket for top of double PS68 or Open Par Cart. Sits on top of unit, thus adding height. Front of basket is slanted and 5" h.
SL-V	N/A	24 long	Slides (pair).
SLT-V	N/A	24 long	Slides for slanting (pair), includes safety stop. Can slant up to 4 slots.
TOP-SINGLE-V	10	24 x 20 x 1	Stainless top for single PS68.
TOP-SINGLE-H-V	10	26.75 x 20 x 1	Stainless top with push handle in front, or single PS68. 16.75" w handle protrudes 2.25".
TOP-DOUBLE-V	10	24.5 x 39 x 1	Stainless top for a double PS68.
TOP-DOUBLE-B-V	10	24.5 x 39 x 1	Top four open Par Cart epoxy coated blue.
LH3	N/A	3L x 1H	Bin Tag (label holder) four baskets. Specify white, yellow, green, red or blue.
LH132PS	N/A	13.86L x 2H	Label holder clear.
LH134PS	N/A	13.86L x 4H	Label holder clear.

Par Stor® Accessories Continued

MODEL NUMBER	REFERENCE # PHOTO	DIMENSIONS	DESCRIPTION
PNC320-V	N/A	24.5 x 38.5 x 35	Cart cover for 320-V. Must specify colour and type of closure.
PNC600-V	N/A	24.5 x 20 x 66	Cart cover with two handle cut outs for 600H-V. Must specify colour and type of closure.
5C	N/A	5	Caster, swivel for PS68. Not for Par Cart.
5CB	N/A	5	Caster, brake for PS68. Not for Par Cart.
PSLF	N/A		Leveling foot for PS68.
CB18JB-V	N/A	0.5 x 1.5 x 17.5	Standard cross bar for PS68 frame.
INSERT-V	9	19.5 x 21.75	Bottom dust shield for PS68.
PSCAP-V	3	24.75 x 16.875	Stainless steel dust cover for top of a PS68.
REDSTOP	8		Red safety stop with hardware (included in slant slide).
FR31-VHD	7	24 x 31.5	Stationary PS68 frame, 24 slots. No cross bars or leveling feet.
FR68-VHD	7	24 x 68	Stationary PS68 frame, 57 slots. No cross bars or leveling feet.

Materials

PAR STOR

- Frame is 1" square 12-gauge cold rolled steel, nickel/chrome plated
- Cross bar is .625" square, 12-gauge steel tube
- Each stationary frame has .75" height adjustable floor foot bolts
- Casters are 5"; two swivel and two swivel brake
- Slides are ball bearing full-extension
- Bottom dust shield is plastic

PAR CART

- Frame is 1" square 16-gauge tube, epoxy coated gray
- Integrated dolly is 1" x 2" 16-gauge tube, epoxy coated gray
- Floor is 18 gage, epoxy coated gray
- Casters are 5"; two swivel and two swivel brake
- Donut bumper is rubber
- Enclosure panels are steel epoxy coated blue
- Door is .375" clear acrylic
- Door hinges (3) are steel pin style
- Slides are ball bearing full-extension

WEIGHT LOADS

- Each slide has a 50 lb. test load capacity