

IFA-9 and IFA-10

The PS-1 Wall mount power supply for the IFA Series

The new PS-1 is a regulated ± 16 volt @ 300 mA wall mount power supply. One PS-1 will power any one of the IFA series interface devices now offered by Benchmark.

The IFA-9 - a Compact 1 in/6 out Stand Alone audio DA

Features:

- 20 k Ω balanced input
- +27 dBu input clip point
- CMR 90 dB @ 2 kHz, 75 dB @ 20 kHz typical
- Common mode input filter virtually eliminates RFI
- Master gain range: -10 to +20 dB
- THD = 0.0009% @ 2 kHz typical
- DIM-30 is 0.005%
- Noise floor: -104 dBu @ unity gain
- Dynamic range: 130+ dB
- Highest sonic quality
- Bi-colored LED for signal presence & peak level indication
- 60 Ω balanced output
- +27 dBu output clip point
- Individual output gain range: unity to -20 dB

Requires one PS-1 wall mount power supply or the PS-12 rackmount power supply.

The IFA -10 - a Compact 4 in/4 out Assignable Mixer

Features:

- 20 k Ω balanced input
- +27 dBu input clip point
- CMR 90 dB @ 2 kHz, 75 dB @ 20 kHz typical
- Common mode input filter virtually eliminates RFI
- Master gain range: -10 to +20 dB
- THD = 0.0009% @ 2 kHz typical
- DIM-30 is 0.005%
- Noise floor: -104 dBu @ unity gain
- Dynamic range: 130+ dB
- Highest sonic quality
- 60 Ω balanced output
- +27 dBu output clip point
- Individual output gain range: unity to -20 dB

Requires one PS-1 wall mount power supply or the PS-12 rackmount power supply.

Benchmark Media Systems, Inc.
5925 Court Street Road
Syracuse, NY 13206 -1707
Phone: (315) 437-6300 FAX: (315)437-8119