



AXIS WALL SCONCE by Juniper

SPECIFICATIONS

Typical Lead Time
6-8 Weeks

Color / Finish
Satin Nickel

Size
12 in

Color Temperature
3000K

Power Supply
L. Standard Local 120-277V |
2-Wire/TRIAC/Forward-Phase,
0-10V, ELV
Dimming/Reverse-Phase

Total Wattage & Lumens
12 IN - 4.5W, 0-270LM
24 IN - 9W, 0-650LM
36 IN - 14W, 0-900LM
48 IN - 18.5W, 0-1200LM

Light Quality
CRI 95+, R9 90+

LED Lifespan
50,000 hrs, L80

Body Material
Bronze, Frosted PMMA

Weight
12 IN - 5 lbs
24 IN - 9 lbs
36 IN - 13 lbs
48 IN - 17 lbs

Power
Class 2, 120-277 AC input,
24VDC output

Mounting
Mounted to wall using
provided wood screws

Certifications
cUL, UL, CE, Title 24, Damp
Location Rated

MORE INFORMATION & OPTIONS

Designer
Miren Lasnier at Juniper

Length Options
12 IN
24 IN
36 IN
48 IN
2.5 IN x 5 IN Profile

Color Temperature Options
2700K
3000K
3500K
4000K

Finish Options
Satin Brass
Polished Brass
Black Oxide
Antique Pewter
Black Walnut
Grey-Stained Ash

Dimming Options
2-Wire/TRIAC/Forward
Phase
0-10V
3-Wire/Ecosystem

Power Supply Options
L. Standard Local 120-277V |
2-Wire/TRIAC/Forward-Phase,
0-10V, ELV
Dimming/Reverse-Phase
R. Standard Remote
120-277V | 0-10V Dimming
R. Standard Remote
120-277V | ELV Dimming
R. Standard Remote 120V |
2-Wire/TRIAC/Forward-Phase
R. Standard Remote 277V |
2-Wire/TRIAC/Forward-Phase
R. Lutron Remote 120-277V |
3-Wire, Digital Ecosystem
Dimming | Hi-Lume Series
R. Lutron Remote 120V |
2-Wire/TRIAC/Forward-Phase
Dimming | Hi-lume
Series