



AXIS WALL SCONCE by Juniper

SPECIFICATIONS

Typical Lead Time 6-8 Weeks	Color / Finish	Size 36 in	Color Temperature 3000K	Power Supply L. Standard Local 120-277V 2-Wire/TRIAC/Forward-Phase, 0-10V, ELV Dimming/Reverse-Phase
Total Wattage & Lumens 12 IN – 4.5W, 0-270LM 24 IN – 9W, 0-650LM 36 IN – 14W, 0-900LM 48 IN – 18.5W, 0-1200LM	Light Quality CRI 95+, R9 90+	LED Lifespan 50,000 hrs, L80	Body Material Bronze, Frosted PMMA	Weight 12 IN – 5 lbs 24 IN – 9 lbs 36 IN – 13 lbs 48 IN – 17 lbs
Power Class 2, 120-277 AC input, 24VDC output	Mounting Mounted to wall using provided wood screws	Certifications cUL, UL, CE, Title 24, Damp Location Rated		

MORE INFORMATION & OPTIONS

Designer Miren Lasnier at Juniper	Length Options 12 IN 24 IN 36 IN 48 IN 2.5 IN x 5 IN Profile	Color Temperature Options 2700K 3000K 3500K 4000K	Finish Options Satin Brass Polished Brass Black Oxide Antique Pewter Black Walnut Grey-Stained Ash	Dimming Options 2-Wire/TRIAC/Forward-Phase 0-10V 3-Wire/Ecosystem
---	--	--	---	---

Power Supply Options
 L. Standard Local 120-277V |
 2-Wire/TRIAC/Forward-Phase, 0-10V, ELV
 Dimming/Reverse-Phase
 R. Standard Remote
 120-277V | 0-10V Dimming
 R. Standard Remote
 120-277V | ELV Dimming
 R. Standard Remote 120V |
 2-Wire/TRIAC/Forward-Phase
 R. Standard Remote 277V |
 2-Wire/TRIAC/Forward-Phase
 R. Lutron Remote 120-277V |
 3-Wire, Digital Ecosystem
 Dimming | Hi-Lume Series
 R. Lutron Remote 120V |
 2-Wire/TRIAC/Forward-Phase
 Dimming | Hi-lume
 Series