



THIN SOLIDS CUBE by Juniper

SPECIFICATIONS

Typical Lead Time
6-8 Weeks

Mounting
1 Mounting Point

Segment Length
18 in [45.7 cm]

Color / Finish
Satin Brass

Color Temperature
3000K

Lens Finish
Frosted

Power Supply
R. Standard Remote
120-277V | 0-10V Dimming

Canopy
5" Cover Plate - Remote
Power Only

Total Wattage & Lumens/Fixture
12 IN - 40.8W, 0-3600LM
18 IN - 61.2W, 0-5400LM
24 IN - 81.6W, 0-7200LM

Light Quality
CRI 95+, R9 90+

LED Lifespan
50,000 hrs, L80

Body Material
Solid Brass, PMMA

Weight
12 IN - 7 lbs
18 IN - 8 lbs
24 IN - 9 lbs

Power
24VDC output Class 2
constant voltage power
supply
120VAC input voltage

Mounting
(x1, x2, or x4) 1/16" aircraft
cables, field adjustable
16ft Clear-jacketed 22AWG
co-axial silver cord, field
adjustable
1, 2, or 4 mounting point
options

Certifications
cUL, UL, CE, Damp Location
Rated, Title 24

MORE INFORMATION & OPTIONS

Designer
Peter Bristol

Length Options
12 IN (22.9 IN Diagonal)
18 IN (31.3 IN Diagonal)
24 IN (39.6 IN Diagonal)

Color Temperature Options
2700K
3000K
3500K
4000K

Finish Options
Satin Brass
Satin Nickel
Black Oxide

Dimming Options
2-Wire/TRIAC/Forward
Phase
0-10V
3-Wire/Ecosystem

Power Supply Options
L. Standard Local 120-277V |
2-Wire/TRIAC/Forward-Phase,
0-10V, ELV
Dimming/Reverse-Phase
R. Standard Remote
120-277V | 0-10V Dimming
R. Standard Remote
120-277V | ELV Dimming
R. Standard Remote 120V |
2-Wire/TRIAC/Forward-Phase
R. Standard Remote 277V |
2-Wire/TRIAC/Forward-Phase
R. Lutron Remote 120-277V |
3-Wire, Digital Ecosystem
Dimming | Hi-lume Series

Canopy Options
7" Local Canopy for Local
Power <54W
12.5" Local Canopy for
Local Power >55W
5" Cover Plate for Remote
Power
Remote Power Cord
Gripper