



## THIN SOLIDS CUBE by Juniper

### SPECIFICATIONS

**Typical Lead Time**  
6-8 Weeks

**Mounting**  
1 Mounting Point

**Segment Length**  
24 in [61 cm]

**Color / Finish**  
Satin Brass

**Color Temperature**  
3000K

**Lens Finish**  
Frosted

**Power Supply**  
R. Standard Remote  
120-277V | 0-10V Dimming

**Canopy**  
5" Cover Plate - Remote  
Power Only

**Total Wattage & Lumens/Fixture**  
12 IN - 40.8W, 0-3600LM  
18 IN - 61.2W, 0-5400LM  
24 IN - 81.6W, 0-7200LM

**Light Quality**  
CRI 95+, R9 90+

**LED Lifespan**  
50,000 hrs, L80

**Body Material**  
Solid Brass, PMMA

**Weight**  
12 IN - 7 lbs  
18 IN - 8 lbs  
24 IN - 9 lbs

**Power**  
24VDC output Class 2  
constant voltage power  
supply  
120VAC input voltage

**Mounting**  
(x1, x2, or x4) 1/16" aircraft  
cables, field adjustable  
16ft Clear-jacketed 22AWG  
co-axial silver cord, field  
adjustable  
1, 2, or 4 mounting point  
options

**Certifications**  
cUL, UL, CE, Damp Location  
Rated, Title 24

### MORE INFORMATION & OPTIONS

**Designer**  
Peter Bristol

**Length Options**  
12 IN (22.9 IN Diagonal)  
18 IN (31.3 IN Diagonal)  
24 IN (39.6 IN Diagonal)

**Color Temperature Options**  
2700K  
3000K  
3500K  
4000K

**Finish Options**  
Satin Brass  
Satin Nickel  
Black Oxide

**Dimming Options**  
2-Wire/TRIAC/Forward  
Phase  
0-10V  
3-Wire/Ecosystem

**Power Supply Options**  
L. Standard Local 120-277V |  
2-Wire/TRIAC/Forward-Phase,  
0-10V, ELV  
Dimming/Reverse-Phase  
R. Standard Remote  
120-277V | 0-10V Dimming  
R. Standard Remote  
120-277V | ELV Dimming  
R. Standard Remote 120V |  
2-Wire/TRIAC/Forward-Phase  
R. Standard Remote 277V |  
2-Wire/TRIAC/Forward-Phase  
R. Lutron Remote 120-277V |  
3-Wire, Digital Ecosystem  
Dimming | Hi-lume Series

**Canopy Options**  
7" Local Canopy for Local  
Power <54W  
12.5" Local Canopy for  
Local Power >55W  
5" Cover Plate for Remote  
Power  
Remote Power Cord  
Gripper