

Questions? Comments? Get in touch with us, or snap a shot of yourself enjoying your new sofa and tag us:

HAPPY@ELEPHANTINABOX.COM ELEPHANTINABOX.COM @ELEPHANT.INABOX





ELEPHANT IN A BOX

SOFA SET-UP INSTRUCTIONS

INSIDE THE BOX YOU WILL FIND:

- Sofa Body Elephant CoreBlue wooden beams (2 pieces)
- Black wooden beams (2 pieces)
- Base Lining
- Thumb screws & Wing nuts (8 Pieces)
- Back Lining (2 Pieces)
- Front Panel
- Seat Cushions (2 pieces)
- Back cushions (2 pieces)
- Stopper Screws & Nuts (4 pieces)
- Back Covers (2 pieces)
- Armrests (2 pieces, attached)Set of 4 straps (for future moving)
- Wing Screws (4 pieces)
- Braces



Open the box.



Push the cushion, then twist and remove the wooden support.



Take the cushions out by using the belt.




Expand the sofa honeycomb by pulling outwards on the armrests in a straight line.



Expand the beams.




Slide the connectors to the middle to lock the beams.



Now, insert the stopper screw in the hole as shown. Make sure that the stopper screw is in the same direction of the hinge.



Do the same for the black beams and make sure that the nut is in the same direction of the hinge.



Place the blue wood beam inside the blue connectors on the front part of the honeycomb and make sure to place the middle support with the middle connector as shown.



Rotate the thumb screw with the wing nut together.



Do the same for the other blue wood beam. See image No. 9



Put the base lining on the sofa with the velcro facing up.

ELEPHANT IN A BOX

SOFA SET-UP INSTRUCTIONS



Make sure to align the ring on the base lining with the hole on the blue connectors.



Insert the black screw in the base lining ring and rotate it with the wing nut.



The final look of the base lining.



Place the black wood beams inside the black connectors at the bottom of the armrests (front and back). Make sure that the velcro is facing down.



Place both back lining pieces on at the same time, starting from a V shape. This will make them fit tighter.



Stick the front panel onto the base lining and the bottom beam by the velcro.



Place the seat cushions as shown.



Stretch and "fluff" the back pillows, they've been cozy for a while:)



Now relax!