

Perfect for transferring sawdust, bark or chips from one place to another, the **Barn Sweep Conveyor** is ideal when coupled with our Rosserhead Debarker. Constructed from 10-gauge formed steel pan and 5" x 5" (12.7 cm x 12.7 cm) square tubing, the barn sweep conveyor can be made up to 150' (45.7 m) level or 100' (30.5 m) upright.

FEATURES AND BENEFITS

- 5'–150' level (1.5 m 45.7 m), 5'–10' (1.5 m 3.05 m) upright barn sweep style conveyor
- 0.625" (1.6 cm) oval link chain with flites on 2' (0.6 m) centers (standard), other options available
- Constructed from 10-gauge formed steel pan and 5" x 5" (12.7 cm x 12.7 cm) square tubing
- 2.44" (6.2 cm) head shaft, tail shaft and idler shaft
- Heavy-duty tubular steel leg package with discharge height of 15' (4.6 m)
- Rexnord gear reducer 25 to 1 reduction
- Chain speed approximately 30 FPM (9.1 m/min)
- 3-hp (2.2-kW), 1800 RPM electric motor
- Ratchet-type chain tensioner





SPECIFICATIONS	US	METRIC
Length (level)	25'	7.6 m
Length (upright)	30'	9.1 m
Motor	3 HP	2.2 kW

OPTIONS INCLUDE

- Up to 150' (45.7 m) level or 100' (30.5 m) upright Hydraulic drive in lieu of standard
- Chain options
- Discharge height options

